Crimp Terminal

Tubular





Specifications:

Maximum electric current

Maximum electrical rating Insulation material Insulation colour

Terminal material Packing

:	AWG	22	20	18	16	14	12	10
	Amperes	9	12	17	18	30	35	50


: 105°C 600 volts.

: Nylon.

: Red (22 to 16 AWG) : Blue (16 to 14 AWG).

: Copper.

: 100 pieces.



Dimensions : Inches (Millimetres)

Specification Table

Wire Range AWG	Dimensions			Material	Crimping	Part Number
(mm ²)	L	D	d1	Material	ΤοοΙ	Fait Nullibel
22 to 16 (0.5 to 1.5)	1.220 (31.00)	0.157 (4.00)	0.071 (1.80)	Copper Tubular	K.S. Model KST2000B With Die Index Colour : Red	WBNY1
16 to 14 (1.5 to 2.5)	1.220 (31.00)	0.181 (4.60)	0.098 (2.50)		K.S. Model KST2000B With Die Index Colour : Blue	WBNY2

Dimensions : Inches (Millimetres)

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheets previously for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC Multicomp is the registered trademark of the Group. © Premier Farnell plc 2009.

http://www.farnell.com http://www.newark.com http://www.cpc.co.uk

