



Product Change Notification / LIAL-15QPNY176

Date:

19-Jan-2021

Product Category:

Instrumentation Amplifier, Linear Op Amps, Memory, Temperature Sensors

PCN Type:

Manufacturing Change

Notification Subject:

CCB 4506 Initial Notice: Qualification of MMT as an additional assembly site for selected products available in 8L TDFN (2x3x0.8mm) package.

Affected CPNs:

[LIAL-15QPNY176_Affected_CPN_01192021.pdf](#)

[LIAL-15QPNY176_Affected_CPN_01192021.csv](#)

Notification Text:

PCN Status:Initial notification.

PCN Type: Manufacturing Change

Microchip Parts Affected:Please open one of the icons found in the Affected CPNs section above.

NOTE: For your convenience Microchip includes identical files in two formats (.pdf and .xls).

Description of Change: Qualification of MMT as an additional assembly site for selected products available in 8L TDFN (2x3x0.8mm) package.

Pre Change:

Assembled at NSEB using gold (Au) bond wire or palladium coated copper with gold flash (CuPdAu) bond wire and 8200T die attach or 8600 die attach material.

Post Change:

Assembled at NSEB using gold (Au) bond wire or palladium coated copper with gold flash (CuPdAu) bond wire and 8200T die attach or 8600 die attach material or assembled at MMT using palladium coated copper with gold flash (CuPdAu) bond wire and 3280 die attach material.

Pre and Post Change Summary:

	Pre Change		Post Change		
Assembly Site	UTAC Thai Limited (UTL-1) LTD. NSEB		UTAC Thai Limited (UTL-1) LTD. NSEB		Microchip Technology Thailand (Branch)/ MMT
Wire material	Au	CuPdAu	Au	CuPdAu	CuPdAu
Die attach material	8200T	8600	8200T	8600	3280
Molding compound material	G700LTD		G700LTD		G700LTD
Lead frame material	A194		A194		A194
Lead Frame Lead Lock	No		No		No

Impacts to Data Sheet:None

Change Impact:None

Reason for Change:To improve on-time delivery performance by qualifying MMT as an additional assembly site.

Change Implementation Status:In Progress

Estimated Qualification Completion Date:February 2021

Note: Please be advised the qualification completion times may be extended because of unforeseen business conditions however implementation will not occur until after qualification has completed and a final PCN has been issued. The final PCN will include the qualification report and estimated first ship date. Also note that after the estimated first ship date guided in the final PCN customers may receive pre and post change parts.

Time Table Summary:

	December 2020					-->	February 2021				
Workweek	49	50	51	52	53		05	06	07	08	09
Initial PCN Issue Date				X							
Qual Report Availability										X	
Final PCN Issue Date										X	

Method to Identify Change: Traceability code

Qualification Plan Please open the attachments included with this PCN labeled as PCN_#_Qual_Plan.

Revision History:December 21, 2020: Issued initial notification.**January 19, 2021:** Re-issued initial notification to update the pre and post change summary to correct the lead frame lead lock of NSEB from Yes to No.

The change described in this PCN does not alter Microchip's current regulatory compliance regarding the material content of the applicable products.

Attachments:

[PCN_LIAL-15QPNY176_Pre and Post Change Lead frame comparison Rev 1.pdf](#)
[PCN_LIAL-15QPNY176_Qual Plan.pdf](#)

Please contact your local [Microchip sales office](#) with questions or concerns regarding this notification.

Terms and Conditions:

If you wish to receive Microchip PCNs via email please register for our PCN email service at our [PCN home page](#) select register then fill in the required fields. You will find instructions about registering for Microchips PCN email service in the [PCN FAQ](#) section.

If you wish to change your PCN profile, including opt out, please go to the [PCN home page](#) select login and sign into your myMicrochip account. Select a profile option from the left navigation bar and make the applicable selections.

Affected Catalog Part Numbers (CPN)

MCP6V77T-E/MNY
24LC32AT-I/MNY
24AA32AT-I/MNY
93LC46AT-I/MNY
93AA46AT-I/MNY
93LC46AT-E/MNY
93LC46BT-I/MNY
93AA46BT-I/MNY
93LC46BT-E/MNY
93C46BT-I/MNY
93C46BT-E/MNY
93C46AT-I/MNY
93C46AT-E/MNY
93LC46CT-I/MNY
93AA46CT-I/MNY
93LC46CT-E/MNY
93LC56CT-I/MNY
93AA56CT-I/MNY
93LC56AT-I/MNY
93AA56AT-I/MNY
93LC56BT-I/MNY
93AA56BT-I/MNY
93LC56CT-E/MNY
93LC56AT-E/MNY
93LC56BT-E/MNY
93LC66CT-I/MNY
93AA66CT-I/MNY
93LC66AT-I/MNY
93AA66AT-I/MNY
93C86CT-E/MNY
25AA320AT-I/MNY100
25AA320AT-I/MNY101
25LC320AT-I/MNY
25AA320AT-I/MNY
25AA320AT-I/MNYB23
25LC320AT-E/MNY
25LC160D-E/MNY
25LC160D-I/MNY
25AA160D-I/MNY
25LC160DT-I/MNY
25AA160DT-I/MNY
25AA160DT-I/MNY-PR
25LC160DT-E/MNY
25AA160DT-E/MNY
25AA160DT-E/MNY-PR
25LC080D-E/MNY

25LC080D-I/MNY
25AA080D-I/MNY
25LC080DT-I/MNY
25AA080DT-I/MNY
25LC080DT-E/MNY
25LC160C-E/MNY
25LC160C-I/MNY
25AA160C-I/MNY
25LC160CT-I/MNY
25AA160CT-I/MNY
25LC160CT-E/MNY
25LC080C-E/MNY
25LC080C-I/MNY
25AA080C-I/MNY
25LC080CT-I/MNY
25AA080CT-I/MNY
25LC080CT-E/MNY
25LC640AT-I/MNY
25AA640AT-I/MNY
25LC640AT-E/MNY
25AA640AT-E/MNY
25LC010AT-I/MNY
25AA010AT-I/MNY
25LC010AT-E/MNY
25LC020AT-I/MNY
25AA020AT-I/MNY
25LC020AT-E/MNY
25LC040AT-I/MNY
25AA040AT-I/MNY
25LC040AT-E/MNY
MCP98242T-BE/MNY
MCP98242T-BE/MNYBA2
MCP98242T-BE/MNYBA3
MCP98242T-BE/MNYBAA
MCP98242T-BE/MNYAB
MCP98242T-BE/MNYBAC
MCP98242T-BE/MNYBAE
MCP98242T-BE/MNYBAF
24LC08BT-I/MNY
24AA08T-I/MNY
24LC08BT-E/MNY
24LC08BHT-I/MNY
24AA08HT-I/MNY
24LC08BHT-E/MNY
24LC16BT-I/MNY
24AA16T-I/MNY
24LC16BT-E/MNY
24AA16T-E/MNY
24LC16BHT-I/MNY

24AA16HT-I/MNY
24LC16BHT-E/MNY
24LC32AT-I/MNYA29
24LC32AT-E/MNY
24LC32AFT-I/MNY
24AA32AFT-I/MNY
24LC32AFT-E/MNY
24AA64T-I/MNY102
24AA64T-I/MNY104
24AA64T-I/MNY105
24AA64T-I/MNY106
24LC64T-I/MNY
24AA64T-I/MNY
24FC64T-I/MNY
24LC64T-E/MNY
24AA64T-E/MNY
24LC64FT-I/MNY106
24LC64FT-I/MNY
24AA64FT-I/MNY
24FC64FT-I/MNY
24LC64FT-E/MNY
24LC128T-I/MNY
24AA128T-I/MNY
24FC128T-I/MNY
24LC128T-E/MNY
24LC04BT-I/MNY
24AA04T-I/MNY
24LC04BT-E/MNY
24LC04BHT-I/MNY
24AA04HT-I/MNY
24LC04BHT-E/MNY
MCP6N11T-001E/MNY
MCP6N11T-002E/MNY
MCP6N11T-005E/MNY
MCP6N11T-010E/MNY
MCP6N11T-100E/MNY
MCP98243T-BE/MNY
93LC66BT-I/MNY
93AA66BT-I/MNY
93LC66CT-E/MNY
93LC66AT-E/MNY
93LC66BT-E/MNY
93C46CT-I/MNY
93C46CT-E/MNY
93C56CT-I/MNY
93C56AT-I/MNY
93C56BT-I/MNY
93C56CT-E/MNY
93C56AT-E/MNY

93C56BT-E/MNY
93C66CT-I/MNY
93C66AT-I/MNY
93C66BT-I/MNY
93C66CT-E/MNY
93C66AT-E/MNY
93C66BT-E/MNY
93LC76CT-I/MNY
93AA76CT-I/MNY
93LC76CT-E/MNY
93LC86CT-I/MNY
93AA86CT-I/MNY
93LC86CT-E/MNY
93C76CT-I/MNY
93C76CT-E/MNY
93C86CT-I/MNY
MCP98243T-BE/MNYAA
MCP98243T-BE/MNYAB
MCP98208T-E/MNY-GLW08
MCP9843T-BE/MNY
MCP6482T-E/MNY
MCP6492T-E/MNY
MCP6472T-E/MNY
34AA04T-I/MNY
34AA04T-E/MNY
MCP6V12T-E/MNY
MCP6V17T-E/MNY
MCP6V32T-E/MNY
MCP6V37T-E/MNY
MCP6V82T-E/MNY
MCP6V87T-E/MNY
MCP6V92T-E/MNY
MCP6V62T-E/MNY
MCP6V67T-E/MNY
MCP6V72T-E/MNY



MICROCHIP

QUALIFICATION PLAN SUMMARY

PCN#: LIAL-15QPNY176

December 10, 2020

Qualification of MMT as an additional assembly site for selected products available in 8L TDFN (2x3x0.8mm) package.

Purpose: Qualification of MMT as an additional assembly site for selected products available in 8L TDFN (2x3x0.8mm) package.

<u>Misc.</u>	Assembly site	MMT
	BD Number	BDM-002777
	CCB#	4506
	MP Code (MPC)	D5AP1Y5QXB00
	Part Number (CPN)	25AA640AT-E/MNY
	MSL information	MSL-1@260C
	Assembly Shipping Media (T/R, Tube/Tray)	Tube
	Base Quantity Multiple (BQM)	3300
	Reliability Site	MTAI
<u>Lead-Frame</u>	Paddle size	83x71
	Material	A194
	DAP Surface Prep	NiPdAu (PPF)
	Treatment	Rough PPF (ME2)
	Process	Etched
	Lead-lock	No
	Part Number	10100853
	Lead Plating	NiPdAu (PPF)
	Strip Size	250x70mm
	Strip Density	1690 units/Strip
<u>Bond Wire</u>	Material	CuPdAu
<u>Die Attach</u>	Part Number	3280
	Conductive	Yes
<u>Mold Compound</u>	Part Number	G700LTD
<u>PKG</u>	PKG Type	TDFN
	Pin/Ball Count	8
	PKG width/size	2x3x0.8mm

Test Name	Conditions	Sample Size	Min. Qty of Spares per Lot (should be properly marked)	Qty of Lots	Total Units	Fail Accept Qty	Special Instructions
Standard Pb-free Solderability	J-STD-002D ; Perform 8 hour steam aging for Matte tin finish and 1 hour steam aging for NiPdAu finish prior to testing. Standard Pb-free: Matte tin/ NiPdAu finish, SAC solder, wetting temp 245°C for both SMD & through hole packages.	22	5	1	27	> 95% lead coverage	Standard Pb-free solderability is the requirement. SnPb solderability (backward solderability-SMD reflow soldering) is required for any plating related changes and highly recommended for other package BOM changes.
Backward Solderability	J-STD-002D ;Perform 8 hours steam aging for Matte tin finish and 1 hour steam aging for NiPdAu finish prior to testing. Backward: Matte tin/ NiPdAu finish, SnPb solder, wetting temp 215°C for SMD.	22	5	1	27	> 95% lead coverage	
Wire Bond Pull - WBP	Mil. Std. 883-2011	5	0	1	5	0 fails after TC	30 bonds from a min. 5 devices.
Wire Bond Shear - WBS	CDF-AEC-Q100-001	5	0	1	5	0	30 bonds from a min. 5 devices.
Wire Sweep							Required for any reduction in wire bond thickness.
Physical Dimensions	Measure per JESD22 B100 and B108	10	0	3	30	0	
External Visual	Mil. Std. 883-2009/2010	All devices prior to submission for qualification testing	0	3	ALL	0	
Preconditioning - Required for surface mount devices	+150°C Bake for 24 hours, moisture loading requirements per MSL level + 3X reflow at peak reflow temperature per Jedec-STD-020E for package type; Electrical test pre and post stress at +25°C. and hot MSL-1 @260	231	15	3	738	0	Spares should be properly identified. 77 parts from each lot to be used for HAST, uHAST, Temp Cycle test.
HAST	+130°C/85% RH for 96 hours or 110°C/85%RH for 264 hours. Electrical test pre and post stress at +25°C and hot temp. 2X Extended stress Max temp testing at 125C.	77	5	3	246	0	Spares should be properly identified. Use the parts which have gone through Pre-conditioning.
UHAST	+130°C/85% RH for 96 hrs or +110°C/85% RH for 264 hrs. Electrical test pre and post stress at +25°C 2X Extended stress Max temp testing at 125C.	77	5	3	246	0	Spares should be properly identified. Use the parts which have gone through Pre-conditioning.

Test Name	Conditions	Sample Size	Min. Qty of Spares per Lot (should be properly marked)	Qty of Lots	Total Units	Fail Accept Qty	Special Instructions
Temp Cycle	<p>-65°C to +150°C for 500 cycles. Electrical test pre and post stress at hot temp; 3 gram force WBP, on 5 devices from 1 lot, test following Temp Cycle stress.</p> <p>2X Extended stress Max temp testing at 125C.</p>	77	5	3	246	0	Spares should be properly identified. Use the parts which have gone through Pre-conditioning.

CCB 4506
Pre and Post Change Lead Frame Comparison
PCN # LIAL-15QPNY176





A Leading Provider of Smart, Connected and Secure Embedded Control Solutions



SMART | CONNECTED | SECURE

Lead frame comparison

Pre change	Post Change				
NSEB	MMT				
<p data-bbox="267 472 1072 1063"></p> <table border="1" data-bbox="287 1082 1049 1159"><tr><td>Lead frame lead-lock</td><td>No</td></tr></table>	Lead frame lead-lock	No	<p data-bbox="1508 472 2288 1063"></p> <table border="1" data-bbox="1508 1082 2280 1159"><tr><td>Lead frame lead-lock</td><td>No</td></tr></table>	Lead frame lead-lock	No
Lead frame lead-lock	No				
Lead frame lead-lock	No				