

PRODUCT-DETAILS

BI-F-4.0.1

BI-F-4.0.1 Binary Input, 4-fold, FM



General Information Extended Product Type BI-F-4.0.1 Product ID 2CDG510003R0011 EAN 4016779941884 Catalog Description BI-F-4.0.1 Binary Input, 4-fold, FM 4 channels can be connected with conventional push-buttons or auxiliary contacts. The information of contact scanning can be used to control free@home actuators or for indicate status inforamtion. The contact scanning voltage are made available by Long Description binary input device. The devices are supplied by free@home bus, there is no additional power supply neccessary. The compact design allows the installation of conventionell $% \left(1\right) =\left(1\right) \left(1\right) \left($ 60 mm installation box or device box.

Ordering	
EAN	4016779941884
Customs Tariff Number	85389091
Minimum Order Quantity	1 piece
E-Number (Sweden)	1701116

Dimensions	
Product Net Depth / Length	40 mm
Product Net Height	12 mm
Product Net Width	39 mm
Product Net Weight	0.044 kg

BI-F-4.0.1

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 EAN	4016779941884
Package Level 1 Depth / Length	23 mm
Package Level 1 Height	65 mm
Package Level 1 Width	92 mm
Package Level 1 Gross Weight	0.06 kg

Data Sheet, Technical Information	2CDG941151P0002
Instructions and Manuals	2CDG941151P0002
Declaration of Conformity - CE	2CDK504096D2701
RoHS Information	2CDK504096D2701

Environmental	
RoHS Status	Following EU Directive 2011/65/EU

Classifications	
ETIM 5	EC000688 - Binary input for bus system
ETIM 6	EC000688 - Binary input for bus system
ETIM 7	EC000688 - Binary input for bus system
eClass	7.0 27143121
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Home\ and\ Building\ Automation \rightarrow free@home \rightarrow Standard\ Inputs \rightarrow Binary\ Inputs,\ Contact\ Scanning$





