

TECHNICAL DATA SHEET

PRO-ELEC

RoHS
Compliant

UK MAINS TO INDUSTRIAL EXTENSIONS LEADS

**MODELS:
PELB0137-PELB0139**



SPECIFICATIONS

Model List:

Model	Connector	Pins	Amps	Voltage	Cable	Length	Colour
PELB0137	1-gang, 13A plug to 16A socket	2P+E	16A	230V	1.5mm ²	350mm	Blue
PELB0138	1-gang, 13A socket to 16A plug						
PELB0139	2-gang, 13A socket to 16A plug						

Important Notice: This data sheet and its contents (the "Information") belong to pro-ELEC. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-ELEC assumes no responsibility for its accuracy or completeness any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-ELEC was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-ELEC's liability for death or personal injury resulting from its negligence.

PRO-ELEC

TECHNICAL DATA SHEET

PRO-ELEC

RoHS
Compliant

Construction:

Description	Material
Plug/socket base and cover:	PA
Plug/socket pins and connector:	Brass
Flexible cable:	H05VV-F 3x 1.5mm ²

Standard:

Compliant with EN60309-2

Conditions of Use:

- A. Ambient temperature in the range -5°C to +40°C, the average value over 24 hours not exceeding 25°C
- B. A situation not subject to exposure to direct radiation from the sun or other source of heat like to raise temperatures above the limits specified in A.
- C. Altitude not exceeding 2,000m above sea level
- D. Atmosphere not subject to abnormal pollution by smoke, chemical fumes, rain, spray, prolonged periods of high humidity or other abnormal conditions

Test Report/Certificate:

Plug: COC No. OP190103.WZE0055 issued by ECM
Coupler and socket: COC No. OP190103.WZE0056 issued by ECM
PVC cable: VDE approval 40006717

Important Notice: This data sheet and its contents (the "Information") belong to pro-ELEC. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-ELEC assumes no responsibility for its accuracy or completeness any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-ELEC was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-ELEC's liability for death or personal injury resulting from its negligence.

PRO-ELEC