

PCB Connector, Header

multicomp PRO

**RoHS
Compliant**




Specifications:

Pitch	: 5.08mm
Poles	: 2 to 24Poles
Housing Material	: PA 66
Pin Dimensions	: Brass, Tin Plated
PCB Hole Diameter	: 1.5mm
Operating Temperature	: -40°C to +105°C

Technical Data:

Nominal Current I_N	: 16A
Nominal Cross Section	: -
Maximum Load Current	: 16A
Insulating Material	: PA
Nominal Voltage	: 300V
Nominal Current	: 16A

Diagram



PCB Layout

Dimensions : Millimetres (Inches)

Part Number Table

Description	Part Number
Term Block, Header, 5.08mm	MCTE-03D11
	ME030-50802
	ME030-50803
	ME030-50804
	ME030-50805
	ME030-50806
	ME030-50807
	ME030-50808
	ME030-50809
	ME030-50810
ME030-50812	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO