



Features

- It de-waters, protects against corrosion, lubricates and prevents squeaks on moving parts
- It quickly frees rusted and seized components

Applications

Provides a 'one-stop' solution to the problems caused by water ingress and corrosion through out most industrial applications. Equally suitable for use in automotive, mechanical and electrical maintenance applications. The highly effective water displacing properties make it an ideal 'damp-start' solution for ignition systems. The protective film is non-conductive and operates at sub zero temperatures. It is safe to use on all metals, plastics and painted finishes.

Directions

Spray from 20cm to 30cm and allow film to penetrate before proceeding.

Technical Information

Appearance	Amber coloured liquid
Odour	White spirit
SG at 25°C	0.79
Pressure at 25°C	5 Bar (Aerosol)
Discharge Rate	1.2g/second (Aerosol)
Temperature Range	Operational from -20°C to +115°C
Flammability	Classified as extremely flammable under CHIP regulations
Flash Point	Not applicable in sealed Aerosol

Storage

The product may be stored at normal temperatures and has a shelf life of not less than 36 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flames.

Note:

Not suitable for use on live electrical equipment.

Part Number Table

Description	Part Number
Lubricant, WD, 400ml, Aerosol	PPC111

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.