

8451 Equivalent 2 Core LSF Cable




**RoHS
Compliant**



Category Type	8451 LSF GREY					
Test Standard	UL1581,UL758					
Conductor	Material	Stranded Tinned Copper				
	Nom.O.D.(mm)	0.25 × 7	<table border="1"> <tr> <td>Up</td> <td>+0.008</td> </tr> <tr> <td>Down</td> <td>-0.008</td> </tr> </table>	Up	+0.008	Down
Up	+0.008					
Down	-0.008					
Insulation	Material	SPP				
	Diameter	1.20 (±0.13)mm × 2				
Color	Black,Red					
Rip-cord	Material	Nylon				
	Colour	White				
Shield	Material	Mylar				
	Colour	Transparent				
Drain	Material	Stranded Tinned Copper				
	Nom.O.D.(mm)	0.25 × 7	<table border="1"> <tr> <td>Up</td> <td>+0.008</td> </tr> <tr> <td>Down</td> <td>-0.008</td> </tr> </table>	Up	+0.008	Down
Up	+0.008					
Down	-0.008					
Shield	Material	AL-foil				
	Color	Blue				
Rip-cord	Material	Nylon				
	Colour	White				
Sheath	External O.D.	3.50(±0.18)mm				
	Surface	Clean,Smooth				
	Material	LSF-PVC				
	Colour	Grey				

Cable Diagram



Characteristics		
Item	Description	Standard
Cond. Resistance A	20°C, Conductor DC Resistance	< 6.02 Ω/100M
Min.Insulation DC Resistance	20°C,Insulation DC Resistance	> 200 MΩ*M
Rated Voltage	-----	300V
Rated Temperature(°C)	-----	80°C

Part Number Table

Description	Part Number
LSF Cable, 2 Core, Single Pair, Grey, 100m	PELB1104

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-ELEC is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands
Farnell.com/exclusive-brands
Element14.com/exclusive-brands

