


TECHNICAL DATA SHEET

PRO-ELEC

Cable Ties - Black and Natural CB20642-771

**RoHS
Compliant**

Materials Used	
Main component	Nylon 66 (flammability: 94V-2 to UL standard)
Main Features	
Operating Temperature: -40 ~ +85°C	
RoHS Compliant	
REACH Compliant	



External Width	External Length	Max. Bundle Dia.	Min. Loop Tensile Strength		Pack Size	Colour	Part Number
			lbs	kgs			
mm	mm	mm			pcs		
1.8	100	22	14	6.5	100	Natural	CT1.8-100NAT100PK
1.8	100	22	14	6.5	100	Black	CT1.8-100BLK100PK
2.5	60	11	18	8	100	Natural	CT2.5-60NAT100PK
2.5	60	11	18	8	100	Black	CT2.5-60BLK100PK
2.5	80	16	18	8	100	Natural	CT2.5-80NAT100PK
2.5	80	16	18	8	100	Black	CT2.5-80BLK100PK
2.5	100	22	18	8	100	Natural	CT2.5-100NAT100PK
2.5	100	22	18	8	1000	Black	CT2.5-100NAT1000PK
2.5	100	22	18	8	100	Natural	CT2.5-100BLK100PK
2.5	100	22	18	8	1000	Black	CT2.5-100BLK1000PK
2.5	120	28	18	8	100	Natural	CT2.5-120NAT100PK
2.5	120	28	18	8	100	Black	CT2.5-120BLK100PK
2.5	140	33	18	8	100	Natural	CT2.5-140NAT100PK
2.5	140	33	18	8	1000	Black	CT2.5-140NAT1000PK
2.5	140	33	18	8	100	Natural	CT2.5-140BLK100PK
2.5	140	33	18	8	1000	Black	CT2.5-140BLK1000PK
2.5	150	35	18	8	100	Natural	CT2.5-150NAT100PK
2.5	150	35	18	8	100	Black	CT2.5-150BLK100PK
2.5	160	40	18	8	100	Natural	CT2.5-160NAT100PK
2.5	160	40	18	8	100	Black	CT2.5-160BLK100PK
2.5	200	53	18	8	100	Natural	CT2.5-200NAT100PK
2.5	200	53	18	8	1000	Black	CT2.5-200NAT1000PK
2.5	200	53	18	8	100	Natural	CT2.5-200BLK100PK
2.5	200	53	18	8	1000	Black	CT2.5-200BLK1000PK

Important Notice : This data sheet and its contents (the "Information") belong to pro-ELEC. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-ELEC assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-ELEC was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-ELEC's liability for death or personal injury resulting from its negligence.

PRO-ELEC