PCB Terminal Block





Specifications

Connection in Acc. with standard EN-VDE

Nominal Current IN : 16Amp
Nominal Cross Section : 2.5mm²
Maximum load current : 16A
Insulating Material : PA

Dimensions

Pitch : 5.08mm
Poles : 3
Housing Material : PA 66

Cage Clamp : Brass, Ni Plated
Contact : Brass, Tin Plated
Screw Thread : M2.6, Steel, Zinc Plated
Wire Size : 12AWG to 26AWG


Wire Strip Length : 7mm


PCB Hole Diameter : 1.5mm


Tightening Torque : 5lb-inch Max.

Operating Temperature : -40°C to +105°C

Diagram







Dimensions: Millimetres (Inches)

Part Number Table

| Description | Part Number |
|---|-------------|
| PCB Terminal Block, 5.08mm, Modular Type, 16A 300V, 3 poles | MC002066 |

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

