PCN # 2097\_ADDENDUM DATE: November 13, 2020

EXPECTED PCN SHIP DATE: November 13, 2020



Quality Assurance 160 Rio Robles San Jose, CA 95134

www.maximintegrated.com

## PROCESS CHANGE NOTICE X PRODUCT CHANGE NOTICE

## **MAXIM INTEGRATED** HEREBY ISSUES NOTIFICATION OF CHANGE THAT MAY AFFECT THE FOLLOWING CATEGORIES:

AFFECTED PRODUCT:         Ordering P/N: (See PN listing XLS in PCN ZIP file)         CHANGE FROM: This is an Addendum to PCN 2097 issued November 2, 2020 with updated limits for breakdown voltages         Datasheet Correction for MAX20067       CHANGE TO: -         Existing Datasheet revision: 19-100112; Rev 0; 7/17       New Datasheet revision release         Absolute Maximum Ratings:       Absolute Maximum Ratings:         VGON, SRC, DRN, to GND: -0.3V to +38V       VGON, SRC, DRN, to GND: NEW RANGE -0.3V to +34V         DRN to GATES:       -38V to +38V         VGON Output Voltage range:       36V (max)         SRC Input Voltage shown above (See the attached datasheet markup file)         There are no other changes to the Form, Fit or function of these devices.         Note: This PCN is an Information Notice only and is effective immediately	DESIGN	WAFER FAB	ASSEMBLY		TEST	X ELEC/MECH SPECS	
CHANGE FROM: This is an Addendum to PCN 2097 issued       CHANGE TO: -         November 2, 2020 with updated limits for breakdown voltages       CHANGE TO: -         Datasheet Correction for MAX20067       New Datasheet revision release         Existing Datasheet revision: 19-100112; Rev 0; 7/17       New Datasheet revision release         Absolute Maximum Ratings:       Absolute Maximum Ratings:         VGON, SRC, DRN, to GND: -0.3V to +38V       DRN to GATES:         DRN to GATES:       -38V to +38V         EC table limits:       VGON Output Voltage range: 36V (max)         SRC Input Voltage Range:       36V (max)         JUSTIFICATION: Our internal breakdown voltage definition has been adjusted in the design rules which resulted in the new maximum voltages shown above (See the attached datasheet markup file)         There are no other changes to the Form, Fit or function of these devices.	AFFECTED PRODUCT:						
November 2, 2020 with updated limits for breakdown voltages Datasheet Correction for MAX20067 Existing Datasheet revision: 19-100112; Rev 0; 7/17 Absolute Maximum Ratings: VGON, SRC, DRN, to GND: -0.3V to +38V DRN to GATES: -38V to +38V EC table limits: VGON Output Voltage range: 36V (max) SRC Input Voltage Range: 0.50V	Ordering P/N: (See PN listing XLS in PCN ZIP file)						
November 2, 2020 with updated limits for breakdown voltages Datasheet Correction for MAX20067 Existing Datasheet revision: 19-100112; Rev 0; 7/17 Absolute Maximum Ratings: VGON, SRC, DRN, to GND: -0.3V to +38V DRN to GATES: -38V to +38V EC table limits: VGON Output Voltage range: 36V (max) SRC Input Voltage Range: 0.50V							
Datasheet Correction for MAX20067 Existing Datasheet revision: 19-100112; Rev 0; 7/17New Datasheet revision releaseAbsolute Maximum Ratings: VGON, SRC, DRN, to GND: -0.3V to +38V DRN to GATES: -38V to +38VAbsolute Maximum Ratings: 	CHANGE FROM: This is an Addendum to PCN 2097 issued			CHANGE TO: -			
Existing Datasheet revision: 19-100112; Rev 0; 7/17New Datasheet revision releaseAbsolute Maximum Ratings: VGON, SRC, DRN, to GND: -0.3V to +38VAbsolute Maximum Ratings: VGON, SRC, DRN, to GND: NEW RANGE -0.3V to +34V DRN to GATES: -38V to +38VAbsolute Maximum Ratings: VGON, SRC, DRN, to GND: NEW RANGE -0.3V to +34V DRN to GATES: NEW RANGE -34V to +34VEC table limits: VGON Output Voltage range: SRC Input Voltage Range:36V (max)EC table limits: VGON Output Voltage Range: SRC Input Voltage Range: NEW limit 32V (max) SRC Input Voltage shown above (See the attached datasheet markup file) There are no other changes to the Form, Fit or function of these devices.New Datasheet revision release	November 2, 2020 with updated limits for breakdown voltages						
Existing Datasheet revision: 19-100112; Rev 0; 7/17New Datasheet revision releaseAbsolute Maximum Ratings: VGON, SRC, DRN, to GND: -0.3V to +38VAbsolute Maximum Ratings: VGON, SRC, DRN, to GND: NEW RANGE -0.3V to +34V DRN to GATES: -38V to +38VAbsolute Maximum Ratings: VGON, SRC, DRN, to GND: NEW RANGE -0.3V to +34V DRN to GATES: NEW RANGE -34V to +34VEC table limits: VGON Output Voltage range: SRC Input Voltage Range:36V (max)EC table limits: VGON Output Voltage Range: SRC Input Voltage Range: NEW limit 32V (max) SRC Input Voltage shown above (See the attached datasheet markup file) There are no other changes to the Form, Fit or function of these devices.New Datasheet revision release							
Absolute Maximum Ratings:Absolute Maximum Ratings:VGON, SRC, DRN, to GND: -0.3V to +38VVGON, SRC, DRN, to GND: NEW RANGE -0.3V to +34VDRN to GATES:-38V to +38VEC table limits:VGON Output Voltage range: 36V (max)VGON Output Voltage Range:36V (max)SRC Input Voltage Range:36V (max)JUSTIFICATION: Our internal breakdown voltage definition has been adjusted in the design rules which resulted in the newmaximum voltages shown above (See the attached datasheet markup file)There are no other changes to the Form, Fit or function of these devices.	Datasheet Correction for MAX20067						
VGON, SRC, DRN, to GND:-0.3V to +38VVGON, SRC, DRN, to GND:NEW RANGE -0.3V to +34VDRN to GATES:-38V to +38VDRN to GATES:NEW RANGE -34V to +34VEC table limits:EC table limits:VGON Output Voltage range:36V (max)SRC Input Voltage Range:36V (max)SRC Input Voltage Range:NEW limit 32V (max)JUSTIFICATION: Our internal breakdown voltage definition has been adjusted in the design rules which resulted in the new maximum voltages shown above (See the attached datasheet markup file)There are no other changes to the Form, Fit or function of these devices.	Existing Datasheet revision: 19-100112; Rev 0; 7/17			New Datasheet revision release			
VGON, SRC, DRN, to GND:-0.3V to +38VVGON, SRC, DRN, to GND:NEW RANGE -0.3V to +34VDRN to GATES:-38V to +38VDRN to GATES:NEW RANGE -34V to +34VEC table limits:EC table limits:VGON Output Voltage range:36V (max)SRC Input Voltage Range:36V (max)SRC Input Voltage Range:NEW limit 32V (max)JUSTIFICATION: Our internal breakdown voltage definition has been adjusted in the design rules which resulted in the new maximum voltages shown above (See the attached datasheet markup file)There are no other changes to the Form, Fit or function of these devices.							
DRN to GATES:-38V to +38VDRN to GATES:NEW RANGE -34V to +34VEC table limits:EC table limits:EC table limits:VGON Output Voltage range:NEW limit 32V (max)SRC Input Voltage Range:36V (max)SRC Input Voltage Range:NEW limit 32V (max)JUSTIFICATION: Our internal breakdown voltage definition has been adjusted in the design rules which resulted in the newmaximum voltages shown above (See the attached datasheet markup file)There are no other changes to the Form, Fit or function of these devices.	Absolute Maximum Ratings:			Absolute Maximum Ratings:			
EC table limits:       EC table limits:         VGON Output Voltage range:       36V (max)         SRC Input Voltage Range:       36V (max)         SRC Input Voltage Range:       36V (max)         SRC Input Voltage Range:       NEW limit 32V (max)         There are no other changes to the Form, Fit or function of these devices.       There are no other changes to the Form, Fit or function of these devices.	VGON, SRC, DRN, to GND: -0.3V to +38V		,	VGON, SRC, DRN, to GND: NEW RANGE -0.3V to +34V			
VGON Output Voltage range:       36V (max)       VGON Output Voltage range:       NEW limit 32V (max)         SRC Input Voltage Range:       36V (max)       SRC Input Voltage Range:       NEW limit 32V (max)         JUSTIFICATION:       Our internal breakdown voltage definition has been adjusted in the design rules which resulted in the new maximum voltages shown above (See the attached datasheet markup file)       There are no other changes to the Form, Fit or function of these devices.	DRN to GATES:	-38V to +38V	I	DRN to GA	ATES:	NEW RANGE -34V to +34V	
VGON Output Voltage range:       36V (max)       VGON Output Voltage range:       NEW limit 32V (max)         SRC Input Voltage Range:       36V (max)       SRC Input Voltage Range:       NEW limit 32V (max)         JUSTIFICATION:       Our internal breakdown voltage definition has been adjusted in the design rules which resulted in the new maximum voltages shown above (See the attached datasheet markup file)       There are no other changes to the Form, Fit or function of these devices.							
SRC Input Voltage Range:       36V (max)         SRC Input Voltage Range:       NEW limit 32V (max)         JUSTIFICATION:       Our internal breakdown voltage definition has been adjusted in the design rules which resulted in the new maximum voltages shown above (See the attached datasheet markup file)         There are no other changes to the Form, Fit or function of these devices.	EC table limits:			EC table limits:			
JUSTIFICATION: Our internal breakdown voltage definition has been adjusted in the design rules which resulted in the new maximum voltages shown above (See the attached datasheet markup file) There are no other changes to the Form, Fit or function of these devices.	VGON Output Voltage	e range: 36V (max)	,	VGON Out	put Voltage range:	NEW limit 32V (max)	
maximum voltages shown above (See the attached datasheet markup file) There are no other changes to the Form, Fit or function of these devices.	SRC Input Voltage Ra	nge: 36V (max)	S	SRC Input	Voltage Range:	NEW limit 32V (max)	
maximum voltages shown above (See the attached datasheet markup file) There are no other changes to the Form, Fit or function of these devices.							
maximum voltages shown above (See the attached datasheet markup file) There are no other changes to the Form, Fit or function of these devices.							
There are no other changes to the Form, Fit or function of these devices.	JUSTIFICATION: Our internal breakdown voltage definition has been adjusted in the design rules which resulted in the new						
	maximum voltages shown above (See the attached datasheet markup file)						
Note: This PCN is an Information Notice only and is effective immediately	There are no other changes to the Form, Fit or function of these devices.						

TRACEABILITY: Maxim Integrated maintains full traceability by device marking, packaging labels and shipment documents.

Maxim Integrated's Change Notification System is designed to keep our customer base apprised of major product, manufacturing, or facility improvements.

or

## Nasser Ali Chaouche

Nasser AliChaouche / PCN Coordinator

For further information, please contact either of the people listed below.

Contact your local Maxim Integrated Company Representative

Nasser AliChaouche, PCN Coordinator 408-601-5660 / pcn.coordinator@maximintegrated.com