



12500 TI Boulevard, MS 8640, Dallas, Texas 75243

PCN#20190411001.1B

**Qualification of an additional material set for select devices in the QFN package
Change Notification / Sample Request**

Date: November 19, 2020

To: Newark/Farnell PCN

Dear Customer:

Revision B is to announce the retraction of select devices.

This is an announcement of a change to a device that is currently offered by Texas Instruments. The details of this change are on the following pages.

We request you acknowledge receipt of this notification within **30** days of the date of this notice. Lack of acknowledgement of this notice within 30 days constitutes acceptance of the change. If you require samples or additional data to support your evaluation, please request within 30 days.

The changes discussed within this PCN will not take effect any earlier than **90** days from the date of this notification, unless customer agreement has been reached on an earlier implementation of the change. This notification period is per TI's standard process.

This notice does not change the end-of-life status of any product. Should product affected be on a previously issued product withdrawal/discontinuance notice, this notification does not extend the life of that product or change the life time buy offering/discontinuance plan.

For questions regarding this notice, contact your local Field Sales Representative or the PCN Team (PCN_ww_admin_team@list.ti.com). **For sample requests or sample related questions, contact the TI Samples Team at pcn_sr_team@list.ti.com.**

Sincerely,

PCN Team
SC Business Services

20190411001.1B
Attachment: 1

Products Affected:

The devices listed on this page are a subset of the complete list of affected devices. According to our records, these are the devices that you have purchased within the past twenty-four (24) months. The corresponding customer part number is also listed, if available.

DEVICE	CUSTOMER PART NUMBER
TPS62240DRVR	null
TPS62240DRVT	null
TPS22959DNYT	null

Technical details of this Product Change follow on the next page(s).

PCN Number:	20190411001.1B		PCN Date:	Nov. 19, 2020									
Title:	Qualification of an additional material set for select devices in the QFN package												
Customer Contact:	PCN Manager	Dept:	Quality Services										
Proposed 1st Ship Date:	July 26 2019	Estimated Sample Availability:	Provided upon Request										
Change Type:													
<input type="checkbox"/>	Assembly Site	<input type="checkbox"/>	Assembly Process	<input checked="" type="checkbox"/> Assembly Materials									
<input type="checkbox"/>	Design	<input type="checkbox"/>	Electrical Specification	<input type="checkbox"/> Mechanical Specification									
<input type="checkbox"/>	Test Site	<input type="checkbox"/>	Packing/Shipping/Labeling	<input type="checkbox"/> Test Process									
<input type="checkbox"/>	Wafer Bump Site	<input type="checkbox"/>	Wafer Bump Material	<input type="checkbox"/> Wafer Bump Process									
<input type="checkbox"/>	Wafer Fab Site	<input type="checkbox"/>	Wafer Fab Materials	<input type="checkbox"/> Wafer Fab Process									
	<input type="checkbox"/>	Part number change											
PCN Details													
Description of Change:													
<p>Revision B is to announce the <u>retraction</u> of select devices. These devices will continue to be manufactured as prior and will not be subjected to the change described in this notification. See Page 2 above for the list of retracted devices.</p> <p>Texas Instruments is pleased to announce the qualification of an additional material set for the devices listed in pg 2 of this notification as follows:</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th></th> <th style="text-align: center;">Current</th> <th style="text-align: center;">Additional</th> </tr> </thead> <tbody> <tr> <td>Mount Compound</td> <td style="text-align: center;">4207768</td> <td style="text-align: center;">4207123</td> </tr> <tr> <td>Mold Compound</td> <td style="text-align: center;">4208625</td> <td style="text-align: center;">4222198</td> </tr> </tbody> </table>						Current	Additional	Mount Compound	4207768	4207123	Mold Compound	4208625	4222198
	Current	Additional											
Mount Compound	4207768	4207123											
Mold Compound	4208625	4222198											
Reason for Change:													
Continuity of Supply													
Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative):													
None													
Anticipated impact on Material Declaration													
<input type="checkbox"/>	No Impact to the Material Declaration	<input checked="" type="checkbox"/>	Material Declarations or Product Content reports are driven from production data and will be available following the production release. Upon production release the revised reports can be obtained from the TI ECO website .										
Changes to product identification resulting from this PCN:													
Not Applicable													
Product Affected													
See Page 2													

Qualification Results
Data Displayed as: Number of lots / Total sample size / Total failed

Type	Test Name / Condition	Duration	Qual Device: 27541DRZR_V200	Qual Device: 430FR5969IRGZR	Qual Device: AD51220IRVAR	Qual Device: AD58548SRGCR
AC	Autoclave 121C	96 Hours	3/231/0	3/231/0	3/231/0	3/231/0
BLR	Board Level Reliability, Temp Cycle, -40/125C	1000 Cycles	-	-	-	-
ED	Electrical Distributions	Cpk>1.67 Room, Hot, & Cold	-	-	-	-
ED	Electrical Characterization	Per Datasheet Parameters	-	-	-	-
FLAM	Flammability (IEC 695-2-2)	--	-	-	-	-
FLAM	Flammability (UL 94V-0)	--	-	-	-	-
FLAM	Flammability (UL-1694)	--	-	-	-	-
HAST	Biased HAST, 130C/85%RH	96 Hours	-	3/231/0	-	-
HBM	ESD - HBM	1000 V	-	-	-	-
CDM	ESD - CDM	250 V	-	3/9/0	-	-
HTOL	Life Test, 125C	1000 Hours	-	-	-	-
HTOL	Life Test, 150C	300 Hours	-	-	-	-
HTSL	High Temp. Storage Bake, 150C	1000 Hours	-	3/229/0	-	-
HTSL	High Temp. Storage Bake, 170C	420 Hours	-	-	3/231/0	-
LU	Latch-up	(per JESD78)	-	-	-	-
PD	Physical Dimensions	--	3/15/0	3/15/0	3/15/0	3/15/0
PTC	Power Temperature Cycle, -40/125C	1000 Cycles	-	-	-	-
SD	Surface Mount Solderability	8 Hours Steam Age, Pb-Free	-	-	-	-
SD	Surface Mount Solderability	Pb	-	-	-	-
TC	Temperature Cycle, -55/125C	700 Cycles	-	-	-	-
TC	Temperature Cycle, -65/150C	500 Cycles	3/231/0	3/231/0	3/231/0	3/231/0
THB	Biased Temperature and Humidity, 85C/85%RH	1000 Hours	-	-	-	-
UHAST	Unbiased HAST, 110C/85%RH	264 Hours	-	-	-	-
UHAST	Unbiased HAST, 130C/85%RH	96 Hours	-	-	-	-
VM	Visual / Mechanical	(per mfg. Site specification)	3/984/0	3/984/0	3/984/0	3/984/0
WBP	Bond Pull	Wires	3/228/0	3/228/0	-	-
WBS	Ball Bond Shear	Wires	3/228/0	3/228/0	-	-

Type	Test Name / Condition	Duration	Qual Device: CC2541F256RHAR	Qual Device: DRV10866DSCR	Qual Device: RGC-DC	Qual Device: S320F28030R SHT
AC	Autoclave 121C	96 Hours	-	3/231/0	-	3/231/0
BLR	Board Level Reliability, Temp Cycle, -40/125C	1000 Cycles	-	-	1/32/0	-
ED	Electrical Distributions	Cpk>1.67 Room, Hot, & Cold	-	-	-	-
ED	Electrical Characterization	Per Datasheet Parameters	-	-	-	-
FLAM	Flammability (IEC 695-2-2)	--	-	-	-	-
FLAM	Flammability (UL 94V-0)	--	-	-	-	-
FLAM	Flammability (UL-1694)	--	-	-	-	-
HAST	Biased HAST, 130C/85%RH	96 Hours	-	-	-	-
HBM	ESD - HBM	1000 V	-	-	-	-
CDM	ESD - CDM	250 V	-	-	-	-
HTOL	Life Test, 125C	1000 Hours	-	-	-	-
HTOL	Life Test, 150C	300 Hours	-	-	-	-
HTSL	High Temp. Storage Bake, 150C	1000 Hours	3/231/0	-	-	3/230/0
HTSL	High Temp. Storage Bake, 170C	420 Hours	-	-	-	-
LU	Latch-up	(per JESD78)	-	-	-	-
PD	Physical Dimensions	--	3/15/0	3/15/0	-	3/15/0
PTC	Power Temperature Cycle, -40/125C	1000 Cycles	-	-	-	-
SD	Surface Mount Solderability	8 Hours Steam Age, Pb-Free	-	-	-	3/66/0
SD	Surface Mount Solderability	Pb	-	-	-	-
TC	Temperature Cycle, -55/125C	700 Cycles	3/230/0	-	-	-
TC	Temperature Cycle, -65/150C	500 Cycles	-	3/231/0	-	3/231/0
THB	Biased Temperature and Humidity, 85C/85%RH	1000 Hours	-	-	-	3/219/0
UHAST	Unbiased HAST, 110C/85%RH	264 Hours	3/231/0	-	-	-
UHAST	Unbiased HAST, 130C/85%RH	96 Hours	-	3/231/0	-	-
VM	Visual / Mechanical	(per mfg. Site specification)	3/984/0	3/984/0	-	3/984/0
WBP	Bond Pull	Wires	-	3/228/0	-	3/228/0
WBS	Ball Bond Shear	Wires	-	3/228/0	-	3/228/0

Type	Test Name / Condition	Duration	Qual Device: TPS6300DRCR	Qual Device: TPS65631WDSKR	QBS Package Reference: TPS7A4701QRGWQ1	QBS Package Reference: TRS3122ERGER
AC	Autoclave 121C	96 Hours	3/231/0	3/231/0	3/231/0	3/231/0
BLR	Board Level Reliability, Temp Cycle, -40/125C	1000 Cycles	-	-	1/32/0	-
ED	Electrical Distributions	Cpk>1.67 Room, Hot, & Cold	-	-	3/90/0	-
ED	Electrical Characterization	Per Datasheet Parameters	-	-	-	1/30/0
FLAM	Flammability (IEC 695-2-2)	--	-	-	-	3/15/0
FLAM	Flammability (UL 94V-0)	--	-	-	-	3/15/0
FLAM	Flammability (UL-1694)	--	-	-	-	3/15/0
HAST	Biased HAST, 130C/85%RH	96 Hours	-	-	3/231/0	3/231/0
HBM	ESD - HBM	1000 V	-	-	1/3/0	-
CDM	ESD - CDM	250 V	-	-	1/3/0	-
HTOL	Life Test, 125C	1000 Hours	-	-	3/231/0	-
HTOL	Life Test, 150C	300 Hours	-	-	-	1/77/0
HTSL	High Temp. Storage Bake, 150C	1000 Hours	-	-	1/45/0	3/231/0
HTSL	High Temp. Storage Bake, 170C	420 Hours	-	3/230/0	-	-
LU	Latch-up	(per JESD78)	-	-	1/12/0	1/6/0
PD	Physical Dimensions	--	3/15/0	3/15/0	3/30/0	3/30/0
PTC	Power Temperature Cycle, -40/125C	1000 Cycles	-	-	1/50/0	-
SD	Surface Mount Solderability	8 Hours Steam Age, Pb-Free	3/66/0	-	1/15/0	1/22/0
SD	Surface Mount Solderability	Pb	-	-	1/15/0	-
TC	Temperature Cycle, -55/125C	700 Cycles	-	-	-	-
TC	Temperature Cycle, -65/150C	500 Cycles	3/231/0	3/225/0	3/231/0	3/231/0
THB	Biased Temperature and Humidity, 85C/85%RH	1000 Hours	-	-	-	-
UFAST	Unbiased HAST, 110C/85%RH	264 Hours	-	-	-	-
UFAST	Unbiased HAST, 130C/85%RH	96 Hours	-	-	-	-
VM	Visual / Mechanical	(per mfg. Site specification)	3/984/0	3/984/0	-	3/984/0
WBP	Bond Pull	Wires	3/228/0	3/228/0	3/90/0	3/228/0
WBS	Ball Bond Shear	Wires	3/228/0	3/228/0	3/90/0	3/228/0

- Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable
- The following are equivalent HTOL options based on an activation energy of 0.7eV: 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours
- The following are equivalent HTSL options based on an activation energy of 0.7eV: 150C/1k Hours, and 170C/420 Hours
- The following are equivalent Temp Cycle options per JESD47: -55C/125C/700 Cycles and -65C/150C/500 Cycles
Quality and Environmental data is available at TI's external Web site: <http://www.ti.com/>

Green/Pb-free Status:
Qualified Pb-Free(SMT) and Green

For questions regarding this notice, e-mails can be sent to the contacts shown below or your local Field Sales Representative.

Location	E-Mail
USA	PCNAmericasContact@list.ti.com
Europe	PCNEuropeContact@list.ti.com
Asia Pacific	PCNAsiaContact@list.ti.com
WW PCN Team	PCN_ww_admin_team@list.ti.com