

PRODUCT DATASHEET LED BULKHEAD 6 W 4000 K WT

LED BULKHEAD | Wall and ceiling luminaires



AREAS OF APPLICATION

- Outdoor
- Basements, garages, warehouses

PRODUCT BENEFITS

- Easy and quick installation
- Energy-efficient thanks to LED technology

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP54



TECHNICAL DATA

Electrical data


Nominal wattage	5.50 W
Operating mode	Mains voltage
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 К
Color rendering index Ra	≥80
Light color (designation)	Cool White
Luminous flux	450 lm
Luminous efficacy	76 lm/W

Light technical data

Dimensions & weight



Length	117.0 mm
Width	168.0 mm
Height	70.0 mm
Product weight	175.00 g

Colors & materials

Body material Polycarbonate (PC)	
Product color	White
Housing color	White
Cover material	Acrylonitrile butadiene styr

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Lifespan	
Number of switching cycles	100000
Lifespan	20000 h

Additional product data

Mounting type	Surface
Mounting location	Wall

Capabilities

Dimmable	No
Type of connection	Screw terminal
LED module replaceable	Not replaceable

Certificates & standards

Protection class	11
Type of protection	IP54
Standards	CE/EAC/REACH/ROHS

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075271586	Folding carton box 1	78 mm x 124 mm x 177 mm	202.00 g	1.71 dm³
4058075271593	Shipping carton box 8	327 mm x 263 mm x 196 mm	1924.00 g	16.86 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.