LOGPERIODIC TELEVISION AERIAL

	SPECIFICATION				
	Product Range:	LP20FHV	LP20 ACTIVE*	LP20K	
	Forward Gain	7.5dBi	7.5dBi	7.5dBi	
	Front/Back Ratio	21dB	21dB	21dB	
	Acceptance Angle deg \pm	16°	16°	16°	
	Noise		<2.5dB	-	
	Amplification	•	20dB	-	
	Length	440mm	440mm	440mm	

The Antiference Log periodic aerial is famous amongst professional installers for its level gain across the full frequency range. It is a particularly neat and compact solution ideal for use in strong signal areas where confined installation spaces are a problem. The design also makes it ideal for leisure requirements such as boats or caravans.

Log**PERIODIC** TELEVISION AERIALS

SIGNAL AREAS DIRECTIONAL COMPATIBLE

RESISTANT CONNECTION

FOR MEDIUM *AMPLIFIED SIGNAL AREAS SIGNAL

AMPLIFIED FOR MEDIUM HIGHLY FREEVIEW WEATHER SIGNAL SIGNAL AREAS DIRECTIONAL COMPATIBLE RESISTANT

SPECIFICATION				
Product Range:	LP28F	LP28 ACTIVE*	LP28K	
Forward Gain	9.5dBi	9.5dBi	9.5dBi	
Front/Back Ratio	25dB	25dB	25dB	
Acceptance Angle deg ±	16°	16°	16°	
Noise	2	<2.5dB	-	
Amplification	÷	20dB	-	
Length	1058mm	1058mm	1058mm	

The larger and practical Antiference LP28 Log periodic aerial provides additional gain across the frequency range and is ideal for medium signal areas. As with the smaller LP20 range, the LP28 is available with built in amplifier if extra reception is required.