



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 26

TEROSON PU 92 WH

SDS No. : 180161
V012.0

Revision: 07.04.2021

printing date: 08.04.2021

Replaces version from: 21.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON PU 92 WH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

1-Component sealant

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Respiratory sensitizer

Category 1

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Diphenylmethane diisocyanate, isomers and homologues

Signal word: Danger

Hazard statement: H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Supplemental information

Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
As from 24 August 2023 adequate training is required before industrial or professional use.
Further information: <https://www.feica.eu/PUinfo>

Precautionary statement: P261 Avoid breathing mist/vapours.
Prevention P280 Wear protective gloves.

Precautionary statement: P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor.
Response

2.3. Other hazards

Persons suffering from allergic reactions to isocyanates should avoid contact with the product.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

1-Component moisture-curing sealant

Base substances of preparation:

PUR polymer

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Xylene - mixture of isomeres 1330-20-7	215-535-7 01-2119488216-32	1- < 5 %	Asp. Tox. 1 H304 Acute Tox. 4; Inhalation H332 Acute Tox. 4; Dermal H312 Skin Irrit. 2 H315 Flam. Liq. 3 H226 Eye Irrit. 2 H319 STOT SE 3 H335 STOT RE 2 H373
ethylbenzene 100-41-4	202-849-4 01-2119489370-35	1- < 5 %	Flam. Liq. 2 H225 Acute Tox. 4; Inhalation H332 Asp. Tox. 1 H304 STOT RE 2 H373 Aquatic Chronic 3 H412 Eye Irrit. 2 H319 STOT SE 3 H335 STOT SE 3 H336
Titanium dioxide 13463-67-7	236-675-5 01-2119489379-17	1- < 3 %	Carc. 2; Inhalation H351
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	918-167-1 01-2119472146-39	1- < 3 %	Aquatic Chronic 4 H413 Asp. Tox. 1 H304 Flam. Liq. 3 H226
methylenediphenyl diisocyanate 26447-40-5	247-714-0	0,1- < 1 %	Acute Tox. 4; Inhalation H332 Skin Irrit. 2 H315 Eye Irrit. 2 H319 Carc. 2 H351 STOT RE 2 H373 STOT SE 3 H335 Resp. Sens. 1 H334 Skin Sens. 1 H317
MDI homopolymer 25686-28-6	500-040-3 500-040-3 01-2119457013-49	0,1- < 1 %	Acute Tox. 4; Inhalation H332 Skin Irrit. 2 H315 Eye Irrit. 2 H319 Resp. Sens. 1 H334 Skin Sens. 1 H317 STOT SE 3 H335 Carc. 2 H351 STOT RE 2; Inhalation H373
4,4'- methylenediphenyl diisocyanate	202-966-0	0,1- < 1 %	Carc. 2

101-68-8	01-2119457014-47		H351 Acute Tox. 4; Inhalation H332 STOT RE 2 H373 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 Resp. Sens. 1 H334 Skin Sens. 1B H317
----------	------------------	--	---

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Fresh air, oxygen supply, warmth; seek specialist medical attention.
Delayed effects possible after inhalation.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.
Avoid contact with skin and eyes.
Keep unprotected persons away.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.
Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Hygiene measures:

- Do not eat, drink or smoke while working.
- Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container protected against moisture.
Ensure good ventilation/extraction.
Store in a cool, dry place.
Keep away from heat and direct sunlight.
Keep container tightly sealed and store in a frost free place.

7.3. Specific end use(s)

1-Component sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Polyvinyl chloride 9002-86-2 [POLYVINYL CHLORIDE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Polyvinyl chloride 9002-86-2 [POLYVINYL CHLORIDE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Xylene 1330-20-7 [XYLENE, O-, M-, P- OR MIXED ISOMERS]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Xylene 1330-20-7 [XYLENE, O-, M-, P- OR MIXED ISOMERS]	50	220	Time Weighted Average (TWA):		EH40 WEL
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	50	221	Time Weighted Average (TWA):	Indicative	ECTLV
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	100	442	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Xylene 1330-20-7 [XYLENE, O-, M-, P- OR MIXED ISOMERS]	100	441	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Di-"isononyl" phthalate 28553-12-0 [DIISONONYL PHTHALATE]		5	Time Weighted Average (TWA):		EH40 WEL
Ethylbenzene 100-41-4 [ETHYLBENZENE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Ethylbenzene 100-41-4 [ETHYLBENZENE]	100	441	Time Weighted Average (TWA):		EH40 WEL
Ethylbenzene 100-41-4 [ETHYLBENZENE]	100	442	Time Weighted Average (TWA):	Indicative	ECTLV
Ethylbenzene 100-41-4 [ETHYLBENZENE]	200	884	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Ethylbenzene 100-41-4 [ETHYLBENZENE]	125	552	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Titanium dioxide 13463-67-7		4	Time Weighted Average (TWA):		EH40 WEL

[TITANIUM DIOXIDE, RESPIRABLE]					
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Methylenediphenyl diisocyanate 26447-40-5 [ISOCYANATES, ALL (AS -NCO)]		0,02	Time Weighted Average (TWA):		EH40 WEL
Methylenediphenyl diisocyanate 26447-40-5 [ISOCYANATES, ALL (AS -NCO)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [ISOCYANATES, ALL (AS -NCO)]		0,02	Time Weighted Average (TWA):		EH40 WEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [ISOCYANATES, ALL (AS -NCO)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
4,4'-Methylenediphenyl diisocyanate, homopolymer 25686-28-6 [ISOCYANATES, ALL (AS -NCO)]		0,02	Time Weighted Average (TWA):		EH40 WEL
4,4'-Methylenediphenyl diisocyanate, homopolymer 25686-28-6 [ISOCYANATES, ALL (AS -NCO)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Polyvinyl chloride 9002-86-2 [POLYVINYL CHLORIDE (PVC)]		1	Time Weighted Average (TWA):		IR_OEL
Polyvinyl chloride 9002-86-2 [POLYVINYL CHLORIDE (PVC)]		10	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE]		4	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE]		10	Time Weighted Average (TWA):		IR_OEL
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS]	50	221	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	50	221	Time Weighted Average (TWA):	Indicative	ECLTV
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	100	442	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS]	100	442	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Di-"isononyl" phthalate 28553-12-0 [DIISONONYL PHTHALATE]		5	Time Weighted Average (TWA):		IR_OEL
Ethylbenzene 100-41-4 [ETHYLBENZENE]	100	442	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Ethylbenzene 100-41-4 [ETHYLBENZENE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Ethylbenzene 100-41-4 [ETHYLBENZENE]	100	442	Time Weighted Average (TWA):	Indicative	ECLTV
Ethylbenzene 100-41-4 [ETHYLBENZENE]	200	884	Short Term Exposure Limit (STEL):	Indicative	ECLTV

Ethylbenzene 100-41-4 [ETHYLBENZENE]	200	884	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		4	Time Weighted Average (TWA):		IR_OEL
Methylenediphenyl diisocyanate 26447-40-5 [ISOCYANATES, ALL, EXCEPT METHYL ISOCYANATE (CAS NO. 624- 83-9) AND TOLUENE (2,4 OR 2,6 DIISOCYANATE (CAS NO. 584-84-9, 91- 08-7)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Methylenediphenyl diisocyanate 26447-40-5 [ISOCYANATES, ALL, EXCEPT METHYL ISOCYANATE (CAS NO. 624- 83-9) AND TOLUENE (2,4 OR 2,6 DIISOCYANATE (CAS NO. 584-84-9, 91- 08-7)]		0,02	Time Weighted Average (TWA):		IR_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [4,4'-METHYLENE-DIPHENYL DIISOCYANATE (AS -NCO)]	0,005		Time Weighted Average (TWA):		IR_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [ISOCYANATES, ALL, EXCEPT METHYL ISOCYANATE (CAS NO. 624- 83-9) AND TOLUENE (2,4 OR 2,6 DIISOCYANATE (CAS NO. 584-84-9, 91- 08-7)]		0,02	Time Weighted Average (TWA):		IR_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [ISOCYANATES, ALL, EXCEPT METHYL ISOCYANATE (CAS NO. 624- 83-9) AND TOLUENE (2,4 OR 2,6 DIISOCYANATE (CAS NO. 584-84-9, 91- 08-7)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Xylene - mixture of isomeres 1330-20-7	aqua (freshwater)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	sediment (freshwater)				12,46 mg/kg		
Xylene - mixture of isomeres 1330-20-7	Soil				2,31 mg/kg		
Xylene - mixture of isomeres 1330-20-7	aqua (marine water)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	aqua (intermittent releases)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	sewage treatment plant (STP)		6,58 mg/l				
Xylene - mixture of isomeres 1330-20-7	sediment (marine water)				12,46 mg/kg		
ethylbenzene 100-41-4	aqua (intermittent releases)		0,1 mg/l				
ethylbenzene 100-41-4	aqua (freshwater)		0,1 mg/l				
ethylbenzene 100-41-4	sediment (marine water)				1,37 mg/kg		
ethylbenzene 100-41-4	sediment (freshwater)				13,7 mg/kg		
ethylbenzene 100-41-4	sewage treatment plant (STP)		9,6 mg/l				
ethylbenzene 100-41-4	aqua (marine water)		0,01 mg/l				
ethylbenzene 100-41-4	Soil				2,68 mg/kg		
ethylbenzene 100-41-4	oral				20 mg/kg		
Titanium dioxide 13463-67-7	aqua (freshwater)						no hazard identified
Titanium dioxide 13463-67-7	aqua (marine water)						no hazard identified
Titanium dioxide 13463-67-7	sewage treatment plant (STP)						no hazard identified
Titanium dioxide 13463-67-7	sediment (freshwater)						no hazard identified
Titanium dioxide 13463-67-7	sediment (marine water)						no hazard identified
Titanium dioxide 13463-67-7	Soil						no hazard identified
Titanium dioxide 13463-67-7	Aquatic (intermit. releases)						no hazard identified
Titanium dioxide 13463-67-7	Predator						no hazard identified
4,4'-Methylenediphenyl diisocyanate, homopolymer 25686-28-6	aqua (freshwater)		1 mg/l				
4,4'-Methylenediphenyl diisocyanate, homopolymer 25686-28-6	aqua (marine water)		0,1 mg/l				
4,4'-Methylenediphenyl diisocyanate, homopolymer 25686-28-6	Soil				1 mg/kg		
4,4'-Methylenediphenyl diisocyanate, homopolymer 25686-28-6	sewage treatment plant (STP)		1 mg/l				
4,4'-Methylenediphenyl diisocyanate, homopolymer 25686-28-6	aqua (intermittent releases)		10 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (freshwater)		1 mg/l				

4,4'-methylenediphenyl diisocyanate 101-68-8	aqua (marine water)		0,1 mg/l				
4,4'-methylenediphenyl diisocyanate 101-68-8	Soil				1 mg/kg		
4,4'-methylenediphenyl diisocyanate 101-68-8	sewage treatment plant (STP)		1 mg/l				
4,4'-methylenediphenyl diisocyanate 101-68-8	Air						no hazard identified
4,4'-methylenediphenyl diisocyanate 101-68-8	Predator						no potential for bioaccumulation
4,4'-methylenediphenyl diisocyanate 101-68-8	aqua (intermittent releases)		10 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Xylene - mixture of isomers 1330-20-7	Workers	inhalation	Long term exposure - systemic effects		221 mg/m3	
Xylene - mixture of isomers 1330-20-7	Workers	inhalation	Acute/short term exposure - systemic effects		442 mg/m3	
Xylene - mixture of isomers 1330-20-7	Workers	inhalation	Long term exposure - local effects		221 mg/m3	
Xylene - mixture of isomers 1330-20-7	Workers	inhalation	Acute/short term exposure - local effects		442 mg/m3	
Xylene - mixture of isomers 1330-20-7	Workers	dermal	Long term exposure - systemic effects		212 mg/kg	
Xylene - mixture of isomers 1330-20-7	General population	inhalation	Long term exposure - systemic effects		65,3 mg/m3	
Xylene - mixture of isomers 1330-20-7	General population	inhalation	Acute/short term exposure - systemic effects		260 mg/m3	
Xylene - mixture of isomers 1330-20-7	General population	inhalation	Long term exposure - local effects		65,3 mg/m3	
Xylene - mixture of isomers 1330-20-7	General population	inhalation	Acute/short term exposure - local effects		260 mg/m3	
Xylene - mixture of isomers 1330-20-7	General population	dermal	Long term exposure - systemic effects		125 mg/kg	
Xylene - mixture of isomers 1330-20-7	General population	oral	Long term exposure - systemic effects		12,5 mg/kg	
ethylbenzene 100-41-4	Workers	inhalation	Acute/short term exposure - local effects		293 mg/m3	
ethylbenzene 100-41-4	General population	inhalation	Long term exposure - systemic effects		15 mg/m3	
ethylbenzene 100-41-4	General population	oral	Long term exposure - systemic effects		1,6 mg/kg	
ethylbenzene 100-41-4	Workers	dermal	Long term exposure - systemic effects		180 mg/kg	
ethylbenzene 100-41-4	Workers	inhalation	Long term exposure - systemic effects		77 mg/m3	
4,4'-Methylenediphenyl diisocyanate, homopolymer 25686-28-6	Workers	inhalation	Long term exposure - local effects		0,05 mg/m3	
4,4'-Methylenediphenyl diisocyanate, homopolymer 25686-28-6	Workers	inhalation	Acute/short term exposure - local effects		0,1 mg/m3	
4,4'-Methylenediphenyl diisocyanate, homopolymer 25686-28-6	General population	inhalation	Long term exposure - local effects		0,025 mg/m3	
4,4'-Methylenediphenyl diisocyanate, homopolymer 25686-28-6	General population	inhalation	Acute/short term exposure - local effects		0,05 mg/m3	
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	inhalation	Long term exposure - local effects		0,05 mg/m3	no hazard identified
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	inhalation	Acute/short term exposure - local effects		0,1 mg/m3	no hazard identified
4,4'- methylenediphenyl diisocyanate 101-68-8	General population	inhalation	Long term exposure - local effects		0,025 mg/m3	no hazard identified
4,4'- methylenediphenyl diisocyanate 101-68-8	General population	inhalation	Acute/short term exposure - local		0,05 mg/m3	no hazard identified

			effects			
--	--	--	---------	--	--	--

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Xylene 1330-20-7 [XYLENE O-, M-, P-, OR MIXED ISOMERS]	Methylhippuric acids	Creatinine in urine	Sampling time: End of shift.		UKEH40BMG V		
Methylenediphenyl diisocyanate 26447-40-5 [ISOCYANATES (APPLIES TO HDI, IPDI, TDI AND MDI)]	Isocyanate-derived diamine	Creatinine in urine	Sampling time: At the end of the period of exposure.		UKEH40BMG V		
4,4'-Methylenediphenyl diisocyanate 101-68-8 [ISOCYANATES (APPLIES TO HDI, IPDI, TDI AND MDI)]	Isocyanate-derived diamine	Creatinine in urine	Sampling time: At the end of the period of exposure.		UKEH40BMG V		
4,4'-Methylenediphenyl diisocyanate, homopolymer 25686-28-6 [ISOCYANATES (APPLIES TO HDI, IPDI, TDI AND MDI)]	Isocyanate-derived diamine	Creatinine in urine	Sampling time: At the end of the period of exposure.		UKEH40BMG V		

8.2. Exposure controls:

Engineering controls:

Use only in well ventilated areas.

Respiratory protection:

In case of dust formation, we recommend wearing of appropriate respiratory protection equipment with particle filter P (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Fluorinated rubber (FKM; ≥ 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Fluorinated rubber (FKM; ≥ 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway).

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	solid material pasty white
Odor	of solvent
Odour threshold	No data available / Not applicable
pH	Not available.
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	Not available.
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	
lower	0,1 % (V)
upper	7,6 % (V)
Vapour pressure (20 °C (68 °F))	< 100 hPa
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	1,19 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

Ignition temperature	> 200 °C (> 392 °F)
max. VOC content:	70 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with water: Pressure built up in closed vessel (CO₂).
Reaction with water, alcohols, amines.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Humidity

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

At higher temperatures isocyanate may be released.
Carbon dioxide is generated under contact with moisture, leading to pressure in the cans. Danger of cans bursting!

SECTION 11: Toxicological information

General toxicological information:

Persons suffering from allergic reactions to isocyanates should avoid contact with the product.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Xylene - mixture of isomeres 1330-20-7	LD50	3.523 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))
ethylbenzene 100-41-4	LD50	3.500 mg/kg	rat	not specified
Titanium dioxide 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
methylenediphenyl diisocyanate 26447-40-5	LD50	> 2.000 mg/kg	rat	not specified
MDI homopolymer 25686-28-6	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
4,4'- methylenediphenyl diisocyanate 101-68-8	LD50	> 2.000 mg/kg	rat	other guideline:

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Xylene - mixture of isomeres 1330-20-7	LD50	1.700 mg/kg	rabbit	not specified
ethylbenzene 100-41-4	LD50	15.433 mg/kg	rabbit	not specified
Titanium dioxide 13463-67-7	LD50	>= 10.000 mg/kg	hamster	not specified
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	LD50	> 2.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
methylenediphenyl diisocyanate 26447-40-5	LD50	> 6.200 mg/kg	rabbit	not specified
MDI homopolymer 25686-28-6	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	LC50	11 mg/l	vapour	4 h	rat	not specified
ethylbenzene 100-41-4	LC50	17,2 mg/l	vapour	4 h	rat	not specified
Titanium dioxide 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	moderately irritating		rabbit	not specified
ethylbenzene 100-41-4	moderately irritating	24 h	rabbit	not specified
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	mildly irritating		rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
methylenediphenyl diisocyanate 26447-40-5	highly irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
4,4'- methylenediphenyl diisocyanate 101-68-8	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
ethylbenzene 100-41-4	slightly irritating		rabbit	not specified
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
methylenediphenyl diisocyanate 26447-40-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Xylene - mixture of isomeres 1330-20-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	not sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
4,4'- methylenediphenyl diisocyanate 101-68-8	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Xylene - mixture of isomeres 1330-20-7	negative	in vitro mammalian chromosome aberration test	with and without		EU Method B.10 (Mutagenicity)
Xylene - mixture of isomeres 1330-20-7	negative	sister chromatid exchange assay in mammalian cells	with and without		EU Method B.19 (Sister Chromatid Exchange Assay In Vitro)
ethylbenzene 100-41-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
ethylbenzene 100-41-4	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
ethylbenzene 100-41-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
ethylbenzene 100-41-4	negative	sister chromatid exchange assay in mammalian cells	with and without		not specified
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	negative	sister chromatid exchange assay in mammalian cells	with and without		equivalent or similar to OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
methylenediphenyl diisocyanate 26447-40-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
4,4'- methylenediphenyl diisocyanate 101-68-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Xylene - mixture of isomeres 1330-20-7	negative	intraperitoneal		rat	OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)
ethylbenzene 100-41-4	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
ethylbenzene 100-41-4	negative	inhalation		mouse	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Titanium dioxide 13463-67-7	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Hydrocarbons, C11-C12,	negative			mouse	equivalent or similar to OECD

isoalkanes, < 2% aromatics 64742-48-9					Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	negative			rat	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Xylene - mixture of isomeres 1330-20-7	not carcinogenic	oral: gavage	103 w 5 d/w	rat	male/female	EU Method B.32 (Carcinogenicity Test)
ethylbenzene 100-41-4	carcinogenic	inhalation: vapour	104 w 6 h/d, 5 d/w	rat	male/female	equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Titanium dioxide 13463-67-7	not carcinogenic	inhalation	24 m 6 h/d; 5 d/w	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
MDI homopolymer 25686-28-6	carcinogenic	inhalation: aerosol	2 y 6 h/d	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
4,4'- methylenediphenyl diisocyanate 101-68-8	carcinogenic	inhalation: aerosol	2 y 6 h/d	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
ethylbenzene 100-41-4	NOAEL P 1000 ppm NOAEL F1 100 ppm	One generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 415 (One-Generation Reproduction Toxicity Study)
ethylbenzene 100-41-4	NOAEL P 500 ppm NOAEL F1 500 ppm NOAEL F2 500 ppm	Two generation study	inhalation	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Titanium dioxide 13463-67-7	NOAEL P > 1.000 mg/kg NOAEL F1 > 1.000 mg/kg		oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	NOAEL P >= 1.720 mg/kg NOAEL F1 >= 1.720 mg/kg	screening	inhalation	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Xylene - mixture of isomeres 1330-20-7	NOAEL 150 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
ethylbenzene 100-41-4	NOAEL 75 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Titanium dioxide 13463-67-7	NOAEL 1.000 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	NOAEL 5.000 mg/kg	oral: gavage	13 weeks daily	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
MDI homopolymer 25686-28-6		inhalation: aerosol	2 y (main); 1 y (satellite) 6 h/d; 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOAEL 0,0002 mg/l	inhalation: aerosol	main: 2 y; satellite:1 y 6 h/d; 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
ethylbenzene 100-41-4	0,641 mm ² /s	40 °C	OECD Test Guideline 114	
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	0,34 mm ² /s	40 °C	not specified	

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Xylene - mixture of isomers 1330-20-7	LC50	2,6 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
ethylbenzene 100-41-4	LC50	4,2 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Titanium dioxide 13463-67-7	LC50	Toxicity > Water solubility	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	LL50	Toxicity > Water solubility	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
methylenediphenyl diisocyanate 26447-40-5	LC50	> 10.000 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	not specified
MDI homopolymer 25686-28-6	LC50	> 1.000 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	LC50	> 1.000 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Xylene - mixture of isomers 1330-20-7	EC50	3,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
ethylbenzene 100-41-4	EC50	> 1,8 - 2,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	EL50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
methylenediphenyl diisocyanate 26447-40-5	EC50	83 mg/l	48 h	Daphnia magna	not specified
MDI homopolymer 25686-28-6	EC50	129,7 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	EC50	129,7 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
ethylbenzene 100-41-4	NOEC	0,96 mg/l	7 d	Ceriodaphnia dubia	OECD 211 (Daphnia magna, Reproduction Test)
MDI homopolymer 25686-28-6	NOEC	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOEC	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Xylene - mixture of isomers 1330-20-7	ErC50	4,36 mg/l	73 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Xylene - mixture of isomers 1330-20-7	EC10	1,9 mg/l	73 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
ethylbenzene 100-41-4	EC50	7,7 mg/l	96 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
ethylbenzene 100-41-4	NOEC	4,5 mg/l	96 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	EL50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	NOELR	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
methylenediphenyl diisocyanate 26447-40-5	ErC50	> 100 mg/l	72 h	Desmodesmus subspicatus	not specified
MDI homopolymer 25686-28-6	EC50	> 1.640 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
MDI homopolymer 25686-28-6	NOEC	1.640 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	EC50	> 1.640 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOELR	1.640 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Xylene - mixture of isomers 1330-20-7	EC 50	> 1 - 10 mg/l			not specified
ethylbenzene 100-41-4	EC50	> 152 mg/l	30 min	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Titanium dioxide 13463-67-7	EC0	Toxicity > Water solubility	24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
methylenediphenyl diisocyanate 26447-40-5	EC 50	> 100 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
MDI homopolymer 25686-28-6	EC50	> 100 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	EC50	> 100 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Xylene - mixture of isomers 1330-20-7	readily biodegradable	aerobic	90 %	28 day	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
ethylbenzene 100-41-4	readily biodegradable	aerobic	69 %	33 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics 64742-48-9	not readily biodegradable.	aerobic	31,3 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
methylenediphenyl diisocyanate 26447-40-5	not inherently biodegradable	aerobic	0 %	28 day	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
methylenediphenyl diisocyanate 26447-40-5	not readily biodegradable.	not specified	0 %	28 d	OECD 301 A - F
MDI homopolymer 25686-28-6	not readily biodegradable.	aerobic	> 0 - < 60 %	28 d	OECD 301 A - F
MDI homopolymer 25686-28-6	not inherently biodegradable	aerobic	0 %	28 d	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
4,4'- methylenediphenyl diisocyanate 101-68-8	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Xylene - mixture of isomers 1330-20-7	25,9	56 day		Oncorhynchus mykiss	not specified
ethylbenzene 100-41-4	1	42 d	10 °C	Oncorhynchus kisutch	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
methylenediphenyl diisocyanate 26447-40-5	< 1	112 d		Oncorhynchus mykiss	not specified
MDI homopolymer 25686-28-6	> 92 - 200	28 d		Cyprinus carpio	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	92 - 200	28 d		Cyprinus carpio	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Xylene - mixture of isomers 1330-20-7	3,16	20 °C	not specified
ethylbenzene 100-41-4	3,6	20 °C	EU Method A.8 (Partition Coefficient)
4,4'- methylenediphenyl diisocyanate 101-68-8	4,51	22 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Xylene - mixture of isomers 1330-20-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
ethylbenzene 100-41-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Titanium dioxide 13463-67-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
MDI homopolymer 25686-28-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
4,4'- methylenediphenyl diisocyanate 101-68-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

SECTION 14: Transport information**14.1. UN number**

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.2. UN proper shipping name

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.3. Transport hazard class(es)

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.4. Packing group

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation 1005/2009/EC):	Not applicable
Prior Informed Consent (PIC) (Regulation 649/2012/EC):	Not applicable
Persistent Organic Pollutants (POPs) (Regulation 2019/1021/EC) :	Not applicable

EU. REACH, Annex XVII, Marketing and Use Restrictions (Regulation 1907/2006/EC):

Contains:	Diisononyl phthalate
	CAS 28553-12-0
	ethylbenzene
	CAS 100-41-4
	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
	CAS 64742-48-9

This substance is restricted under Entry 52, 40, Refer to Annex XVII of the REACH Regulation for details of the restriction.

VOC content (2010/75/EU)	12 %
-----------------------------	------

VOC Paints and Varnishes (EU):

Product (sub)category:	This product is not a subject of the Directive 2004/42/EC
max. VOC content:	70 g/l

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H225 Highly flammable liquid and vapor.
- H226 Flammable liquid and vapor.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.