



12500 TI Boulevard, MS 8640, Dallas, Texas 75243

PCN#20210427002.1A
Qualify TI Malaysia as an additional Assembly site for Select Devices
Change Notification / Sample Request

Date: May 14, 2021
To: Newark/Farnell PCN

Revision A is to update/correct the Assembly city references in the Changes to product identification resulting from the PCN section.

Dear Customer:

This is an announcement of a change to a device that is currently offered by Texas Instruments. The details of this change are on the following pages.

Texas Instruments requires acknowledgement of receipt of this notification within **30** days of the date of this notice. Lack of acknowledgement of this notice within 30 days constitutes acceptance of the change. If samples or additional data are required, requests must be received within **30 days** of this notification.

The changes discussed within this PCN will not take effect any earlier than the proposed first ship date on Page 3 of this notification, unless customer agreement has been reached on an earlier implementation of the change.

This notice does not change the end-of-life status of any product. Should product affected be on a previously issued product withdrawal/discontinuance notice, this notification does not extend the life of that product or change the life time buy offering/discontinuance plan.

For questions regarding this notice or to provide acknowledgement of this PCN, you may contact your local Field Sales Representative or the PCN Team (PCN_ww_admin_team@list.ti.com). For sample requests or sample related questions, contact your local Field Sales Representative.

Sincerely,

PCN Team
SC Business Services

20210427002.1
Change Notification / Sample Request
Attachments

Products Affected:

The devices listed on this page are a subset of the complete list of affected devices. According to our records, these are the devices that you have purchased within the past twenty-four (24) months. The corresponding customer part number is also listed, if available.

DEVICE	CUSTOMER PART NUMBER
LM2901M/NOPB	null
LM2675M-3.3/NOPB	null
LM2674M-ADJ/NOPB	null
LM2675M-ADJ/NOPB	null
LP2951CM-3.3/NOPB	null

Technical details of this Product Change follow on the next page(s).

PCN Number:	20210427002.1A	PCN Date:	May 14, 2021
Title:	Qualify TI Malaysia as an additional Assembly site for Select Devices		
Customer Contact:	PCN Manager	Dept:	Quality Services
Proposed 1st Ship Date:	Aug. 11, 2021	Estimated Sample Availability:	Date provided at sample request
Change Type:			
<input checked="" type="checkbox"/>	Assembly Site	<input type="checkbox"/>	Design
<input type="checkbox"/>	Assembly Process	<input type="checkbox"/>	Data Sheet
<input checked="" type="checkbox"/>	Assembly Materials	<input type="checkbox"/>	Part number change
<input type="checkbox"/>	Mechanical Specification	<input type="checkbox"/>	Test Site
<input checked="" type="checkbox"/>	Packing/Shipping/Labeling	<input type="checkbox"/>	Test Process
		<input type="checkbox"/>	Wafer Bump Site
		<input type="checkbox"/>	Wafer Bump Material
		<input type="checkbox"/>	Wafer Bump Process
		<input type="checkbox"/>	Wafer Fab Site
		<input type="checkbox"/>	Wafer Fab Materials
		<input type="checkbox"/>	Wafer Fab Process
PCN Details			
Description of Change:			
Revision A is to update/correct the Assembly city references in the Changes to product identification resulting from the PCN section.			
Texas Instruments is pleased to announce the qualification of TI Malaysia as an Additional Assembly site for the list of devices shown below. Current assembly site and Material differences are as follows:			
	TIEM	AP1	MLA
Mount Compound	8075531	SID#101375281	4147858
Mold Compound	8096859	SID#101323397	4211880
Lead Finish	Matte Sn	Matte Sn	NiPdAu
##Bond wire, diameter	Au, 1.3 mils	Au, 1.3 mils	Cu, 1.3 mils
## - Applies to only the LM2674M-5.0/NOPB			
NOTE: Devices are currently built at either TIEM or AP1 or both			
Upon expiry of this PCN TI will combine lead free solutions in a single standard part number , for this device. For example; LM2901M/NOPB – can ship with both Matte Sn and NiPdAu.			
Example:			
<ul style="list-style-type: none"> - Customer order for 7500 units of LM2901M/NOPB with 2500 units SPQ (Standard Pack Quantity per Reel). - TI can satisfy the above order in one of the following ways. <ul style="list-style-type: none"> I. 3 Reels of NiPdAu finish. II. 3 Reels of Matte Sn finish III. 2 Reels of Matte Sn and 1 reel of NiPdAu finish. IV. 2 Reels of NiPdAu and 1 reel of Matte Sn finish. 			
Reason for Change:			
Continuity of Supply			
Anticipated impact on Form, Fit, Function, Quality or Reliability (positive / negative):			
None			
Anticipated impact on Material Declaration			
<input type="checkbox"/>	No Impact to the Material Declaration	<input checked="" type="checkbox"/>	Material Declarations or Product Content reports are driven from production data and will be available following the production release. Upon production release the revised reports can be obtained at the site link below

<http://www.ti.com/quality/docs/materialcontentsearch.tsp>

Changes to product identification resulting from this PCN:

Assembly Site	Assembly Site Origin (22L)	Assembly Country Code (23L)	Assembly City
TIEM	CU6	MYS	Kuala Lumpur Melaka
AP1	AKR	PHL	Cupang, Muntinlupa City
TI Malaysia	MLA	MYS	Ayutthaya Kuala Lumpur

Sample product shipping label (not actual product label)

G3: Matte Sn
G4: NiPdAu

Product Affected:

LM2674M-12/NOPB	LM2675MX-ADJ/J7002911	LM5101AMX/NOPB	LMV844MAX/NOPB
LM2674M-3.3/NOPB	LM2675MX-ADJ/NOPB	LM5101AMX/S7003027	LP2951ACM-3.0/NOPB
LM2674M-5.0/NOPB	LM2901M/NOPB	LM5101BMA/NOPB	LP2951ACM-3.3/NOPB
LM2674M-ADJ/NOPB	LM2901MX/NOPB	LM5101BMAX/NOPB	LP2951ACM/NOPB
LM2674MX-12/NOPB	LM2902M/NOPB	LM5101CMA/NOPB	LP2951ACMX-3.0/NOPB
LM2674MX-3.3/NOPB	LM2902MX/E7002681	LM5101CMAX/NOPB	LP2951ACMX-3.3/NOPB
LM2674MX-5.0/NOPB	LM2902MX/NAK2	LM5101M/NOPB	LP2951ACMX/NOPB
LM2674MX-ADJ/NOPB	LM2902MX/NOPB	LM5101MX/NOPB	LP2951CM-3.0/NOPB
LM2675M-12/NOPB	LM324AM/NOPB	LM5109AMA/NOPB	LP2951CM-3.3/NOPB
LM2675M-3.3/NOPB	LM324AMX/NOPB	LM5109AMAX/NOPB	LP2951CM/NOPB
LM2675M-5.0/NOPB	LM324M/NOPB	LM5109BMA/NOPB	LP2951CMX-3.0/NOPB
LM2675M-ADJ/NOPB	LM324MX/NOPB	LM5109BMAX/NOPB	LP2951CMX-3.3/NOPB
LM2675MX-12/NOPB	LM339AM/NOPB	LM5109MA/NOPB	LP2951CMX/E7002608
LM2675MX-3.3/E7002948	LM339AMX/NOPB	LM5109MAX/NOPB	LP2951CMX/J7000697
LM2675MX-3.3/NAK2	LM339M/NOPB	LMV324M/NOPB	LP2951CMX/NAK2
LM2675MX-3.3/NOPB	LM339MX/NOPB	LMV324MX/NOPB	LP2951CMX/NOPB
LM2675MX-5.0/NOPB	LM5101AM/NOPB	LMV844MA/NOPB	



TI Information
Selective Disclosure

Qualification Report

Approve Date 16-Feb-2021

Qualification Results

Data Displayed as: Number of lots / Total sample size / Total failed

Type	Test Name / Condition	Duration	Qual Device: LM2675MXADHH NC	Qual Device: LM5101AMXSF0 S4	Qual Device: LMV844MAX/NO PB	QBS Package Reference: CD4081BM96	QBS Package Reference: LM393DR ROUG H LDE	QBS Package Reference: LP2951ACMX- 3.3/S2	QBS Package Reference: TCA9546ADR R LE
AC	Autoclave 121C	96 Hours	3/231/0	-	3/231/0	3/228/0	3/231/0	1/77/0	3/231/0
ED	Auto Electrical Distributions	Cpk>1.67 Room, hot, and cold test	-	-	-	-	-	1/30/0	-
ED	Electrical Characterization, side by side	-	1/30/0	1/30/0	1/30/0	-	-	-	-
FLAM	Flammability (UL 94V-0)	-	-	-	-	-	-	-	3/15/0
HAST	Biased HAST, 130C/85%RH	192 Hours (for info)	-	-	-	-	-	3/231/0	-
HAST	Biased HAST, 130C/85%RH	96 Hours	-	-	-	-	-	3/231/0	-
HTOL	Life Test, 125C	1000 Hours	-	-	-	-	-	1/77/0	-
HTSL	High Temp Storage Bake 170C	420 Hours	-	-	-	-	3/231/0	-	3/231/0
LI	Lead Fatigue	Leads	-	-	-	3/66/0	3/66/0	-	-
LI	Lead Pull	Leads	-	-	-	3/126/0	3/72/0	-	-
PD	Physical Dimensions	(per mechanical drawing)	-	-	-	3/15/0	3/90/0	1/30/0	-
SD	Solderability	Pb Free	-	-	-	3/66/0	-	-	3/66/0
TC	Temperature Cycle, -65/150C	500 Cycles	3/231/0	-	3/231/0	3/231/0	3/231/0	1/77/0	3/231/0
VM	Visual / Mechanical	-	3/984/0	3/984/0	3/984/0	3/984/0	3/984/0	3/984/0	3/984/0
WBP	Bond Pull	Wires	3/228/0	3/228/0	3/228/0	3/228/0	3/228/0	3/90/0	3/228/0
WBS	Ball Bond Shear	Wires	3/228/0	3/228/0	3/228/0	3/228/0	3/228/0	3/90/0	3/228/0

- QBS: Qual By Similarity
 - Qual Devices LM2675MXADHHNC, LM5101AMXSF0S4 and LMV844MAX/NOPB are qualified at LEVEL1-260C
 - Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable
 - The following are equivalent HTOL options based on an activation energy of 0.7eV: 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours
 - The following are equivalent HTSL options based on an activation energy of 0.7eV: 150C/1k Hours, and 170C/420 Hours
 - The following are equivalent Temp Cycle options per JESD47: -55C/125C/700 Cycles and -65C/150C/500 Cycles
- Quality and Environmental data is available at TI's external Web site: <http://www.ti.com/>
Green/Pb-free Status:
 Qualified Pb-Free(SMT) and Green

For questions regarding this notice, e-mails can be sent to the contacts shown below or your local Field Sales Representative.

Location	E-Mail
USA	PCNAmericasContact@list.ti.com
Europe	PCNEuropeContact@list.ti.com
Asia Pacific	PCNAsiaContact@list.ti.com
WW PCN Team	PCN_ww_admin_team@list.ti.com

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.