



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 17

LOCTITE 572

SDS No. : 454059
V008.0

Revision: 24.06.2021
printing date: 25.06.2021

Replaces version from: 29.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 572

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Anaerobic

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation

H319 Causes serious eye irritation.

Category 2

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Warning

| | |
|--|---|
| Hazard statement: | H319 Causes serious eye irritation. |
| Supplemental information | EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains: Linalool May produce an allergic reaction. |
| Precautionary statement: | **** **For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.**** |
| Precautionary statement: Response | P337+P313 If eye irritation persists: Get medical advice/attention. |

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Anaerobic adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. | EC Number REACH-Reg No. | content | Classification |
|---------------------------------|-------------------------------|------------|--|
| Octan-1-ol 111-87-5 | 203-917-6 01-2119486978-10 | 10- 20 % | Eye Irrit. 2 H319 Aquatic Chronic 3 H412 |
| Titanium dioxide 13463-67-7 | 236-675-5 01-2119489379-17 | 1- < 5 % | Carc. 2; Inhalation H351 |
| Cumene hydroperoxide 80-15-9 | 201-254-7 01-2119475796-19 | 0,1- < 1 % | STOT RE 2 H373 Skin Corr. 1B H314 Acute Tox. 2; Inhalation H330 Aquatic Chronic 2 H411 Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Org. Perox. E H242 |
| Linalool 78-70-6 | 201-134-4 01-2119474016-42 | 0,1- < 1 % | Skin Irrit. 2 H315 Eye Irrit. 2 H319 Skin Sens. 1B H317 |

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

Prolonged or repeated contact may cause skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Refer to Technical Data Sheet

7.3. Specific end use(s)

Anaerobic

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|------------------------------|--|-----------------|
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST] | | 6 | Time Weighted Average (TWA): | | EH40 WEL |
| Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST] | | 2,4 | Time Weighted Average (TWA): | | EH40 WEL |
| Silicon dioxide 112945-52-5 [Dust, respirable dust] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Silicon dioxide 112945-52-5 [Dust, inhalable dust] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |

Occupational Exposure Limits

Valid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|------------------------------|--|-----------------|
| Fluorophlogopite (Mg ₃ K[AlF ₂ O(SiO ₃) ₃]) 12003-38-2 [FLUORIDE] | | 2,5 | Time Weighted Average (TWA): | | IR_OEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE] | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS] | | 6 | Time Weighted Average (TWA): | | IR_OEL |
| Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS] | | 2,4 | Time Weighted Average (TWA): | | IR_OEL |
| Silicon dioxide 112945-52-5 [DUSTS NON-SPECIFIC] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Silicon dioxide 112945-52-5 [DUSTS NON-SPECIFIC] | | 4 | Time Weighted Average (TWA): | | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|---|------------------------------|-----------------|--------------|-----|--------------|--------|----------------------|
| | | | mg/l | ppm | mg/kg | others | |
| Octan-1-ol 111-87-5 | aqua (marine water) | | 0,02 mg/l | | | | |
| Octan-1-ol 111-87-5 | sediment (freshwater) | | | | 2,1 mg/kg | | |
| Octan-1-ol 111-87-5 | sediment (marine water) | | | | 0,21 mg/kg | | |
| Octan-1-ol 111-87-5 | aqua (freshwater) | | 0,2 mg/l | | | | |
| Octan-1-ol 111-87-5 | sewage treatment plant (STP) | | 55,5 mg/l | | | | |
| Octan-1-ol 111-87-5 | Soil | | | | 1,6 mg/kg | | |
| Titanium dioxide 13463-67-7 | aqua (freshwater) | | | | | | no hazard identified |
| Titanium dioxide 13463-67-7 | aqua (marine water) | | | | | | no hazard identified |
| Titanium dioxide 13463-67-7 | sewage treatment plant (STP) | | | | | | no hazard identified |
| Titanium dioxide 13463-67-7 | sediment (freshwater) | | | | | | no hazard identified |
| Titanium dioxide 13463-67-7 | sediment (marine water) | | | | | | no hazard identified |
| Titanium dioxide 13463-67-7 | Soil | | | | | | no hazard identified |
| Titanium dioxide 13463-67-7 | Aquatic (intermit. releases) | | | | | | no hazard identified |
| Titanium dioxide 13463-67-7 | Predator | | | | | | no hazard identified |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (freshwater) | | 0,0031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (marine water) | | 0,00031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (intermittent releases) | | 0,031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Sewage treatment plant | | 0,35 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sediment (freshwater) | | | | 0,023 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sediment (marine water) | | | | 0,0023 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Soil | | | | 0,0029 mg/kg | | |
| Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6 | aqua (freshwater) | | 0,2 mg/l | | | | |
| Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6 | aqua (marine water) | | 0,02 mg/l | | | | |
| Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6 | aqua (intermittent releases) | | 2 mg/l | | | | |
| Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6 | sediment (freshwater) | | | | 2,22 mg/kg | | |
| Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6 | sediment (marine water) | | | | 0,222 mg/kg | | |
| Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6 | Soil | | | | 0,327 mg/kg | | |
| Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6 | sewage treatment plant (STP) | | > 10 mg/l | | | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|---|--------------------|-------------------|--|---------------|------------|---------|
| Octan-1-ol 111-87-5 | Workers | dermal | Acute/short term exposure - systemic effects | | 125 mg/kg | |
| Octan-1-ol 111-87-5 | Workers | inhalation | Acute/short term exposure - systemic effects | | 220 mg/m3 | |
| Octan-1-ol 111-87-5 | Workers | dermal | Long term exposure - systemic effects | | 125 mg/kg | |
| Octan-1-ol 111-87-5 | Workers | inhalation | Long term exposure - systemic effects | | 220 mg/m3 | |
| Octan-1-ol 111-87-5 | General population | inhalation | Acute/short term exposure - systemic effects | | 65 mg/m3 | |
| Octan-1-ol 111-87-5 | General population | oral | Acute/short term exposure - systemic effects | | 75 mg/kg | |
| Octan-1-ol 111-87-5 | General population | dermal | Long term exposure - systemic effects | | 75 mg/kg | |
| Octan-1-ol 111-87-5 | General population | inhalation | Long term exposure - systemic effects | | 65 mg/m3 | |
| Octan-1-ol 111-87-5 | General population | oral | Long term exposure - systemic effects | | 75 mg/kg | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Workers | inhalation | Long term exposure - systemic effects | | 6 mg/m3 | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | Workers | dermal | Acute/short term exposure - systemic effects | | 5 mg/kg | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | Workers | inhalation | Acute/short term exposure - systemic effects | | 16,5 mg/m3 | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | Workers | dermal | Long term exposure - systemic effects | | 2,5 mg/kg | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | Workers | inhalation | Long term exposure - systemic effects | | 2,8 mg/m3 | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | General population | inhalation | Acute/short term exposure - systemic effects | | 4,1 mg/m3 | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | General population | oral | Acute/short term exposure - systemic effects | | 1,2 mg/kg | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | General population | dermal | Acute/short term exposure - systemic effects | | 2,5 mg/kg | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | General population | dermal | Long term exposure - systemic effects | | 1,25 mg/kg | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | General population | inhalation | Long term exposure - systemic effects | | 0,7 mg/m3 | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | General population | oral | Long term exposure - systemic effects | | 0,2 mg/kg | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | General population | dermal | Long term exposure - local effects | | 1,5 mg/cm2 | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | Workers | dermal | Long term exposure - local effects | | 3 mg/cm2 | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | Workers | dermal | Acute/short term exposure - local effects | | 3 mg/cm2 | |
| Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6 | General population | dermal | Acute/short term exposure - local effects | | 1,5 mg/cm2 | |

effects

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|----------------------------|------------------------------------|
| Appearance | paste paste, liquid white |
| Odor | slightly |
| Odour threshold | No data available / Not applicable |
| pH | Not applicable |
| Melting point | No data available / Not applicable |
| Solidification temperature | No data available / Not applicable |
| Initial boiling point | No data available / Not applicable |
| Flash point | > 93 °C (> 199.4 °F); no method |
| Evaporation rate | No data available / Not applicable |
| Flammability | No data available / Not applicable |
| Explosive limits | No data available / Not applicable |
| Vapour pressure | No data available / Not applicable |
| Relative vapour density: | No data available / Not applicable |

| | |
|--|------------------------------------|
| Density | No data available / Not applicable |
| Bulk density | No data available / Not applicable |
| Solubility | No data available / Not applicable |
| Solubility (qualitative) (Solvent: Water) | Insoluble |
| Solubility (qualitative) (Solvent: Acetone) | Soluble |
| Partition coefficient: n-octanol/water | No data available / Not applicable |
| Auto-ignition temperature | No data available / Not applicable |
| Decomposition temperature | No data available / Not applicable |
| Viscosity | No data available / Not applicable |
| Viscosity (kinematic) | No data available / Not applicable |
| Explosive properties | No data available / Not applicable |
| Oxidising properties | No data available / Not applicable |

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Peroxides.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

General toxicological information:

Prolonged or repeated contact may cause skin irritation.

11.1. Information on toxicological effects**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---------------------------------|---------------|---------------|---------|---|
| Octan-1-ol 111-87-5 | LD50 | > 5.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Titanium dioxide 13463-67-7 | LD50 | > 5.000 mg/kg | rat | OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure) |
| Cumene hydroperoxide 80-15-9 | LD50 | 382 mg/kg | rat | other guideline: |
| Linalool 78-70-6 | LD50 | 2.790 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---------------------------------|--|------------------------|---------|--|
| Octan-1-ol 111-87-5 | LD50 | 2.000 - 4.000 mg/kg | rabbit | |
| Octan-1-ol 111-87-5 | Acute toxicity estimate (ATE) | 2.500 mg/kg | | Expert judgement |
| Titanium dioxide 13463-67-7 | LD50 | >= 10.000 mg/kg | hamster | not specified |
| Cumene hydroperoxide 80-15-9 | LD50 | 530 - 1.060 mg/kg | rat | other guideline: |
| Cumene hydroperoxide 80-15-9 | Acute toxicity estimate (ATE) | 1.100 mg/kg | | Expert judgement |
| Linalool 78-70-6 | LD50 | 5.610 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|---------------------------------|---------------|-------------|-----------------|------------------|---------|---------------|
| Titanium dioxide 13463-67-7 | LC50 | > 6,82 mg/l | dust | 4 h | rat | not specified |
| Cumene hydroperoxide 80-15-9 | LC50 | 1,370 mg/l | vapour | 4 h | rat | not specified |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---------------------------------|------------------------|------------------|---------|---|
| Octan-1-ol 111-87-5 | slightly irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Titanium dioxide 13463-67-7 | not irritating | 4 h | rabbit | equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Cumene hydroperoxide 80-15-9 | corrosive | | rabbit | Draize Test |
| Linalool 78-70-6 | irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---------------------------------|----------------|------------------|---------|---|
| Octan-1-ol 111-87-5 | irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Titanium dioxide 13463-67-7 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Linalool 78-70-6 | irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|---------------------------------|-----------------|---------------------------------------|------------|--|
| Octan-1-ol 111-87-5 | not sensitising | Draize Test | guinea pig | Draize Test |
| Titanium dioxide 13463-67-7 | not sensitising | Mouse local lymphnode assay (LLNA) | mouse | equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| Linalool 78-70-6 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|---------------------------------|----------|--|--|---------|---|
| Octan-1-ol 111-87-5 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Octan-1-ol 111-87-5 | negative | mammalian cell gene mutation assay | with and without | | equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Titanium dioxide 13463-67-7 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Titanium dioxide 13463-67-7 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Titanium dioxide 13463-67-7 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Cumene hydroperoxide 80-15-9 | positive | bacterial reverse mutation assay (e.g Ames test) | without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Linalool 78-70-6 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Linalool 78-70-6 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Linalool 78-70-6 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Octan-1-ol 111-87-5 | negative | oral: gavage | | mouse | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| Titanium dioxide 13463-67-7 | negative | oral: gavage | | mouse | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| Cumene hydroperoxide 80-15-9 | negative | dermal | | mouse | not specified |
| Linalool 78-70-6 | negative | oral: gavage | | mouse | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|---------------------------------|------------------|-------------------------|---|---------|-------------|--|
| Titanium dioxide 13463-67-7 | not carcinogenic | inhalation | 24 m 6 h/d; 5 d/w | rat | male/female | OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|---------------------------------|---|-----------|-------------------------|---------|--|
| Titanium dioxide 13463-67-7 | NOAEL P > 1.000 mg/kg NOAEL F1 > 1.000 mg/kg | | oral: gavage | rat | OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test) |
| Linalool 78-70-6 | NOAEL P 365 mg/kg NOAEL F1 365 mg/kg | | oral: gavage | rat | OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|---------------------------------|-------------------|-------------------------|--|---------|--|
| Octan-1-ol 111-87-5 | NOAEL 1.000 mg/kg | dermal | 90 d 6 h/d, 5 d/w | rat | OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) |
| Titanium dioxide 13463-67-7 | NOAEL 1.000 mg/kg | oral: gavage | 90 d daily | rat | OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| Cumene hydroperoxide 80-15-9 | | inhalation: aerosol | 6 h/d 5 d/w | rat | not specified |
| Linalool 78-70-6 | NOAEL 117 mg/kg | oral: gavage | 28 d daily | rat | OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents) |

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|-----------------------------|---------------|---|--|
| Octan-1-ol 111-87-5 | LC50 | 13,3 mg/l | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Titanium dioxide 13463-67-7 | LC50 | Toxicity > Water solubility | 48 h | Leuciscus idus | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Cumene hydroperoxide 80-15-9 | LC50 | 3,9 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Linalool 78-70-6 | LC50 | 27,8 mg/l | 96 h | Salmo gairdneri (new name: Oncorhynchus mykiss) | OECD Guideline 203 (Fish, Acute Toxicity Test) |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|-----------------------------|---------------|---------------|--|
| Octan-1-ol 111-87-5 | EC50 | 47 mg/l | 24 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Titanium dioxide 13463-67-7 | EC50 | Toxicity > Water solubility | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Cumene hydroperoxide 80-15-9 | EC50 | 18,84 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Linalool 78-70-6 | EC50 | 59 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|--------|---------------|---------------|---|
| Octan-1-ol 111-87-5 | NOEC | 1 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|-----------------------------|---------------|---|---|
| Octan-1-ol 111-87-5 | EC10 | 4,2 mg/l | 48 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | DIN 38412-09 |
| Octan-1-ol 111-87-5 | EC50 | 14 mg/l | 48 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | DIN 38412-09 |
| Titanium dioxide 13463-67-7 | EC50 | Toxicity > Water solubility | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Cumene hydroperoxide 80-15-9 | EC50 | 3,1 mg/l | 72 h | Desmodesmus subspicatus (reported as Scenedesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Cumene hydroperoxide 80-15-9 | NOEC | 1 mg/l | 72 h | Desmodesmus subspicatus (reported as Scenedesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Linalool 78-70-6 | EC50 | 88,3 mg/l | 96 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Linalool 78-70-6 | EC10 | 38,4 mg/l | 96 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|-----------------------------|---------------|-------------------------|--|
| Octan-1-ol 111-87-5 | EC 50 | 350 mg/l | 3 h | activated sludge | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| Titanium dioxide 13463-67-7 | EC0 | Toxicity > Water solubility | 24 h | Pseudomonas fluorescens | DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test) |
| Cumene hydroperoxide 80-15-9 | EC10 | 70 mg/l | 30 min | | not specified |
| Linalool 78-70-6 | EC0 | 100 mg/l | 3 h | | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |

12.2. Persistence and degradability

The product is not biodegradable.

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|---------------------------------|----------------------------|-----------|---------------|---------------|--|
| Octan-1-ol 111-87-5 | readily biodegradable | aerobic | 92 % | 28 d | OECD Guideline 310 (Ready Biodegradability CO2 in Sealed Vessels (Headspace Test)) |
| Cumene hydroperoxide 80-15-9 | not readily biodegradable. | aerobic | 3 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| Linalool 78-70-6 | readily biodegradable | aerobic | > 97,1 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| Linalool 78-70-6 | inherently biodegradable | | 100 % | 13 d | OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test) |

12.3. Bioaccumulative potential

| Hazardous substances CAS-No. | Bioconcentration factor (BCF) | Exposure time | Temperature | Species | Method |
|---------------------------------|-------------------------------|---------------|-------------|-------------|---|
| Cumene hydroperoxide 80-15-9 | 9,1 | | | calculation | OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) |

12.4. Mobility in soil

Cured adhesives are immobile.

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---------------------------------|--------|-------------|--|
| Octan-1-ol 111-87-5 | 3,5 | 23 °C | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| Cumene hydroperoxide 80-15-9 | 1,6 | 25 °C | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| Linalool 78-70-6 | 3,1 | 25 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT / vPvB |
|---------------------------------|---|
| Octan-1-ol 111-87-5 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Titanium dioxide 13463-67-7 | According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances. |
| Cumene hydroperoxide 80-15-9 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Linalool 78-70-6 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Do not empty into drains / surface water / ground water.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Not dangerous goods |

14.2. UN proper shipping name

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Not dangerous goods |

14.3. Transport hazard class(es)

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Not dangerous goods |

14.4. Packing group

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Not dangerous goods |

14.5. Environmental hazards

| | |
|------|----------------|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

14.6. Special precautions for user

| | |
|------|----------------|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|---|----------------|
| Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): | Not applicable |
| Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): | Not applicable |
| Persistent organic pollutants (Regulation (EU) 2019/1021): | Not applicable |

EU. REACH, Annex XVII, Marketing and Use Restrictions (Regulation 1907/2006/EC): Not applicable

VOC content < 3 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H242 Heating may cause a fire.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.