

# ACCESSORIES

Save valuable workspace



The ERSA Stacking Rack saves space by letting you stack two soldering stations safely on the workbench by means of the special recesses in the base plate and the rear wall. There is no danger of your ERSA soldering stations slipping.

**Order no.:**  
**STR 100** Stacking Rack  
 (Delivery without soldering station)

## ERSA STR 100 Stacking Rack for soldering stations



**Specifications:**  
 Sn63Pb37; Sn60Pb40;  
 Sn60Pb38Cu2; Sn62Pb36Ag2;  
 Lead-free solder wire Sn96,5Ag3,5  
 and Tiffany solder wire

**Dimensions:**  
 0.6 mm (0.024 in); 0.8mm (0.031 in);  
 1.0 mm (0.039 in); 1.5 mm (0.059 in)  
 and 2.0 mm (0.079 in) on 100 g  
 (4 oz), 250 g (10 oz) and 500 g  
 (20 oz) spool. 1.0 mm (0.039 in);  
 1.5 mm (0.059 in) and 2.0 mm  
 (0.079 in) on 1,000 g(40 oz) spools.  
 Other alloys, wire diameter, packing  
 drumsizes and quantities on request.

**Order nos.:**  
 see separate ERSA price list

## ERSA Solder wire



**Order nos:**  
**FMKANC 32-005**  
 No-Clean flux core cream F-SW 32,  
 DIN 8511, 5 ml cartridge on  
 colophony basis, low activated,  
 incl. tappet and 1 needle (plastic)  
 diameter 0.4 mm (0.016 in)

**FMIF8001-PEN**  
 Flux-Pen with flux core IF 8001,  
 FSW-34, DIN 8511, 7 ml  
**FMIF 2005-001**  
 Low solid No-Clean flux core  
 IF 2005 M F-SW 34, DIN 8511, 100 ml  
 (without picture)

## ERSA SMD solder paste / flux cream



ERSA desoldering wicks are indispensable for effectively and gently removing flux and solder residue from SMD-boards in particular. Fine tissue, high capillarity and optimal flux content ensure optimal soldering results.

**Order nos.:**  
 No-Clean desold. wicks, 1.5 m (4.9ft) long  
**WICK NC 1,5/10** 1.5 mm (0.06 in) width  
 (10 pieces)  
**WICK NC 2,2/10** 2.2 mm (0.09 in) width  
 (10 pieces)  
**WICK NC 2,7/10** 2.7 mm (0.1 in) width  
 (10 pieces)  
**WICK-NC SET** No-Clean desold.wicks  
 consisting of WICK NC 1,5 (1 pcs), WICK  
 NC 2,2 (2 pcs) and WICK NC 2,7 (1 pcs.)

## ERSA Desoldering wicks

A must for every workbench



This ESD-safe tool allows for quick and reliable replacement of all internally heated ERSA soldering tips and the 422-type desoldering inserts. It incorporates an additional

side cutter and screw driver allowing the multi-purpose use of this versatile tool.  
**Order no.:**  
**3ZT00164** Tip exchanger



Crooked tweezers to grip components easily and safely.

**Order no.:**  
**3ZT00165** Crooked tweezers

## ERSA Tip Exchanger / Tweezers