

Heldite, 51 Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.ltd/Heldite

April 2018

PRODUCT DATA SHEET

	111111111111111111111111111111111111111
Product	H2OK Potable Water Pipe Jointing Compound
Туре	Semi-permanent pipe and thread sealant.
Intended Use	Designed to seal bolted, flanged or screwed pipe joints to prevent leakage in most engineering situations and plumbing systems delivering hot and cold potable water and low pressure steam
Special Features	Silicone-based, does not support microbiological growth. Non-toxic, environmentally friendly. A WRAS approved material - meets the requirements of the Water Regulations Advisory Scheme (WRAS) Tests of effect on Water Quality, BS 6920:2014: Parts 1 – 3/ Hot (up to 85 Centigrade) and Cold Water Use.
Preparation	All joints must be completely clean, dry and free from any cleansing agents or loose material prior to application.
Application	Apply with a putty knife.
Coats	For screwed joints apply one coat around cleaned mating thread, remove excess material and screw up immediately.
Drying Time	Not applicable.
Re-coating Time	As required immediately.
Application Temp.	Ideally 15 – 25°C
Coverage	Approximately 16 squares metres per litre.
Maintenance	Not applicable.
Compatibility	Compatible with most metals, plastics and rubber.
Settlement	Stir well before use.
Shelf-life/Storage	Many years if stored in a cool, dry area in original sealed container.
Hazards	Do not eat or drink while using product. Keep container tightly closed. Keep away from children and pets. For full product safety data sheet visit www.rustins.ltd/Heldite
Clean-Up	Clean equipment and brushes with white spirit.
Sizes	250ml