



- ROBUST** : Switches with gilt contacts.
 - Metal case, epoxy finish.
- PRECISE** : Good long-term stability.
 - Q factor between 55 and 100, depending on decade.
- EASY** : 19" standard rack size tilted front panel.
 - Intermediate tap at each decade.



ROBUST
INDUCTANCE from
1 μ H to 11,111 110 H



Specifications

- Each decade consists of inductors wound around a ferrite pot core, which gives a Q factor between 55 and 100.
- Like all inductors of this type, the applied voltage mostly depends on the operating frequency. The voltage must be limited to avoid core saturation and overheating.
- Professional quality switches with gilt contacts.
- Output of each decade on 4 mm safety socket.
- Screen outputs (front panel and case) on safety earth socket.

Other specifications

- Safety : Complies with EN 61010-1, overvoltage category I, pollution degree 1.
- Max voltage : 300 V AC/DC (reinforced insulation).
- Presentation : aluminium mounting plate, screen-printed satin epoxy finish, metal case, epoxy finish.

Décade	x 1 μ H	x10 μ H	x100 μ H	x1 mH	x10 mH	x100 mH	x 1H
Q factor	55	55	60	70	100	100	60
Frequency	5 M	1 M	500 k	500 k	50 k	50 k	10 k
Max DC current	800 mA	700 mA	380 mA	140 mA	70 mA	50 mA	40 mA
Max resistance	0,25 Ω	0,55 Ω	1,8 Ω	3,4 Ω	12,1 Ω	82 Ω	250 Ω
Accuracy	5%	5%	5%	5%	5%	5%	10%

- The assembly is mounted on the front panel which fits into a 19" standard subrack.
- Mounting plate dimensions: H = 2U (U = 44,45 mm)
L = 84F (F = 5,08 mm)

