


**RoHS
Compliant**



Description

The product is a double sided thermally conductive adhesive tape. Thermal tapes are simple and convenient to use, which will drastically improve production efficiency. This product has several different thicknesses to allow an alternative to a range of screw fixings and hot melt adhesives.

Features

- Specifically designed for easy use and storage
- Excellent adhesion strength
- Very good thermal insulation
- Provided as a roll of 300mm × 300mm

Applications

- Heat sink security
- Vehicle control circuit boards
- LED light bar and metal frame assembly
- Excellent replacement for screws and hot melt adhesives

Physical Properties

Characteristic	Part Number		
	MPGCS-008T-300-0.1	MPGCS-008T-300-0.15	MPGCS-008T-300-0.25
Thickness	0.1mm	0.15mm	0.25mm
Colour	Colour		
Carrier	Fibreglass		
Adhesion	1.1	1.4	1.4
Breakdown Voltage	2kV	3kV	3.8kV
Temperature Resistance			
Short term	120°C		
Long term	180°C		
Thermal conductivity (ASTM-D5470)	0.8 W/mk		
Temperature Usage Range	-20°C to +120°C		
Flame Rating	UL94 V-0		

Part Number Table

Description	Part Number
Thermally Conductive Adhesive Tape, White, 0.8 W/mk, 300mm × 300mm × 0.1mm	MPGCS-008T-300-0.1
Thermally Conductive Adhesive Tape, White, 0.8 W/mk, 300mm × 300mm × 0.15mm	MPGCS-008T-300-0.15
Thermally Conductive Adhesive Tape, White, 0.8 W/mk, 300mm × 300mm × 0.25mm	MPGCS-008T-300-0.25

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.