

Thunderbolt 3 Dock - Dual 4K 60Hz Monitor TB3 Laptop Docking Station with DisplayPort, HDMI & 1080p VGA - 85W Power Delivery & Charging - 2x USB-A, Ethernet - Mac & Windows

Product ID: TB3DK2DHVUE



Create a powerful and flexible workstation with this Thunderbolt 3 dock. With dedicated dual video output, you can connect your Thunderbolt 3 equipped MacBook Pro or Windows laptop to two 4K monitors, through a single Thunderbolt 3 cable.

Simply connect the TB3 dock to your laptop with included TB3 cable and start working immediately. No time-consuming driver installations are required.

Great for editing 4K video or other Ultra HD tasks, this Thunderbolt 3 docking station supports 40Gbps speeds and 4K resolution at 60Hz on two monitors. Enjoy ultimate flexibility in setting up your workstation, with monitor options including DisplayPort (DP), HDMI and VGA.

The dock offers many dedicated dual-video options:

2x DisplayPort (4096 x 2160p @ 60Hz)

1x DisplayPort + 1 HDMI (4096 x 2160p @ 60Hz)

1x VGA (1920 x 1200p @ 60Hz) + 1x DisplayPort (4096 x 2160p @ 60Hz)

1x VGA (1920 x 1200p @ 60Hz) + 1x HDMI (4096 x 2160p @ 60Hz)

Harness the reliability and speed of a wired network connection with the Gigabit Ethernet port (supporting PXE Boot and Wake-on-LAN). Connect your USB devices with two USB 3.0 Type-A ports.

Through a single 120W power adapter, the Thunderbolt 3 docking station simultaneously powers and charges your laptop and your attached peripherals while it's docked. It provides up to 85W of charging power through Power Delivery.

The TB3DK2DHVUE is fully Thunderbolt 3 Certified and backed by a StarTech.com 3-year warranty and free lifetime technical support.



Certifications, Reports and Compatibility

Applications

- Review or edit images, video or media files on two 4K displays
- Ideal for permanent or mobile workstations, with multiple monitor options

Features

- HIGH PERFORMANCE FEATURES: This Thunderbolt 3 certified dock supports dual 4K60Hz on DisplayPort and HDMI, 1080p VGA, 85W Power Delivery for laptop charging, 2-port USB-A hub & gigabit Ethernet ports
- FLEXIBLE MONITOR COMBINATIONS: Offers support for new and legacy monitors in mulitple video output combinations. Dual DP, DP + HDMI, DP + VGA, or HDMI + VGA for creative and productivity usage.
- EASY TO DEPLOY & SETUP: Thunderbolt 3 Dock requires no driver setup or additional display adapters and with the included Thunderbolt 3 cable and front facing host port, this dock is easy to install
- WIDE COMPATIBILITY: TB3 docking station for Thunderbolt 3 laptops incl. MacBook; extended dual display support on MacBook Pro/Air with Intel processor & single display with Apple M1 Chip; supports other major operating systems like Windows and macOS
- IDEAL FOR CREATIVE PROFESSIONALS: The high performance Thunderbolt 3 port replicator is perfect for professionals in photography, video production, CAD, Industrial, and Architectural designers

Hardware		
	Warranty	3 Years
	4K Support	Yes
	Fast-Charge Port(s)	Yes
	Displays Supported	2
	Bus Type	Thunderbolt 3
	Industry Standards	Thunderbolt 3
		IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
		USB 3.0 - Backward compatible with USB 2.0 and 1.
	Chipset ID	Intel - Alpine Ridge JHL6540



Intel - WGI210AT

ASMedia - ASM1042A

Parade - PS176

Chrontel - CH7517

Performance

Maximum Data Transfer

Rate

40 Gbps (Thunderbolt 3)

5 Gbps (USB 3.0)

2 Gbps (Ethernet; Full-Duplex)

Maximum Digital Resolutions

Dual display - DisplayPort - 4096 x 2160p @ 60Hz

Dual display - 1x DisplayPort + 1x HDMI - 4096 x 2160p @ 60Hz

Dual display - 1x VGA 1920 x 1200 @ 60Hz + 1x DisplayPort

4096 x 2160p @ 60Hz

Dual display - 1x VGA 1920 x 1200 @ 60Hz + 1x HDMI 4096 x

2160p @ 60Hz

Single display - DisplayPort - 4096 x 2160p @ 60Hz

Single display - VGA - 1920 x 1200 @ 60Hz

Single display - HDMI - 4096 x 2160p @ 60Hz

Type and Rate

Thunderbolt 3 - 40 Gbit/s

UASP Support

Yes

Compatible Networks

10/100/1000 Mbps

Auto MDIX

Yes

PXE

Yes

Full Duplex Support

Yes

Connector(s)

Connector Type(s)

Thunderbolt 3 USB-C (24-pin) (40Gbps)

DisplayPort (20 pin)

HDMI (19 pin)

VGA (15 pin, High Density D-Sub)

USB Type-A (9 pin) USB 3.0 (5 Gbps)



RJ-45

Software	OS Compatibility	Windows 7, 8, 8.1, 10, 11 macOS 10.12 - 10.15, 11.0, 12.0
Special Notes / Requirements		
Requirements	System and Cable Requirements	Thunderbolt 3 equipped computer with a Thunderbolt 3 port
	Note	A 4K-capable display is required to achieve 4K x 2K resolution (4K is also known as 4K x 2K).
		MacBook Air and MacBook Pro systems using the new Apple M1 chip support only a single external display over the Thunderbolt 3 ports, even when connected to a Thunderbolt 3 docking station with more than one video output. This single monitor limitation does not affect Intel-based Macs with Thunderbolt 3.
Power	Power Source	AC Adapter Included
	Power Delivery	85W
	Input Voltage	100 - 240 AC
	Input Current	1.8 A
	Output Voltage	19V DC
	Output Current	6.32 A
	Center Tip Polarity	Positive
	Plug Type	N
	Power Consumption (In Watts)	120W
Environmental Environmental		
	Operating Temperature	0C to 40C (32F to 104F)
	Storage Temperature	-20C to 70C (-4F to 158F)
	Humidity	20~80% RH (Non-condensing)
Physical Characteristics		
	Color	Gray



	Material	Aluminum
	Cable Length	19.7 in [50 cm]
	Product Length	7.7 in [19.6 cm]
	Product Width	2.3 in [58.6 mm]
	Product Height	0.9 in [23.5 mm]
	Weight of Product	12.0 oz [340 g]
Packaging Information		
	Package Length	10.0 in [25.4 cm]
	Package Width	7.4 in [18.7 cm]
	Package Height	2.6 in [65 mm]
	Shipping (Package) Weight	2.9 lb [1.3 kg]
What's in the Box		
	Included in Package	docking station
		Thunderbolt 3 cable
		universal power adapter
		power cords (UK, EU)
		instruction manual

^{*}Product appearance and specifications are subject to change without notice.