## USB 3.1 CM to AF Cable

# pro-signal



#### **Specifications**

### RoHS Compliant

Connector to Connector : Type C Plug to Type A Receptacle

Contact Resistance :  $3\Omega$  Max.


Insulation Resistance : DC 300V/10ms,  $10M\Omega$  Min.

USB Standard : USB 3.1

Cable Length : 150mm (0.49ft)

Jacket Colour : Black

### Diagram



No	Description	Qty.	Unit
1	[30AWG+EAM]×2P+[30AWG+A]×1P+24AWG×1C+A2EB OD:4.5mm Black PVC No mark	1	m
2	USB3.0 AF Blue insulation Pin plated gold	1	Pcs
3	USB 3.1C Type Connector PCB=SMT(C:10nf+R:5.1kΩ) Shell plated nickel	'	FUS
4	Transparent PE	2	
5	45P PVC Black	12	g
6	USB Type C Shell plated nickel up	1 Pcs	
7	USB Type C Shell plated nickel down	I	FUS
8	Low pressure molding compound	0.5	g

#### **Part Number Table**

	Description	Part Number
ı	USB 3.1 CM to AF Cable, 150mm	PSG91481

**Dimensions: Millimetres** 

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands

