



MASTER VALUE LEDspot MV

MASTER LED spot VLE D 3.7-35W GU10 927 60D

Delivering a warm, halogen-like accent beam, the MASTER VALUE LEDspot MV is a perfect for spot-lighting. Thanks to its high CRI, it achieves more natural colours, enabling cosy and comfortable ambience for residential and hospitality situations, and emphasising the beauty of merchandise in retail. These LEDspots have the familiar look and feel of glass spots, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables creation of the desired atmosphere, and it works with a broad selection of dimmers.

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

Product data


General Information	
Cap base	GU10 [GU10]
EU RoHS compliant	Yes
Nominal lifetime (nom.)	25000 h
Switching cycle	50,000X
	Narrow Cone
Light Technical	
Colour Code	927 [CCT of 2,700 K]
Beam Angle (Nom)	60 °
Luminous flux (nom.)	270 lm
Luminous intensity (nom.)	300 cd

Colour designation	Warm white (WW)
Correlated Colour Temperature (Nom)	2700 K
Luminous efficacy (rated) (nom.)	72.00 lm/W
Colour consistency	<6
Colour rendering index (nom.)	90
LLMF at end of nominal lifetime (nom.)	70 %
Luminous flux in 90° cone (rated)	270 lm
Operating and Electrical	
Input frequency	50 to 60 Hz
Power (Rated) (Nom)	3.7 W
Lamp current (nom.)	18 mA

MASTER VALUE LEDspot MV


Wattage equivalent	35 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light (nom.)	0.5 s
Power factor (nom.)	0.9
Voltage (Nom)	220-240 V
Temperature	
T-Case maximum (nom.)	70 °C
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb shape	PAR16 [PAR 2 inch]
Approval and Application	
Energy Efficiency Class	F

Dimensional drawing



GU10 220-240V 3.7-35W 270lm 60D 2700K D


Photometric data



LEDspots MAS VLED SLR 3,7W PAR16 GU10 927 60D-POC-POC

Suitable for accent lighting	Yes
Energy consumption kWh/1,000 hours	4 kWh
	467608
Product Data	
Full product code	871951431226500
Order product name	MASTER LED spot VLE D 3.7-35W GU10 927 60D
EAN/UPC – product	8719514312265
Order code	31226500
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
SAP material	929002979802
SAP net weight (piece)	0.038 kg


Product	D	C
MASTER LED spot VLE D 3.7-35W GU10 927 60D	50 mm	54 mm



LEDspots MAS VLED SLR 3,7W PAR16 GU10 927 60D-ADL-ADL


MASTER VALUE LEDspot MV

Photometric data




LEDspots MAS VLED SLR 3,7W PAR16 GU10 927 60D-LDD-LDD

Lifetime



LEDspots LED 25K



LEDspots LMP 25K

