Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET



1/13

Techspray ProWick Desoldering Flux coated braid (UK HSE - Great Britain)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: Techspray ProWick Desoldering Flux coated braid (UK HSE - Great Britain)
Product code	: 1802/1803/1804/1805/1806/1808/1809/1810/ 1811/1812/1813 All Part Numbers
Product description	: Soldering Remover.
Product type	: Solid.
Other means of identification	: Soldering Remover. Industrial/Professional use UFI:GY3C-H04K-7006-PEGW

1.2 Relevant identified uses of the substance or mixture and uses advised against Not applicable.

1.3 Details of the supplier of the safety data sheet

Manufacturer Techspray 8125 Cobb Center Drive Kennesaw, GA 30152 Tel:678-819-1408 Toll free: 800-858-4043 Fax: 806-372-8750

Distributor

Impoter ITW Contamination Control BV Saffierlaan 5 VZ-2132 Hoofddorp The Netherlands Email: info@itw-cc.com Tel: +31 88 1307 400 FAX: +31 88 1307 499

e-mail address of person : info@itw-cc.com responsible for this SDS

National contact

ITW Contamination Control BV Saffierlaan 5 VZ-2132 Hoofddorp The Netherlands Email: info@itw-cc.com Tel: +31 88 1307 400 FAX: +31 88 1307 499

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number	: EMERGENCY HEALTH INFORMATION:
	United Kingdom (England or Wales) 0845 46 47 or Scotland 08454 24 24 24 (UK only).
<u>Supplier</u>	
Telephone number	: (800)-858-4043

relephone number	. (000)-030-4	043		
Date of issue/Date of revision	: 12/17/2021	Date of previous issue	: 12/17/2021	Version : 7

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Hours of operation	: 8:00 AM to 5:00 PM
Information limitations	: EMERGENCY HEALTH INFORMATION:
	EMERGENCY SPILL INFORMATION:
	Transport information

SECTION 2: Hazards identification

 2.1 Classification of the substance or mixture

 Product definition
 : Mixture

 Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 Skin Sens. 1, H317

 Aquatic Acute 1, H400

 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity: 3 percent of the mixture consists of component(s) of unknown acute dermal toxicity 3 percent of the mixture consists of component(s) of unknown acute inhalation toxicity

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	1	May cause an allergic skin reaction. Very toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	1	Wear protective gloves. Avoid release to the environment. Avoid breathing dust. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
Response	:	Collect spillage. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	1	Not applicable.
Disposal	1	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	rosin
Supplemental label elements	:	FOR INDUSTRIAL USE ONLY For professional use only. Recycling/recovery of copper In accordance with regional regulations UK: Caution: exposure to fumes from this material may cause certain sensitive individuals to develop eczema and/or occupational asthma. May cause sensitization by inhalation and skin contact. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles		Not applicable.
Special packaging requirem	<u>ien</u>	t <u>s</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.

Techspray ProWick Desoldering Flux coated braid (UK HSE - Great Britain)

SECTION 2: Hazards identification

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures :	Mixture	I	1	
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
copper	EC: 231-159-6 CAS: 7440-50-8	≥90	Aquatic Acute 1, H400 (M=10000) Aquatic Chronic 2, H411	[1]
rosin	EC: 232-475-7 CAS: 8050-09-7 Index: 650-015-00-7	≤3	Skin Sens. 1, H317	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Techspray ProWick Desoldering Flux coated braid (UK HSE - Great Britain)

SECTION 4: First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
4.2 Most important symptom	ns and effects, both acute and delayed
Over-exposure signs/symp	<u>ptoms</u>
Eye contact	: Adverse symptoms may include the following: irritation redness watering
Inhalation	: Adverse symptoms may include the following: asthma wheezing and breathing difficulties May cause sensitisation by inhalation. respiratory tract irritation
Skin contact	: Adverse symptoms may include the following: irritation redness sensitiser May cause allergic reactions in certain individuals.
Ingestion	: Adverse symptoms may include the following: Ingestion Seek medical attention.
4.3 Indication of any immed	iate medical attention and special treatment needed
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

: Use an extinguishing agent suitable for the surrounding fire.
: None known.
from the substance or mixture
: This material is very toxic to aquatic life. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
: No specific data.
: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Techspray ProWick Desoldering Flux coated braid (UK HSE - Great Britain)

SECTION 5: Firefighting measures

Special protective equipment for fire-fighters	-	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves)
		conforming to European standard EN 469 will provide a basic level of protection for
		chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	containment and cleaning up
Small spill	: Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: 12/17/2021

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Date of issue/Date of revision	Date	of issue/Date	of revision
--------------------------------	------	---------------	-------------

: 12/17/2021

5/13

SECTION 7: Handling and storage

Danger criteria		
	Notification and MAPP threshold	Safety report threshold
E1	100 tonne	200 tonne

7.3 Specific end use(s)

Recommendations

Demonstration

Industrial sector specific solutions

- : Not available.
- : UK: Caution: exposure to fumes from this material may cause certain sensitive individuals to develop eczema and/or occupational asthma. May cause sensitization by inhalation and skin contact. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name		Exposure limit valuesEH40/2005 WELs (United Kingdom (UK), 1/2020). Inhalation sensitiser.STEL: 0.15 mg/m³ 15 minutes. Form: FumeTWA: 0.05 mg/m³ 8 hours. Form: Fume		
rosin				
Recommended monitoring : procedures	atmosphere or k of the ventilation protective equip the following: E the assessment limit values and atmospheres - C exposure to che (Workplace atm for the measure	ontains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectiveness of or other control measures and/or the necessity to use respiratory ment. Reference should be made to monitoring standards, such as suropean Standard EN 689 (Workplace atmospheres - Guidance for a of exposure by inhalation to chemical agents for comparison with measurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment of emical and biological agents) European Standard EN 482 hospheres - General requirements for the performance of procedures ement of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be		

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
rosin	DNEL	Long term Oral	10 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	10 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	17 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	35 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	117 mg/m³	Workers	Systemic

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Date of issue/Date of revision : 12/17/2021 Date of previous issue : 12/17/2021

SECTION 8: Exposure controls/personal protection

	• •
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	1	Solid. [Metal.]
Colour	1	Various
Odour	1	Odourless.
Odour threshold	1	Not available.
Melting point/freezing point	1	Not available.
Initial boiling point and boiling range	1	Not available.
Flammability (solid, gas)	:	Not available.
Upper/lower flammability or explosive limits	1	Not applicable.
Flash point	:	Not applicable.
Auto-ignition temperature	1	Not applicable.
Decomposition temperature	4	Not available.
рН	4	Not available.
Viscosity	1	Not applicable.
Solubility(ies)	1	Not available.
Solubility in water	1	Not available.

SECTION 9: Physical and chemical properties

Partition coefficient: n-octanol/ water	:	Not applicable.
Vapour pressure	1	Not available.
Evaporation rate	4	Not available.
Relative density	1	Not available.
Vapour density	1	Not applicable.
Explosive properties	1	Not available.
Oxidising properties	:	Not available.
Particle characteristics		
Median particle size	1	Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
rosin	LD50 Oral	Rat	7600 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
rosin	7600	N/A	N/A	N/A	N/A

Irritation/Corrosion	
Conclusion/Summary	: Not available.
Sensitisation	
Conclusion/Summary	: Not available.
Mutagenicity	
Conclusion/Summary	: Not available.
Carcinogenicity	
Conclusion/Summary	: Not available.
Reproductive toxicity	
Conclusion/Summary	: Not available.
Teratogenicity	

Techspray ProWick Desoldering Flux coated braid (UK HSE - Great Britain)

Techspray ProWick Desoldering Flux coated braid (UK HSE - Great Britain)		
SECTION 11: Toxicological information		
Conclusion/Summary	: Not available.	
Specific target organ toxici	<u>ty (single exposure)</u>	
Not available.		
Specific target organ toxici	ty (repeated exposure)	
Not available.		
Aspiration hazard		
Not available.		
Information on likely routes of exposure	: Not available.	
Potential acute health effect		
Eye contact	: May cause eye irritation.	
Inhalation	: May cause sensitisation by inhalation.	
Skin contact	: May cause sensitisation by skin contact.	
Ingestion	: Do not ingest. If swallowed then seek immediate medical assistance.	
	ysical, chemical and toxicological characteristics	
Eye contact	: Adverse symptoms may include the following: irritation redness watering	
Inhalation	: Adverse symptoms may include the following: asthma wheezing and breathing difficulties May cause sensitisation by inhalation. respiratory tract irritation	
Skin contact	: Adverse symptoms may include the following: irritation redness sensitiser May cause allergic reactions in certain individuals.	
Ingestion	: Adverse symptoms may include the following: Ingestion Seek medical attention.	
Delayed and immediate effect	cts as well as chronic effects from short and long-term exposure	
Short term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Long term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	Not available.	
Potential chronic health eff Not available.	<u>ects</u>	
Conclusion/Summary	: Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.	
Carcinogenicity	: No known significant effects or critical hazards.	
Mutagenicity	: No known significant effects or critical hazards.	
Provide and the first state		

Reproductive toxicity : No known significant effects or critical hazards.

Date of issue/Date of revision

:12/17/2021

9/13

Techspray ProWick Desoldering Flux coated braid (UK HSE - Great Britain)

SECTION 11: Toxicological information

Other information

: UK: Caution: exposure to fumes from this material may cause certain sensitive individuals to develop eczema and/or occupational asthma. May cause sensitization by inhalation and skin contact. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure	
copper	Acute EC50 1100 µg/l Fresh water	Aquatic plants - Lemna minor	4 days	
	Acute EC50 2.1 µg/l Fresh water	Daphnia - Daphnia longispina - Juvenile (Fledgling, Hatchling, Weanling)	48 hours	
	Acute IC50 13 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours	
	Acute IC50 5.4 mg/l Marine water	Aquatic plants - Plantae - Exponential growth phase	72 hours	
	Acute LC50 0.072 µg/l Marine water	Crustaceans - Amphipoda - Adult	48 hours	
	Acute LC50 7.56 µg/l Marine water	Fish - Periophthalmus waltoni - Adult	96 hours	
	Chronic NOEC 2.5 µg/l Marine water	Algae - Nitzschia closterium - Exponential growth phase	72 hours	
	Chronic NOEC 7 mg/l Fresh water	Aquatic plants - Ceratophyllum demersum	3 days	
	Chronic NOEC 0.02 mg/l Fresh water	Crustaceans - Cambarus bartonii - Mature	21 days	
	Chronic NOEC 2 µg/l Fresh water	Daphnia - Daphnia magna	21 days	
	Chronic NOEC 0.8 µg/l Fresh water	Fish - Oreochromis niloticus - Juvenile (Fledgling, Hatchling, Weanling)	6 weeks	

Conclusion/Summary

: Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
rosin	1.9 to 7.7	-	high

12.4 Mobility in soil		
Soil/water partition coefficient (Koc)	: Not available.	
Mobility	: Not available.	

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

Techspray ProWick Desoldering Flux coated braid (UK HSE - Great Britain)

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

-				
	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

 14.7 Transport in bulk
 : Not available.

 according to IMO
 instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Techspray ProWick Desoldering Flux coated braid (UK HSE - Great Britain)

SECTION 15: Regulatory information

SECTION 15: Regulat	tory information			
on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.			
Other EU regulations				
Industrial emissions (integrated pollution prevention and control) - Air	: Listed			
Industrial emissions (integrated pollution prevention and control) - Water	: Listed			
Ozone depleting substance	<u>es (1005/2009/EU)</u>			
Not listed.				
Prior Informed Consent (PIC Not listed.	<u>C) (649/2012/EU)</u>			
Persistent Organic Pollutan Not listed.	<u>1ts</u>			
Seveso Directive This product is controlled und Danger criteria	der the Seveso Directive.			
Category				
E1				
International regulations Chemical Weapon Convention Not listed.	on List Schedules I, II & III Chemicals			
Montreal Protocol Not listed.				
Stockholm Convention on Per Not listed.	ersistent Organic Pollutants			
Rotterdam Convention on Pr Not listed.	rior Informed Consent (PIC)			
UNECE Aarhus Protocol on F Not listed.	POPs and Heavy Metals			
Inventory list				
Australia	: All components are listed or exempted.			
Canada	: All components are listed or exempted.			
China	: All components are listed or exempted.			
Europe	: All components are listed or exempted.			
Japan	: Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.			
New Zealand	: All components are listed or exempted.			
Philippines	: All components are listed or exempted.			
Republic of Korea	: All components are listed or exempted.			
Taiwan	: All components are listed or exempted.			

Date of issue/Date of revision

Thailand

: Not determined.

Techspray ProWick Desoldering Flux coated braid (UK HSE - Great Britain)

SECTION 15: Regulatory information

Turkey	: All components are listed or exempted.	
United States	: All components are active or exempted.	
Viet Nam	: All components are listed or exempted.	
15.2 Chemical safety assessment	: This product contains substances for which Chemical Safety Assessments are still required.	

SECTION 16: Other information

Indicates information that has changed from previously issued version.

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Aquatic Acute 1 Aquatic Chronic 2 Skin Sens. 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 SKIN SENSITISATION - Category 1
Date of printing	: 12/17/2021
Date of issue/ Date of revision	: 12/17/2021
Date of previous issue	: 12/17/2021
Version	: 7
N. C. C. C. States	

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.