



WDI9600 | Laser USB Barcode Scanner **Versatile USB 1D Barcode Scanner with Best-In-Class Reading Performance**



Key Features

- Enhanced linear imaging technology for superior scanning and depth of field
- Soft line viewfinder technology to easily target the barcode to be read
- USB type C connectivity
- Disinfectant-ready enclosure resistant to harsh chemical cleaning
- Supports all common 1D barcodes, including GS1 DataBar™ linear codes.

WDI9600 | Laser USB Barcode Scanner

OPTICS & PERFORMANCE

Image Sensor: CCD Solid-State
Light Source/Illumination: Dual LED Array 612 - 630 nm
Read Rate (Maximum): 1,000,000 pixel/sec (400 reads/sec)
Print Contrast Ratio (Minimum): 15%
Reading Angle: Pitch: +/- 65°; Roll (Tilt): +/- 45°;
Skew (Yaw): +/- 65°
Resolution (Maximum): 0.077 mm / 3 mils
Reading Indicators: Beeper (adjustable tone); three green lights (3GL) good read feedback: 'green spot' on the code, dual good read LEDs

DECODING CAPABILITY

1D/Linear Codes: Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.

DEPTH OF FIELD

Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

Code 39: 5 mils: 2.0 to 14.6 in (5.0 to 37 cm)
Code 39: 7.5 mils: 2.0 to 21.3 in (5.0 to 54 cm)
Code 39: 10 mils: 2.0 to 28.9 in (5.0 to 73.5 cm)
Code 39: 20 mils: 1 to 57.9 in (2.5 to 147 cm)
EAN/UPC: 13 mils: 1.4 to 35.4 in (3.5 to 90 cm)

PHYSICAL CHARACTERISTICS

Scanner Dimension: 6.5 x 2.7 x 4.3 in (16.6 x 6.8 x 10.9 cm)
Scanner Weight: 5.75 oz (163.0 g) (scanner only)
Color: Black/yellow
Trigger: Scan button

ELECTRICAL

Input Voltage: 5 VDC +/- 5%
Operating (Typical): <350 mA @ 5V; <150 mA @ 12V
Standby/Idle (Typical): <60 mA @ 5V; <30 mA @ 12V

CONNECTIVITY

Interface: USB type C (USB only)

USER ENVIRONMENT

Operating Temperature: 32 to 122 °F (0 to 50 °C)
Storage/Transport Temperature: -40 to 158 °F (-40 to 70 °C)
Humidity (Non-condensing): 0%~95%
Drop Durability: Withstands repeated drops from 6.0 ft (1.8 m) onto a concrete surface.
Sealing: IP52
Ambient Light: 0 - 130,000 lux

REGULATORY

Agency Approvals: The product meets necessary safety and regulatory approvals for its intended use.
The Quick Reference Guide for this product can be referred to for a complete list of certifications.
Environmental Compliance: Complies to China RoHS; complies to EU RoHS
LED Classification: Exempt group according to IEC 62471

ACCESSORIES

WaspProtect Extended Service Plan WDI9600 48 Hr 2-Yr (SKU 633809009211)
Wasp WDI4700, WDI9600 Scanner Smart Stand (SKU 633809007231)
Battery Pack, Removable, RBP-9001, Black (SKU 633809008771)



Wasp North America

1400 10th Street
Plano, Texas 75074
1-866-547-9277

www.waspbarcode.com

Wasp Europe

Dunstable Road
Redbourn, St Albans AL3 7PR, UK
0845-430-1971

www.waspbarcode.co.uk

Wasp International

+1 214-547-4100