



Product: [10GXS13](#) 

10GXS Category 6A Enhanced Cable, 4 Pair, U/UTP, CMP

Product Description

10GXS Category 6A Enhanced Premise Horizontal Cable (625MHz), 4 Pair, 23 AWG Solid Bare Copper Conductors, U/UTP, Plenum-CMP, Flamarrest® PVC-LS Jacket

Technical Specifications

Product Overview

Suitable Applications:	Premise Horizontal Cable, Ethernet up to 10GBASE-T, Wi-Fi 6, Wi-Fi 5, PoE++, PoE+, PoE, Noisy Environments, Data Center EoR and MoR, Network Backbone, HDBaseT, HDBaseT 4K UHD
Patent:	This product has one or more applicable patents. More information on patents can be found at https://www.belden.com/resources/patents .

Construction Details

Conductor

Size	Stranding	Material	Number of Pairs
23 AWG	Solid	BC - Bare Copper	4

Insulation

Material	Color Code
FEP - Fluorinated Ethylene Propylene	White & Blue, White & Orange, White & Green, White & Brown

Outer Jacket

Separator	Material	Material Trade Name	Nom. Diameter	Ripcord
Center Member (Patented EquiSpline®), EquiBlock™ Barrier Technology	PVC - Polyvinyl Chloride	Flamarrest®	0.265 in (6.73 mm)	Yes

Overall Cable Diameter (Nominal):	0.265 in (6.73 mm)
-----------------------------------	--------------------

Electrical Characteristics

Electricals

Max. Conductor DCR	Max. Capacitance Unbalance
82 Ohm/km	45 pF/100m

Delay

Frequency	Max. Delay	Max. Delay Skew	Nom. Velocity of Prop.	Typical Delay Skew
100 MHz	537.6 ns/100m	45 ns/100m	69%	30 ns/100m

High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. PSNEXT [dB]	Min. PSACR [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance	Min. PSANEXT [dB]	Min. PSAACRF [dB]	Min. TCL [dB]	Min. ELTCTL [dB]
1	2.1 dB/100m	75.3	73.2	74.8	20.0	100 ± 15 Ohm	105 ± 10 Ohm	75.0	77.0	40.0	35.0
4	3.8 dB/100m	66.3	62.5	62.8	23.0	100 ± 15 Ohm	100 ± 15 Ohm	75.0	76.2	40.0	23.0
8	5.3 dB/100m	61.8	56.5	56.7	24.5	100 ± 15 Ohm	100 ± 15 Ohm	75.0	70.1	40.0	16.9
10	5.9 dB/100m	60.3	54.4	54.8	25.0	100 ± 15 Ohm	100 ± 15 Ohm	75.0	68.2	40.0	15.0
16	7.4 dB/100m	57.2	49.8	50.7	25.0	100 ± 15 Ohm	100 ± 15 Ohm	75.0	64.1	38.0	10.9
20	8.3 dB/100m	55.8	47.5	48.8	25.0	100 ± 15 Ohm	100 ± 15 Ohm	75.0	62.2	37.0	9.0
25	9.3 dB/100m	54.3	45.0	46.8	24.3	100 ± 15 Ohm	100 ± 15 Ohm	75.0	60.2	36.0	7.0

31.25	10.4 dB/100m	52.9	42.5	44.9	23.6	100 ± 15 Ohm	100 ± 10 Ohm	75.0	58.3	35.1	5.1
62.5	14.8 dB/100m	48.4	33.6	38.9	21.5	100 ± 15 Ohm	100 ± 10 Ohm	73.6	52.3	32.0	
100	18.9 dB/100m	45.3	26.4	34.8	20.1	100 ± 15 Ohm	100 ± 10 Ohm	70.5	48.2	30.0	
200	27.0 dB/100m	40.8	13.8	28.8	18.0	100 ± 22 Ohm	100 ± 10 Ohm	66.0	42.2	27.0	
250	30.4 dB/100m	39.3	9.0	26.8	17.3	100 ± 32 Ohm	100 ± 10 Ohm	64.5	40.2	26.0	
300	33.5 dB/100m	38.1	4.6	25.3	16.8	100 ± 32 Ohm	100 ± 10 Ohm	63.3	38.7	25.2	
350	36.3 dB/100m	37.1	0.8	23.9	16.3	100 ± 32 Ohm	100 ± 10 Ohm	62.3	37.3	24.6	
400	39.0 dB/100m	36.3		22.8	15.9	100 ± 32 Ohm	100 ± 10 Ohm	61.5	36.2	24.0	
450	41.5 dB/100m	35.5		21.7	15.5	100 ± 32 Ohm	100 ± 10 Ohm	60.7	35.1	23.5	
500	43.9 dB/100m	34.8		20.8	15.2	100 ± 32 Ohm	100 ± 10 Ohm	60.0	34.2	23.0	
550	46.2 dB/100m	33.2		20.0	14.9	100 ± 32 Ohm	100 ± 10 Ohm	59.4	33.4		
600	48.4 dB/100m	32.6		19.2	14.7	100 ± 32 Ohm	100 ± 10 Ohm	58.8	32.6		
625	49.5 dB/100m	32.4		18.9	14.5	100 ± 32 Ohm	100 ± 10 Ohm	58.6	32.3		
750	54.7 dB/100m	32.2		17.3	14.0			57.4	30.7		
860	58.9 dB/100m	31.3		16.1	13.6			56.5	29.5		

Voltage

UL Voltage Rating
300 V (CMP), 300 V (CL3P)

Mechanical Characteristics

Temperature

UL Temperature	Operating	Installation	Storage
105°C	-20°C To +75°C	0°C To +50°C	-20°C To +75°C

Bend Radius

Stationary Min.	Installation Min.
1.25 in (31.8 mm)	2.75 in (69.9 mm)

Max. Pull Tension:	25 lbs (11 kg)
Bulk Cable Weight:	37 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Plenum, Indoor
Sustainability:	Product Lens™, Environmental Product Declaration (EPD) Available
Flammability / Reaction to Fire:	NFPA 262, UL 910 (Plenum), FT6, FT6, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMP;CMP-LP (0.7A);CL3P-LP (0.7A)
CEC / C(UL) Compliance:	CMP
ICEA Compliance:	S-116-732-2013
IEEE Compliance:	IEEE 802.3bt Type 1, Type 2, Type 3, Type 4
NEMA Compliance:	ANSI/NEMA WC-66
Data Category:	Category 6A
TIA/EIA Compliance:	ANSI/TIA-568.2-D Category 6A
ISO/IEC Compliance:	ISO/IEC 11801-1, IEC 61156-5
CENELEC Compliance:	Segregation class according EN50174-2 = a
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	Verified Channel/Category 6A
Non-Plenum Number:	10GXS12

Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Values above 625 MHz are for Engineering Information Only. Print Includes Descending Footage/Meter Markings from Max. Put-Up Length to 0.
--------	--

History

Update and Revision:	Revision Number: 0.235 Revision Date: 12-15-2021
----------------------	--

Variants

Item #	Color	Putup Type	Length	UPC
10GXS13 0101000	Black	Reel	1,000 ft	612825004035
10GXS13010A1000	Black	Reel-in-Box	1,000 ft	612825004134
10GXS13 D151000	Blue	Reel	1,000 ft	612825004042
10GXS13D15A1000	Blue	Reel-in-Box	1,000 ft	612825004059
10GXS13 0081000	Gray	Reel	1,000 ft	612825004011
10GXS13008A1000	Gray	Reel-in-Box	1,000 ft	612825004110
10GXS13 0051000	Green	Reel	1,000 ft	612825003991
10GXS13005A1000	Green	Reel-in-Box	1,000 ft	612825004097
10GXS13 0031000	Orange	Reel	1,000 ft	612825003977
10GXS13003A1000	Orange	Reel-in-Box	1,000 ft	612825004073
10GXS13 0071000	Purple	Reel	1,000 ft	612825004004
10GXS13007A1000	Purple	Reel-in-Box	1,000 ft	612825004103
10GXS13 0021000	Red	Reel	1,000 ft	612825003960
10GXS13002A1000	Red	Reel-in-Box	1,000 ft	612825004066
10GXS13 0091000	White	Reel	1,000 ft	612825004028
10GXS13009A1000	White	Reel-in-Box	1,000 ft	612825004127
10GXS13 0041000	Yellow	Reel	1,000 ft	612825003984
10GXS13004A1000	Yellow	Reel-in-Box	1,000 ft	612825004080

© 2022 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.