



## Overview

This is a USB-C to USB 3.0 with HDMI and Type-C charging port hub. The USB3.0 port allows you to connect a USB device to a host computer or another hub, the USB-C female port can charge for the host computer and supply power for the adapter at the same time, and the HDMI port (DP Altmode) allows you to connect an extra monitor so that you can watch videos or slideshows on a big screen. It can work on Macbook or Google new Chromebook Pixel and other USB-C supported devices.

## Advantages

### Higher Power Conversion Efficiency

High Power Conversion Efficiency means low power consumption and low heating  
98.2% @ Vin=5V; 92.5% @ Vin=20V

### More Advanced Power Management

The power can guarantee uninterrupted working of USB-A SSD and U Disk when the Vin is in 5~20V, so the connected USB device will not get disconnected while plugging in and out the PD adapter from the Type-C charging port.

Supported USB device current is as follows:

800mA by Macbook

400mA by Chromebook

**Note:** When the current of the connected USB device is higher than the above listed current, the USB device will get disconnected while plugging the PD adapter and reconnect in a few seconds

## Features

- Supports USB-C male input and HDMI, USB-A and USB-C female output
- USB-C Female:
  - As USB-C charging port (connecting USB-C Power Adapter)
    - When connecting PD Adapter:
      - It supports PD Charging with power up to 60W (20V/3A)
      - When connecting ordinary USB-C Power Adapter:
        - The max power of this port depends on how much power the connected USB-C power adapter can supply
    - As USB-C downstream port (connecting USB-C device):
      - It supports to transmit data up to 5Gbps and charge for the connected USB-C devices (the total output of the USB-C and USB-A port depends on the host PC, eg: USB-A and USB-C share max 1.5A on Macbook, max 900mA on Chromebook)
  - USB-A:
    - Support to transmit data up to 5Gbps and charge for the connected USB device
    - When USB-C Female is connected to Power Adapter:
      - USB-A port supports BC 1.2 with power up to 7.5W (5V/1.5A) when the USB-C power adapter provides power above 7.5W
    - When USB-C Female is connected to USB-C device:
      - The total output of the USB-C and USB-A port depends on the host PC.
      - Eg: USB-A and USB-C share max 1.5A on Macbook, max 900mA on Chromebook.

# USB3.1 Type C Plug to HDMI + USB3.0 Type A and Type C Receptacle Data and Charging Adapter



- HDMI:  
Support HDMI resolution up to 4Kx2K@30Hz, 10.2Gbps Bandwidth
- Multiple USB-C interfaces support plug and play, hot swap
- Easy to use and carry

## Specifications

Convert From : USB3.1 Type C Plug  
Convert To : HDMI + USB3.0 Type A and Type C Receptacle  
Colour : White

## Part Number Table

| Description   | Part Number |
|---|-------------|
| USB3.1 Type C Plug to HDMI + USB3.0 Type A and Type C Receptacle Data and Charging Adapter, White | 83-22045    |

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro  
Farnell.com/multicomp-pro  
sg.element14.com/b/multicomp-pro

