

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Premier Farnell plc 150 Armley Road, Leeds, LS12 2QQ +44 (0) 8701 202530

Telephone:

+44 1865 407333

SECTION 2 INFORMATION ON INGREDIENTS

Products name: Ni-MH battery

Ingredient	Concentration	CAS No.	EC No.	EU Directive 67/548/ EEC Annex I Index No.	Hazard Label
Nickel; Hydroxide	25~35%	12054-48-7	235-008-5	028-008-00-X	Xn, N
Hydrogen-storage	30~40%	-	-	-	-
Alloys Nickel Foam	4~7%	7440-02-0	231-111-4	028-002-00-7	Xn
Nickel Plated Steel Strips	4~6%	-	-	-	-
Steel Shell	0.3~0.5%	-	-	-	-
Potassium Hydroxide	2~2.5%	1310-58-3	215-181-3	019-002-00-8	С
Sodium Hydroxide	0.1~0.2%	1310-73-2	215-185-5	011-002-00-6	С

SECTION 3 HAZARDS IDENTIFICATION

Hazards Identification : This substance is considered to be non-hazardous for transport.

Emergency Overview:

Caution : Avoid contact and inhalation.

Skin Contact : Exposure to electrolyte contained inside the battery may result in chemical burn.

Exposure to nickel may cause dermatitis in some sensitive individuals.

Eye Contact : Exposure to the electrolyte contained inside the battery may result in severe irritation and

chemical burns.

SECTION 4 FIRST-AID MEASURES

Skin Exposure:

If the internal battery materials of an opened battery cell come into contact with the skin, immediately flush with plenty of water.

Eye Exposure:

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

Inhalation Exposure:

If potential for exposure to nickel fumes or dusts occurs, remove immediately to fresh air and seek medical attention.

Oral Exposure

If swallowed, do not induce vomiting. Seek immediate medical attention.







SECTIONS FIRE FIGHTING MEASURES

Extinguishing Media : Suitable: Water spray, Dry chemical, Sandy soil, Carbon dioxide or appropriate foam.

Firefighting:

Protective Equipment : Wear self-contained breathing apparatus and protective clothing to prevent contact with skin

and eyes.

Specific hazards : Emit toxic fumes under fire conditions.

SECTION6 ACCIDENTAL RELEASWE MEASURES

Procedures of Personal Precautions:

Exercise appropriate precautions to minimize direct contact the internal material with skin and eyes.

Methods for cleaning up:

Sweep up with spade, place into a dry, clean, lidded container for disposal. Avoid raising dust .ventilate area and wash spill site after material pickup is complete.

SECTION 7 HANDLING AND STROAGE

Handling:

Wear appropriate protective clothing and safety gloves. Avoid contact the internal material with eyes, skin. Avoid inhalation-the internal material. Mechanical exhaust required. Keep away from ignition sources, heat and flame, Incompatibilities: strong oxidizing agents, corrosives and foods. Such batteries must be packed in inner packagings in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. No smoking at working site.

Storage:

Store in a cool, well-ventilated area. Keep away from ignition sources, heat and flame. Store in a tightly closed container. Incompatibilities: strong oxidizing agents, corrosives and foods.

SECTION 8 EXPOSURE CONTROL/PPE

Engineering Controls: Use ventilation equipment if available. Safety shower an eye bath.

Personal Protective Equipment:

Clothing: Wear appropriate protective clothing.

Hand: Safety gloves.

Other Protect: No smoking, drinking and eating at working site. Wash thoroughly after handling.

SECTION9 PHYSICAL/CHEMICAL PROPERTIES

Appearance : Pale green cylindrical metal shell (containing electrolytes)

Odor : Odorless Melting Point : >300°C

Solubility : Partial soluble in water





SECTION10 STABILITY AND REACTIVITY

Stability : Stable under normal temperatures and pressures.

Materials to Avoid : Strong oxidizing agents, Corrosives.

Conditions to Avoid : Avoid exposure to heat and open flame. Do not puncture, crush or incinerate, prevent

short circuits. Prevent movement which could lead to short circuits.

Hazardous Polymerization : Will not occur. Hazardous Decomposition Products : Metal oxides.

SECTION11 TOXICOLOGICAL INFORMATION

Toxicity DATA : NO data available.

Irritation Data : The internal battery materials may cause irritation to eyes and skin.

SECTION12 ECOLOGICAL INFORMATION

No data available.

SECTION13 DISPOSAL CONSIDERATIONS

Appropriate Method of Disposal of substance:

Contact a licensed professional waste disposal service to dispose of this material.

SECTION 14- TRANSPORT INFORMATION

In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuit and be contained in strong outer packaging that prevents spillage of contents. All original packaging for nickel metal hydride batteries has been designed to be compliant with these regulatory concerns.

Sealed batteries are considered to be "dry cell' batteries and are not subject to dangerous goods for the purpose of air transportation by the U.S. Department of Transportation (DOT), the International Civil Aviation Organization (ICAO), the International Air Transport Association (IATA), or the International Maritime Dangerous Goods regulations (IMDG). IATA requires that batteries being transported by air must be protected from short-circuiting and protected from movement that could lead to short-circuiting.

According to the 61th edition 2020, it complies to the IATA-DGR-Special Provision A199 dangerous goods regulations, and also the consignment is packed with protection of exposed terminals so as to prevent the potential danger by short-circuiting, according to Special Provision 963 under the IMDG dangerous goods regulations.

NIMH SEA Transportation Regulations:

SP963: Exemption From Dangerous Goods

- 1. Button cell
- 2. Batteries Packed with or Contained in Equipment
- 3. Products Weight Less than 100 kg in the container
- 4. When loaded in cargo transport unit in a total quantity of 100 kg gross mass or more, they are Dangerous Goods (Class 9).
- 5. special provisions.





6.

Regulatory Body	Special Provisions
ADR	295-304,598
IMDG	UN3496 SP117 and SP963
UN	UN 3028 Provision 130
US DOT	49 CFR 172.102 Provision 130
IATA	A199
ICAO	UN 3028 Provisions 295-304

SECTION15 REGULATORY INFORMATION

EU Additional classification:

S36/37

Safety Statement: Wear suitable protective clothing and gloves.

SECTION16 OTHER INFORMATION

None.

Part Number
MP001843
MP001174
MP001175
MP001178
MP001179
MP001180
MP001181
MP001182
MP001183
MP001184
MP001185
MP005527

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

