



KRAMER

VP-200N

1:2 Computer Graphics Video Distribution Amplifier



Compatible with HDTV component video signals when used with a breakout cable such as the Kramer C-6M/3RVF.



The **VP-200N**, VP-300N, & VP-400N are high-performance distribution amplifiers for computer graphics video signals with resolutions ranging from VGA through UXGA and higher. They take one input, provides correct buffering and isolation, and distribute the signal to two, three or four identical outputs.

FEATURES

- High Bandwidth - 400MHz (-3dB).
- HDTV Compatible.
- ID Bit Control.
- Advanced Sync Processing - Ensures compatibility with a wide range of computers.
- Selectable Sync Input Impedance - 75Ω (video), 510Ω (Graphics/TTL).
- 3ft 15-pin HD Cable Included.
- Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUT:	1 analog red, green, blue signals, 0.7Vpp/75Ω, H & V sync, TTL level, on 15-pin HD (F) connectors.
OUTPUT:	2/3/4 analog red, green, blue signals, 0.7Vpp/75Ω H & V sync, TTL level, on 15-pin HD (F) connectors.
MAX. OUTPUT LEVEL:	1.8Vpp.
BANDWIDTH (-3dB):	400MHz.
DIFF. GAIN:	0.03%.
DIFF. PHASE:	0.07Deg.
K-FACTOR:	<0.05%.
S/N RATIO:	72dB.
CONTROLS:	Pair of switches for Hs (Horizontal Sync) and Vs (Vertical Sync) on the underside; ID Bit switch on the underside.
COUPLING:	DC.
POWER CONSUMPTION:	12V DC, 95mA.
DIMENSIONS:	12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98") W, D, H.
WEIGHT:	0.3kg (0.67lbs) approx.
INCLUDED ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.

