

**230V~**

50/60Hz  
3p=6h  
4p+5p=9h

**400V~**

50/60Hz  
3p=9h  
4p+5p=6h

Ampere

Poles

Cat.No.

Cat.No.

## Event technology

16	3	013-6x		<b>Shark Plug</b> • with screw terminals • to order screwless connection technology please add "TT" e.g. 013-6TTx IP44		<b>Solid rubber plug</b> • with screwless cable gland • dual-point earthing system • insert: rubber IP44	
16	4		014-6x				
16	5		015-6x				
32	3	023-6x		<b>Power Twist Plug</b> • Contact frame with screws IP66/67		<b>Solid rubber connector</b> • with screwless cable gland • national • with hinged lid • insert: rubber IP44	
32	4		024-6x				
32	5		025-6x				
63	3	033-6xs		<b>Flanged plug straight</b> • with screw terminals • to order screwless connection technology please add "TT" e.g. 613-6TTx IP44		<b>3-way connector - solid rubber</b> • with screwless cable gland • national • with hinged lid • insert: rubber IP44	
63	4		034-6xs				
63	5		035-6xs				
125	3	043-6xs		<b>Shark Connector</b> • with screw terminals • to order screwless connection technology please add "TT" e.g. 213-6TTx IP44		<b>T-Connect</b> • Equipment: 1 CEE-plug 16A 3p 6h 1 CEE-socket 16A 3p 6h 1 cable entry IP44 (IP67 available) other versions on request	
125	4		044-6xs				
125	5		045-6xs				
16	3	613-6x		<b>Power Twist Connector</b> • Contact frame with screws IP66/67		<b>Wall distribution boxes</b> • many designs available on request • solid rubber IP54	
16	4		614-6x				
16	5		615-6x				
32	3	623-6x		<b>Shark Connector</b> • with screw terminals • to order screwless connection technology please add "TT" e.g. 223-6TTx IP44		<b>Mobile distribution boxes</b> • many designs available on request • solid rubber IP44	
32	4		624-6x				
32	5		625-6x				
63	3	233-6xs		<b>Power Twist Connector</b> • Contact frame with screws IP66/67		<b>Series M-SVE</b> • shock-resistant, robust and mobile insulated thermo-plastic box • many designs available on request IP44	
63	4		234-6xs				
63	5		235-6xs				
125	3	243-6xs		<b>Flanged socket straight</b> • with screw terminals • to order screwless connection technology please add "TT" e.g. 313-6TTx IP44		<b>Socket outlet (DIN 49440)</b> • flange 50x50mm • fixing center 38x38mm • screwed contact • available also with Belg./French and British system IP54	
125	4		244-6xs				
125	5		245-6xs				
16	3	313-6x		<b>Flanged socket straight</b> • with screw terminals • to order screwless connection technology please add "TT" e.g. 313-6TTx IP44		<b>Hinged windows</b> • available in different dimensions IP67, IP54	
16	4		314-6x				
16	5		315-6x				
32	3	323-6x		<b>Flanged socket straight</b> • with screw terminals • to order screwless connection technology please add "TT" e.g. 313-6TTx IP44		<b>Socket outlet (DIN 49440)</b> • flange 50x50mm • fixing center 38x38mm • screwed contact • available also with Belg./French and British system IP54	
32	4		324-6x				
32	5		325-6x				

**250V~**

50/60Hz

16	3	1050-0ss		<b>Socket outlet (DIN 49440)</b> • flange 50x50mm • fixing center 38x38mm • screwed contact • available also with Belg./French and British system IP54		<b>Hinged windows</b> • available in different dimensions IP67, IP54	
16	3	1050-0ssw	with sealing bulge				