
USB Cable 2.0 Male Type A to B



1. Cable Spec: 30AWG (7/0.10Cu)×1P+26AWG(7/0.15Cu)×2C+AD(1/0.254Cu)B(48/0.12ALMG) Jacket Material : PVC OD: 4.5±0.2mm Colour : Black

Cable Printing : USB 2.0 Cable fully rated 80°C 30V

2. Connector A : USB A Male Solder Type

Insulation : White Contact : Gold Plated

Shell : Fe (SPCC) Nickel Plated

- 3. Connector B : USB B Male Solder Type
 - Insulation : White

Contact : Gold Plated

- Shell : Fe (SPCC) Nickel Plated
- 4. Over Mold : PVC-Black
- 5. Parameter Settings : CT-8681FA
 - 1. Conductive Resistance : 5Ω
 - 2. Insulative Resistance : 5MΩ (Min.)
 - 3. Hi-Pot : DC 300V/10ms, 1.5mmA/I, 50Hz, 0.03s

Part Number Table

Description	Part Number
USB Cable, 2.0 Male Type A to B, Black, 1m	MP009288

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

