Toroidal Transformer

multicomp PRO



Description

The general purpose toroidal transformers with flying leads. They feature dual primary and dual secondary windings.

Features

- Power rating ranges from 15VA to 1000VA
- Secondary voltages ranges from 2 × 6V AC to 2 × 55V AC
- · Dual primary winding for connection in series or parallel only
- · Secondary windings can be connected in series or parallel or used independently
- · Double insulated primary lead-out
- · Flexible lead-out can be trimmed to any length without the need for removal of enamel
- 100% electrical and flash tested

Circuit Diagram



Nominal Dimensions/Weight (Mounting Excluded)

| Diameter | : 140mm |
|----------|---------|
| Height | : 70mm |
| Weight | : 4.9kg |

Part Number Table

| Description | Part Number |
|--|-------------|
| Toroidal Transformer, 625VA, 2 x 40V, Dual Primary | MCTA625/40 |

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage resulting from any reliance on the Information or use of it (including liability resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

