



Product Change Notification / SYST-21OKIQ186

Date:

23-Mar-2022

Product Category:

8-bit Microcontrollers

PCN Type:

Document Change

Notification Subject:

ERRATA - ATmega164A/PA/324A/PA/644A/PA/1284/P Silicon Errata and Data Sheet Clarification Revision

Affected CPNs:

[SYST-21OKIQ186_Affected_CPN_03232022.pdf](#)
[SYST-21OKIQ186_Affected_CPN_03232022.csv](#)

Notification Text:

SYST-21OKIQ186

Microchip has released a new Product Documents for the ATmega164A/PA/324A/PA/644A/PA/1284/P Silicon Errata and Data Sheet Clarification of devices. If you are using one of these devices please read the document located at [ATmega164A/PA/324A/PA/644A/PA/1284/P Silicon Errata and Data Sheet Clarification](#)

Notification Status: Final

Description of Change: Data Sheet Clarifications added:

- 3.1. Electrical Characteristics – TA = -40°C to 85°C
- 3.2. Electrical Characteristics – TA = -40°C to 105°C

Impacts to Data Sheet: None

Reason for Change: To Improve Productivity

Change Implementation Status: Complete

Date Document Changes Effective: 23 March 2022

NOTE: Please be advised that this is a change to the document only the product has not been changed.

Markings to Distinguish Revised from Unrevised Devices: N/A

Attachments:

[ATmega164A/ PA/ 324A/ PA/ 644A/ PA/ 1284/ P Silicon Errata and Data Sheet Clarification](#)

Please contact your local [Microchip sales office](#) with questions or concerns regarding this notification.

Terms and Conditions:

If you wish to receive Microchip PCNs via email please register for our PCN email service at our [PCN home page](#) select register then fill in the required fields. You will find instructions about registering for Microchips PCN email service in the [PCN FAQ](#) section.

If you wish to change your PCN profile, including opt out, please go to the [PCN home page](#) select login and sign into your myMicrochip account. Select a profile option from the left navigation bar and make the applicable selections.

Affected Catalog Part Numbers (CPN)

ATMEGA1284P-PU
ATMEGA1284-PU
ATMEGA1284P-MU
ATMEGA1284-MU
ATMEGA1284P-AU
ATMEGA1284-AU
ATMEGA1284P-MUR
ATMEGA1284-MUR
ATMEGA1284P-AUR
ATMEGA1284-AUR
ATMEGA324PA-CU
ATMEGA324A-CU
ATMEGA324A-PU
ATMEGA324PA-PU
ATMEGA324A-MCH
ATMEGA324PA-MCH
ATMEGA324PA-MU
ATMEGA324A-MU
ATMEGA324PA-AU
ATMEGA324A-AU
ATMEGA324PA-AUA1
ATMEGA324PA-PN
ATMEGA324PA-MN
ATMEGA324PA-AN
ATMEGA324PA-MNR
ATMEGA324PA-ANR
ATMEGA324PA-MCHR
ATMEGA324PA-MUR
ATMEGA324A-MUR
ATMEGA324PA-AUR
ATMEGA324A-AURA3
ATMEGA324A-AUR
ATMEGA164A-CU
ATMEGA164PA-CU
ATMEGA164A-PU
ATMEGA164PA-PU
ATMEGA164A-MCH
ATMEGA164PA-MCH
ATMEGA164A-MU
ATMEGA164PA-MU
ATMEGA164PA-AU
ATMEGA164A-AU
ATMEGA164A-AUA2
ATMEGA164PA-MN
ATMEGA164PA-AN
ATMEGA164PA-MNR

ATMEGA164PA-ANR
ATMEGA164A-CUR
ATMEGA164PA-CUR
ATMEGA164A-MCHR
ATMEGA164PA-MCHR
ATMEGA164A-MUR
ATMEGA164PA-MUR
ATMEGA164PA-AUR
ATMEGA164A-AUR
ATMEGA164A-AURA2
ATMEGA644A-PU
ATMEGA644PA-PU
ATMEGA644PA-MU
ATMEGA644A-MU
ATMEGA644A-AU
ATMEGA644PA-AU
ATMEGA644PA-MN
ATMEGA644PA-AN
ATMEGA644PA-MNR
ATMEGA644PA-ANR
ATMEGA644PA-MUR
ATMEGA644A-MUR
ATMEGA644A-AUR
ATMEGA644PA-AUR



ATmega164A/PA/324A/PA/ 644A/PA/1284/P

Silicon Errata and Data Sheet Clarifications

Introduction

The ATmega164A/PA/324A/PA/644A/PA/1284/P devices you have received conform functionally to the current device data sheet (www.microchip.com/DS40002070), except for the anomalies described in this document. The errata described in this document will likely be addressed in future revisions of the ATmega164A/PA/324A/PA/644A/PA/1284/P devices.

Note:

- This document summarizes all the silicon errata issues from all revisions of silicon, previous and current.

1. Silicon Issue Summary

- Erratum is not applicable.
- X** Erratum is applicable.

Peripheral	Short Description	Valid for Silicon Revision				
		ATmega164A/PA	ATmega324A/PA		ATmega644A/PA	ATmega1284/P
		Rev. E ₁	Rev. F ₁	Rev. G	Rev. F ₁	Rev. B ₁
Device	No known errata					

Note:

1. This revision is the initial release of the silicon.

2. Silicon Errata Issues

2.1 None

There are no known errata as of this publication date.

3. Data Sheet Clarifications

The following typographic corrections and clarifications are to be noted for the latest version of the device data sheet (www.microchip.com/DS40002070).

Note: Corrections are shown in **bold**. Where possible, the original bold text formatting has been removed for clarity.

3.1 Electrical Characteristics – $T_A = -40^{\circ}\text{C}$ to 85°C

A clarification for the power-down specification limit has been made. This clarification has corrections that are impractical to mark in bold. All the following tables in this section contain the most current information and notes.

Table 28-2. ATmega164A DC Characteristics. $T_A = -40^{\circ}\text{C}$ to 85°C , $V_{CC} = 1.8\text{V}$ to 5.5V (unless otherwise noted)

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
I_{CC}	Power supply current ⁽¹⁾	Active 1 MHz, $V_{CC} = 2\text{V}$		0.3	0.55	mA
		Active 4 MHz, $V_{CC} = 3\text{V}$		1.4	3.5	
		Active 8 MHz, $V_{CC} = 5\text{V}$		4.8	12	
		Idle 1 MHz, $V_{CC} = 2\text{V}$		0.07	0.5	
		Idle 4 MHz, $V_{CC} = 3\text{V}$		0.25	1.5	
		Idle 8 MHz, $V_{CC} = 5\text{V}$		1.0	5.5	
	Power-save mode ⁽²⁾	32.768 kHz T_{OSC} enabled, $V_{CC} = 1.8\text{V}$		0.5		μA
		32.768 kHz T_{OSC} enabled, $V_{CC} = 3\text{V}$		0.6		
	Power-down mode ⁽²⁾	WDT enabled, $V_{CC} = 3\text{V}$		5.0	15	
		WDT disabled, $V_{CC} = 3\text{V}$		0.17	3.0	

Notes:

1. All bits set in the 'PRR0 – Power Reduction Register 0' on page 56 in the data sheet.
2. **Maximum and Typical values for 25°C . Maximum values are test limits in production.**

ATmega164A/PA/324A/PA/644A/PA/1284/...

Data Sheet Clarifications

Table 28-3. ATmega164PA DC Characteristics. $T_A = -40^{\circ}\text{C}$ to 85°C , $V_{CC} = 1.8\text{V}$ to 5.5V (unless otherwise noted)

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units	
I_{CC}	Power supply current ⁽¹⁾	Active 1 MHz, $V_{CC} = 2\text{V}$		0.3	0.5	mA	
		Active 4 MHz, $V_{CC} = 3\text{V}$		1.4	2.7		
		Active 8 MHz, $V_{CC} = 5\text{V}$		4.8	9.0		
		Idle 1 MHz, $V_{CC} = 2\text{V}$		0.07	0.15		
		Idle 4 MHz, $V_{CC} = 3\text{V}$		0.25	0.7		
		Idle 8 MHz, $V_{CC} = 5\text{V}$		1.0	5.0		
	Power-save mode ⁽²⁾	32.768 kHz T_{OSC} enabled, $V_{CC} = 1.8\text{V}$			0.5		μA
		32.768 kHz T_{OSC} enabled, $V_{CC} = 3\text{V}$			0.6		
	Power-down mode ⁽²⁾	WDT enabled, $V_{CC} = 3\text{V}$			5.0	8.0	
		WDT disabled, $V_{CC} = 3\text{V}$			0.17	2.0	

Notes:

1. All bits set in the 'PRR0 – Power Reduction Register 0' on page 56 in the data sheet.
2. **Maximum and Typical values for 25°C . Maximum values are test limits in production.**

ATmega164A/PA/324A/PA/644A/PA/1284/...

Data Sheet Clarifications

Table 28-4. ATmega324A DC characteristics. $T_A = -40^{\circ}\text{C}$ to 85°C , $V_{CC} = 1.8\text{V}$ to 5.5V (unless otherwise noted)

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
I_{CC}	Power supply current ⁽¹⁾	Active 1 MHz, $V_{CC} = 2\text{V}$		0.3	0.55	mA
		Active 4 MHz, $V_{CC} = 3\text{V}$		1.5	3.5	
		Active 8 MHz, $V_{CC} = 5\text{V}$		5.2	12	
		Idle 1 MHz, $V_{CC} = 2\text{V}$		0.06	0.5	
		Idle 4 MHz, $V_{CC} = 3\text{V}$		0.35	1.5	
		Idle 8 MHz, $V_{CC} = 5\text{V}$		1.3	5.5	
	Power-save mode ⁽²⁾	32.768 kHz T_{OSC} enabled, $V_{CC} = 1.8\text{V}$		0.5		μA
		32.768 kHz T_{OSC} enabled, $V_{CC} = 3\text{V}$		0.6		
	Power-down mode ⁽²⁾	WDT enabled, $V_{CC} = 3\text{V}$		4.2	15	
		WDT disabled, $V_{CC} = 3\text{V}$		0.15	3.0	

Notes:

1. All bits set in the 'PRR0 – Power Reduction Register 0' on page 56 in the data sheet.
2. **Maximum and Typical values for 25°C. Maximum values are test limits in production.**

ATmega164A/PA/324A/PA/644A/PA/1284/...

Data Sheet Clarifications

Table 28-5. ATmega324PA DC Characteristics. $T_A = -40^{\circ}\text{C}$ to 85°C , $V_{CC} = 1.8\text{V}$ to 5.5V (unless otherwise noted)

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
I_{CC}	Power supply current ⁽¹⁾	Active 1 MHz, $V_{CC} = 2\text{V}$		0.3	0.5	mA
		Active 4 MHz, $V_{CC} = 3\text{V}$		1.5	2.7	
		Active 8 MHz, $V_{CC} = 5\text{V}$		5.2	9	
		Idle 1 MHz, $V_{CC} = 2\text{V}$		0.06	0.15	
		Idle 4 MHz, $V_{CC} = 3\text{V}$		0.35	0.7	
		Idle 8 MHz, $V_{CC} = 5\text{V}$		1.3	5.0	
	Power-save mode ⁽²⁾	32.768 kHz T_{OSC} enabled, $V_{CC} = 1.8\text{V}$		0.5		μA
		32.768 kHz T_{OSC} enabled, $V_{CC} = 3\text{V}$		0.6		
	Power-down mode ⁽²⁾	WDT enabled, $V_{CC} = 3\text{V}$		4.2	8.0	μA
		WDT disabled, $V_{CC} = 3\text{V}$		0.15	2.0	

Notes:

1. All bits set in the 'PRR0 – Power Reduction Register 0' on page 56 in the data sheet.
2. **Maximum and Typical values for 25°C . Maximum values are test limits in production.**

ATmega164A/PA/324A/PA/644A/PA/1284/...

Data Sheet Clarifications

Table 28-6. ATmega644A DC Characteristics. $T_A = -40^{\circ}\text{C}$ to 85°C , $V_{CC} = 1.8\text{V}$ to 5.5V (unless otherwise noted)

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units	
I_{CC}	Power supply current ⁽¹⁾	Active 1 MHz, $V_{CC} = 2\text{V}$		0.38	0.5	mA	
		Active 4 MHz, $V_{CC} = 3\text{V}$		1.8	2.7		
		Active 8 MHz, $V_{CC} = 5\text{V}$		5.6	9.0		
		Idle 1 MHz, $V_{CC} = 2\text{V}$		0.06	0.15		
		Idle 4 MHz, $V_{CC} = 3\text{V}$		0.2	0.7		
		Idle 8 MHz, $V_{CC} = 5\text{V}$		1.1	2.5		
	Power-save mode ⁽²⁾	32.768 kHz T_{OSC} enabled, $V_{CC} = 1.8\text{V}$			0.5		μA
		32.768 kHz T_{OSC} enabled, $V_{CC} = 3\text{V}$			0.6		
	Power-down mode ⁽²⁾	WDT enabled, $V_{CC} = 3\text{V}$			4.2	20	
		WDT disabled, $V_{CC} = 3\text{V}$			0.15	3.0	

Notes:

1. All bits set in the 'PRR0 – Power Reduction Register 0' on page 56 in the data sheet.
2. **Maximum and Typical values for 25°C. Maximum values are test limits in production.**

ATmega164A/PA/324A/PA/644A/PA/1284/...

Data Sheet Clarifications

Table 28-7. ATmega644PA DC characteristics. $T_A = -40^{\circ}\text{C}$ to 85°C , $V_{CC} = 1.8\text{V}$ to 5.5V (unless otherwise noted)

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units	
I_{CC}	Power supply current ⁽¹⁾	Active 1 MHz, $V_{CC} = 2\text{V}$		0.38	0.5	mA	
		Active 4 MHz, $V_{CC} = 3\text{V}$		1.8	2.7		
		Active 8 MHz, $V_{CC} = 5\text{V}$		5.6	9.0		
		Idle 1 MHz, $V_{CC} = 2\text{V}$		0.06	0.15		
		Idle 4 MHz, $V_{CC} = 3\text{V}$		0.2	0.7		
		Idle 8 MHz, $V_{CC} = 5\text{V}$		1.1	4.0		
	Power-save mode ⁽²⁾	32.768 kHz T_{OSC} enabled, $V_{CC} = 1.8\text{V}$			0.5		μA
		32.768 kHz T_{OSC} enabled, $V_{CC} = 3\text{V}$			0.6		
	Power-down mode ⁽²⁾	WDT enabled, $V_{CC} = 3\text{V}$			4.2	8.0	
		WDT disabled, $V_{CC} = 3\text{V}$			0.15	2.0	

Notes:

1. All bits set in the 'PRR0 – Power Reduction Register 0' on page 56 in the data sheet.
2. **Maximum and Typical values for 25°C. Maximum values are test limits in production.**

ATmega164A/PA/324A/PA/644A/PA/1284/...

Data Sheet Clarifications

Table 28-8. ATmega1284 DC characteristics. $T_A = -40^{\circ}\text{C}$ to 85°C , $V_{CC} = 1.8\text{V}$ to 5.5V (unless otherwise noted)

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units	
I_{CC}	Power supply current ⁽¹⁾	Active 1 MHz, $V_{CC} = 2\text{V}$		0.38	0.55	mA	
		Active 4 MHz, $V_{CC} = 3\text{V}$		1.8	3.5		
		Active 8 MHz, $V_{CC} = 5\text{V}$		5.6	12		
		Idle 1 MHz, $V_{CC} = 2\text{V}$		0.06	0.5		
		Idle 4 MHz, $V_{CC} = 3\text{V}$		0.2	1.5		
		Idle 8 MHz, $V_{CC} = 5\text{V}$		1.1	5.5		
	Power-save mode ⁽²⁾	32.768 kHz T_{OSC} enabled, $V_{CC} = 1.8\text{V}$			0.5		μA
		32.768 kHz T_{OSC} enabled, $V_{CC} = 3\text{V}$			0.6		
	Power-down mode ⁽²⁾	WDT enabled, $V_{CC} = 3\text{V}$			4.2	15	
		WDT disabled, $V_{CC} = 3\text{V}$			0.15	5.0	

Notes:

1. All bits set in the 'PRR0 – Power Reduction Register 0' on page 56 in the data sheet.
2. **Maximum and Typical values for 25°C . Maximum values are test limits in production.**

Table 28-9. ATmega1284P DC characteristics. $T_A = -40^{\circ}\text{C}$ to 85°C , $V_{CC} = 1.8\text{V}$ to 5.5V (unless otherwise noted)

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units	
I_{CC}	Power supply current ⁽¹⁾	Active 1 MHz, $V_{CC} = 2\text{V}$		0.38	0.5	mA	
		Active 4 MHz, $V_{CC} = 3\text{V}$		1.8	2.9		
		Active 8 MHz, $V_{CC} = 5\text{V}$		5.6	9.0		
		Idle 1 MHz, $V_{CC} = 2\text{V}$		0.06	0.15		
		Idle 4 MHz, $V_{CC} = 3\text{V}$		0.2	0.7		
		Idle 8 MHz, $V_{CC} = 5\text{V}$		1.1	5.0		
	Power-save mode ⁽²⁾	32.768 kHz T_{OSC} enabled, $V_{CC} = 1.8\text{V}$			0.5		μA
		32.768 kHz T_{OSC} enabled, $V_{CC} = 3\text{V}$			0.6		
Power-down mode ⁽²⁾	WDT enabled, $V_{CC} = 3\text{V}$			4.2	10	μA	
	WDT disabled, $V_{CC} = 3\text{V}$			0.15	5		

Notes:

1. All bits set in the 'PRR0 – Power Reduction Register 0' on page 56 in the data sheet.
2. **Maximum and Typical values for 25°C . Maximum values are test limits in production.**

3.2 Electrical Characteristics – $T_A = -40^{\circ}\text{C}$ to 105°C

A clarification for the power-down specification limit has been made. This clarification has corrections that are impractical to mark in bold. All the following tables in this section contain the most current information and notes.

Table 29-1. ATmega164PA DC Characteristics. $T_A = -40^{\circ}\text{C}$ to 105°C , $V_{CC} = 1.8\text{V}$ to 5.5V (unless otherwise noted)

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units	
I_{CC}	Power supply current ⁽¹⁾	Active 1 MHz, $V_{CC} = 2\text{V}$			0.7	mA	
		Active 4 MHz, $V_{CC} = 3\text{V}$			3		
		Active 8 MHz, $V_{CC} = 5\text{V}$			11		
		Idle 1 MHz, $V_{CC} = 2\text{V}$			0.17		
		Idle 4 MHz, $V_{CC} = 3\text{V}$			0.85		
		Idle 8 MHz, $V_{CC} = 5\text{V}$			6		
	Power-down mode ⁽²⁾	WDT enabled, $V_{CC} = 3\text{V}$				15	μA
		WDT disabled, $V_{CC} = 3\text{V}$				5	

Notes:

1. All bits set in the 'PRR0 – Power Reduction Register 0' on page 56 in the data sheet.
2. **Maximum and Typical values for 25°C . Maximum values are test limits in production.**

Table 29-2. ATmega324PA DC Characteristics. $T_A = -40^{\circ}\text{C}$ to 105°C , $V_{CC} = 1.8\text{V}$ to 5.5V (unless otherwise noted)

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
I_{CC}	Power supply current ⁽¹⁾	Active 1 MHz, $V_{CC} = 2\text{V}$			0.7	mA
		Active 4 MHz, $V_{CC} = 3\text{V}$			3	
		Active 8 MHz, $V_{CC} = 5\text{V}$			11	
		Idle 1 MHz, $V_{CC} = 2\text{V}$			0.17	
		Idle 4 MHz, $V_{CC} = 3\text{V}$			0.85	
		Idle 8 MHz, $V_{CC} = 5\text{V}$			6	
	Power-down mode ⁽²⁾	WDT enabled, $V_{CC} = 3\text{V}$			15	μA
		WDT disabled, $V_{CC} = 3\text{V}$			5	

Notes:

1. All bits set in the 'PRR0 – Power Reduction Register 0' on page 56 in the data sheet.
2. **Maximum and Typical values for 25°C. Maximum values are test limits in production.**

Table 29-3. ATmega644PA DC Characteristics. $T_A = -40^{\circ}\text{C}$ to 105°C , $V_{CC} = 1.8\text{V}$ to 5.5V (unless otherwise noted)

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
I_{CC}	Power supply current ⁽¹⁾	Active 1 MHz, $V_{CC} = 2\text{V}$			0.7	mA
		Active 4 MHz, $V_{CC} = 3\text{V}$			3	
		Active 8 MHz, $V_{CC} = 5\text{V}$			11	
		Idle 1 MHz, $V_{CC} = 2\text{V}$			0.17	
		Idle 4 MHz, $V_{CC} = 3\text{V}$			0.85	
		Idle 8 MHz, $V_{CC} = 5\text{V}$			6	
	Power-down mode ⁽²⁾	WDT enabled, $V_{CC} = 3\text{V}$			15	μA
		WDT disabled, $V_{CC} = 3\text{V}$			5	

Notes:

1. All bits set in the 'PRR0 – Power Reduction Register 0' on page 56 in the data sheet.
2. **The current consumption values include input leakage current.**

Table 29-4. ATmega1284P DC Characteristics. $T_A = -40^{\circ}\text{C}$ to 105°C , $V_{CC} = 1.8\text{V}$ to 5.5V (unless otherwise noted)

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
I_{CC}	Power supply current ⁽¹⁾	Active 1 MHz, $V_{CC} = 2\text{V}$			0.8	mA
		Active 4 MHz, $V_{CC} = 3\text{V}$			3	
		Active 8 MHz, $V_{CC} = 5\text{V}$			11	
		Idle 1 MHz, $V_{CC} = 2\text{V}$			0.17	
		Idle 4 MHz, $V_{CC} = 3\text{V}$			0.85	
		Idle 8 MHz, $V_{CC} = 5\text{V}$			6	
	Power-down mode ⁽²⁾	WDT enabled, $V_{CC} = 3\text{V}$			18	μA
		WDT disabled, $V_{CC} = 3\text{V}$			13	

Notes:

1. All bits set in the 'PRR0 – Power Reduction Register 0' on page 56 in the data sheet.
2. **Maximum and Typical values for 25°C. Maximum values are test limits in production.**

4. Document Revision History

Note: The document revision is independent of the silicon revision.

4.1 Revision History

Doc Rev.	Date	Comments
B	03/2022	Data Sheet Clarifications added: <ul style="list-style-type: none">• 3.1. Electrical Characteristics – TA = -40°C to 85°C• 3.2. Electrical Characteristics – TA = -40°C to 105°C
A	01/2020	Initial document release. <ul style="list-style-type: none">• Content moved from the data sheet and restructured to the new document template• Updated the die revision list to reflect die revisions in production

The Microchip Website

Microchip provides online support via our website at www.microchip.com/. This website is used to make files and information easily available to customers. Some of the content available includes:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQs), technical support requests, online discussion groups, Microchip design partner program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

Product Change Notification Service

Microchip's product change notification service helps keep customers current on Microchip products. Subscribers will receive email notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, go to www.microchip.com/pcn and follow the registration instructions.

Customer Support

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Embedded Solutions Engineer (ESE)
- Technical Support

Customers should contact their distributor, representative or ESE for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in this document.

Technical support is available through the website at: www.microchip.com/support

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is "unbreakable". Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.

Legal Notice

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AnyRate, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Klear, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, IntelliMOS, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet- Wire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, TrueTime, WinPath, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, GridTime, IdealBridge, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, NVM Express, NVMe, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQL, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, TSHARC, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, Symmcom, and Trusted Time are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2022, Microchip Technology Incorporated and its subsidiaries. All Rights Reserved.

ISBN: 978-1-5224-9696-0

Quality Management System

For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.

Worldwide Sales and Service

AMERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
<p>Corporate Office 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7200 Tel: 480-792-7277 Technical Support: www.microchip.com/support Web Address: www.microchip.com</p> <p>Atlanta Duluth, GA Tel: 678-957-9614 Fax: 678-957-1455</p> <p>Austin, TX Tel: 512-257-3370</p> <p>Boston Westborough, MA Tel: 774-760-0087 Fax: 774-760-0088</p> <p>Chicago Itasca, IL Tel: 630-285-0071 Fax: 630-285-0075</p> <p>Dallas Addison, TX Tel: 972-818-7423 Fax: 972-818-2924</p> <p>Detroit Novi, MI Tel: 248-848-4000</p> <p>Houston, TX Tel: 281-894-5983</p> <p>Indianapolis Noblesville, IN Tel: 317-773-8323 Fax: 317-773-5453 Tel: 317-536-2380</p> <p>Los Angeles Mission Viejo, CA Tel: 949-462-9523 Fax: 949-462-9608 Tel: 951-273-7800</p> <p>Raleigh, NC Tel: 919-844-7510</p> <p>New York, NY Tel: 631-435-6000</p> <p>San Jose, CA Tel: 408-735-9110 Tel: 408-436-4270</p> <p>Canada - Toronto Tel: 905-695-1980 Fax: 905-695-2078</p>	<p>Australia - Sydney Tel: 61-2-9868-6733</p> <p>China - Beijing Tel: 86-10-8569-7000</p> <p>China - Chengdu Tel: 86-28-8665-5511</p> <p>China - Chongqing Tel: 86-23-8980-9588</p> <p>China - Dongguan Tel: 86-769-8702-9880</p> <p>China - Guangzhou Tel: 86-20-8755-8029</p> <p>China - Hangzhou Tel: 86-571-8792-8115</p> <p>China - Hong Kong SAR Tel: 852-2943-5100</p> <p>China - Nanjing Tel: 86-25-8473-2460</p> <p>China - Qingdao Tel: 86-532-8502-7355</p> <p>China - Shanghai Tel: 86-21-3326-8000</p> <p>China - Shenyang Tel: 86-24-2334-2829</p> <p>China - Shenzhen Tel: 86-755-8864-2200</p> <p>China - Suzhou Tel: 86-186-6233-1526</p> <p>China - Wuhan Tel: 86-27-5980-5300</p> <p>China - Xian Tel: 86-29-8833-7252</p> <p>China - Xiamen Tel: 86-592-2388138</p> <p>China - Zhuhai Tel: 86-756-3210040</p>	<p>India - Bangalore Tel: 91-80-3090-4444</p> <p>India - New Delhi Tel: 91-11-4160-8631</p> <p>India - Pune Tel: 91-20-4121-0141</p> <p>Japan - Osaka Tel: 81-6-6152-7160</p> <p>Japan - Tokyo Tel: 81-3-6880-3770</p> <p>Korea - Daegu Tel: 82-53-744-4301</p> <p>Korea - Seoul Tel: 82-2-554-7200</p> <p>Malaysia - Kuala Lumpur Tel: 60-3-7651-7906</p> <p>Malaysia - Penang Tel: 60-4-227-8870</p> <p>Philippines - Manila Tel: 63-2-634-9065</p> <p>Singapore Tel: 65-6334-8870</p> <p>Taiwan - Hsin Chu Tel: 886-3-577-8366</p> <p>Taiwan - Kaohsiung Tel: 886-7-213-7830</p> <p>Taiwan - Taipei Tel: 886-2-2508-8600</p> <p>Thailand - Bangkok Tel: 66-2-694-1351</p> <p>Vietnam - Ho Chi Minh Tel: 84-28-5448-2100</p>	<p>Austria - Wels Tel: 43-7242-2244-39 Fax: 43-7242-2244-393</p> <p>Denmark - Copenhagen Tel: 45-4485-5910 Fax: 45-4485-2829</p> <p>Finland - Espoo Tel: 358-9-4520-820</p> <p>France - Paris Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79</p> <p>Germany - Garching Tel: 49-8931-9700</p> <p>Germany - Haan Tel: 49-2129-3766400</p> <p>Germany - Heilbronn Tel: 49-7131-72400</p> <p>Germany - Karlsruhe Tel: 49-721-625370</p> <p>Germany - Munich Tel: 49-89-627-144-0 Fax: 49-89-627-144-44</p> <p>Germany - Rosenheim Tel: 49-8031-354-560</p> <p>Israel - Ra'anana Tel: 972-9-744-7705</p> <p>Italy - Milan Tel: 39-0331-742611 Fax: 39-0331-466781</p> <p>Italy - Padova Tel: 39-049-7625286</p> <p>Netherlands - Druen Tel: 31-416-690399 Fax: 31-416-690340</p> <p>Norway - Trondheim Tel: 47-72884388</p> <p>Poland - Warsaw Tel: 48-22-3325737</p> <p>Romania - Bucharest Tel: 40-21-407-87-50</p> <p>Spain - Madrid Tel: 34-91-708-08-90 Fax: 34-91-708-08-91</p> <p>Sweden - Gothenberg Tel: 46-31-704-60-40</p> <p>Sweden - Stockholm Tel: 46-8-5090-4654</p> <p>UK - Wokingham Tel: 44-118-921-5800 Fax: 44-118-921-5820</p>