



## **Bubblemat**

Smart anti-fatigue mat with a distinctive bubbled surface







- Raised bubble patterned surface stimulates feet and legs to aid circulation.
- Underfoot cushioning also makes prolonged occupational standing more comfortable.
- A choice of materials depending on the demands of the environment (dry use only).
- Complete mats suitable for workstations and interlocking sections available for longer production lines.



## **Parts**

Part Number	Size	Colour	Weight (kg)	
BF010001	0.6 m x 0.9 m	Black	6.35	
BF010002	0.9 m x 1.2 m	Black	10.5	
BF010003	0.6 m x 0.9 m	Black	6.35	
BF010004	0.6 m x 0.9 m	Black	6.35	
				_

## **Technical Specifications**

Material	Natural rubber
Surface Finish	Bubble
Product Height	14 mm
Product Weight	10 kg
Min.	-20°C

Operating Temperature	
Max. Operating Temperature	+50°C
Resistance to Chemicals	Not resistant to fat and mineral oil
Environmental Resistance	Suitable for predominantly dry environments
UV Resistance	Yes
Typical Applications	General industrial
Installation Method	Loose lay interlocking mats
Cleaning Method	Use a high pressure hose (not exceeding 60psi) to remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats
•	remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic
Method  COO (Country	remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats
Method  COO (Country of Origin)  Tensile	remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats  LK
Method  COO (Country of Origin)  Tensile Strength	remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats  LK  3 MPa
Method  COO (Country of Origin)  Tensile Strength  Elongation  Application	remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats  LK  3 MPa  250%

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com