Printed on 19/05/2022
Page n. 1 / 14
Replaced revision:22 (Dated 04/03/2021)

ΕN

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PRIMER NO 6 Product name

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Primer

1.3. Details of the supplier of the safety data sheet

CHT UK BRIDGWATER LTD Name Full address **Amber House Showground Road**

District and Country TA6 6AJ **Bridgwater** (Somerset)

England

Tel. +44(0)1278411400 +44(0)1278411444

e-mail address of the competent person

responsible for the Safety Data Sheet info.uk@cht.com

CHT Germany GmbH Supplier:

Bismarckstraße 102 72072 Tübingen Germany

1.4. Emergency telephone number

Australia: 0418529118 For urgent inquiries refer to

All other enquiries +44(0)1278 411400

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3 H226 Flammable liquid and vapour. Serious eye damage, category 1 H318 Causes serious eye damage. Skin irritation, category 2 H315 Causes skin irritation.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Danger

Hazard statements:

Flammable liquid and vapour. H226 H318 Causes serious eye damage. H315 Causes skin irritation

@EPY 11.1.2 - SDS 1004.14



Revision nr.23 Dated 19/05/2022 Printed on 19/05/2022 Page n. 2 / 14 Replaced revision:22 (Dated 04/03/2021)

SECTION 2. Hazards identification .../>>

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P310 Immediately call a POISON CENTER / doctor / . . .

Contains: TETRA N BUTYL TITANATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.1 Substances

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

OCTAMETHYLTRISILOXANE

CAS 107-51-7 $85 \le x < 89$ Flam. Liq. 3 H226

EC 203-497-4

INDEX

REACH Reg. 01-2119970219-31 TETRA N BUTYL TITANATE

CAS 5593-70-4 $5 \le x < 6$ Flam. Liq. 3 H226, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335,

STOT SE 3 H336

EC 227-006-8

INDEX

REACH Reg. 01-2119967423-33

TETRAKIS (2-BUTOXYETHYL) ORTHOSILICATE

CAS 18765-38-3 $4.5 \le x < 5$ STOT RE 2 H373, Skin Irrit. 2 H315

EC 242-560-0

INDEX

REACH Reg. 01-2120761533-55-0002

ETHYL SILÏCATE

CAS 78-10-4 0.6 ≤ x < 0.7 Flam. Liq. 3 H226, Acute Tox. 4 H332, Eye Irrit. 2 H319, STOT SE 3 H335 EC STA Inhalation vapours: 11 mg/l, STA Inhalation mists/powders: 1.5 mg/l

INDEX 014-005-00-0 REACH Reg. 01-2119496195-28

2-BUTOXYETHANOL

CAS 111-76-2 0 ≤ x < 0.1 Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315

EC 203-905-0 LD50 Oral: 1200 mg/kg, STA Inhalation vapours: 11 mg/l

INDEX 603-014-00-0 REACH Reg. 01-2119475108-36

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops





Revision nr.23 Dated 19/05/2022 Printed on 19/05/2022 Page n. 3 / 14 Replaced revision:22 (Dated 04/03/2021)

SECTION 4. First aid measures

breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may



Revision nr.23 Dated 19/05/2022 Printed on 19/05/2022 Page n. 4 / 14 Replaced revision:22 (Dated 04/03/2021)

SECTION 7. Handling and storage .../>>

accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021



Revision nr.23 Dated 19/05/2022 Printed on 19/05/2022 Page n. 5 / 14 Replaced revision:22 (Dated 04/03/2021)

SECTION 8. Exposure controls/personal protection .../>>

				OCTAMETHY	/LTRISILOXAN	NE .			
hreshold Limit Va	lue								
Туре	Country	TWA/8h		STEL/15	min	Remarks / 0	Observations		
		mg/m3	ppm	mg/m3	ppm				
OEL	EU	-	200	-		INHAL			
redicted no-effect	concentra	ation - PNEC	;						
Normal value for	fresh water	sediment					1.8	mg/kg	
Normal value for	marine wat	er sediment					0.17	mg/kg	
Normal value of S	STP microo	rganisms					1	mg/l	
Normal value for	the terrestr	ial compartm	ent				0.44	mg/kg	
lealth - Derived no	-effect lev	el - DNEL / D	MEL						
	Effe	cts on consu	mers			Effects on workers			
Route of exposur	e Acu	te Acu	te	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	loca	l syst	emic	local	systemic	local	systemic	local	systemic
Oral				VND	0.04		•		•
					mg/kg bw/d				
Inhalation				VND	19			VND	78
					mg/m3				mg/m3
Skin				VND	5.6			VND	11
					mg/kg bw/d				mg/kg
									bw/d

			TETRA	KIS (2-BUTOXY	ETHYL) ORTH	OSILICATE				
reshold Limit Val	lue									
Туре	Country	TWA/8h		STEL/15	min	Remarks / C	bservations			
		mg/m3	ppm	mg/m3	ppm					
OEL	EU	98				INHAL				
edicted no-effect	concentra	ation - PNEC	;							
Normal value in fr	esh water						10	mg/l		
Normal value in n	narine wate	er					1	mg/l		
Normal value for	fresh water	sediment					63.6	mg/kg/d		
Normal value for	marine wat	ter sediment					6.4	mg/kg/d		
Normal value of S	STP microo	rganisms					463	mg/l		
Normal value for	the terrestr	ial compartm	nent				0.57	mg/kg/d		
ealth - Derived no	-effect lev	el - DNEL / [DMEL							
	Effe	cts on consu	mers			Effects on workers				
Route of exposure	e Acu	te Acu	te	Chronic	Chronic	Acute	Acute	Chronic	Chronic	
	loca	l syst	temic	local	systemic	local	systemic	local	systemic	
Oral		•			12.5		•		•	
					mg/kg bw/d					
Inhalation					10.9				44	
					mg/m3				mg/m3	
Skin					12.5				25	
					mg/kg bw/d				mg/kg	



Revision nr.23 Dated 19/05/2022 Printed on 19/05/2022 Page n. 6 / 14 Replaced revision:22 (Dated 04/03/2021)

SECTION 8. Exposure controls/personal protection .../>>

				ETHY	L SILICATE				
hreshold Limit \	/alue								
Type Country		/ TWA/8h		STEL/15	STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm				
TLV	CZE	44	5.06	200	23				
AGW	DEU	12	1.4	12 (C)	1.4 (C)				
MAK	DEU	86	10	86	10				
TLV	DNK	44	5				E		
VLEP	FRA	85	10						
HTP	FIN	43	5	86	10				
AK	HUN	44							
VLEP	ITA	44	5						
TLV	NOR	44	5						
TGG	NLD	44							
VLE	PRT	44	5						
NDS/NDSCh	POL	44							
TLV	ROU	44	5						
NPEL	SVK	44	5						
WEL	GBR	44	5						
OEL	EU	44	5						
TLV-ACGIH		85	10						
redicted no-effe	ct concentra	ation - PNE	C						
Normal value in	n fresh water						0.19	mg/l	
Normal value in	n marine wate	er					0.019	mg/l	
Normal value for	or fresh wate	r sediment					0.83	mg/kg	
Normal value for	or marine wa	ter sedimen	t				0.083	mg/kg	
Normal value o	f STP microo	organisms					4000	mg/l	
Normal value for	or the terrest	rial compart	ment				0.05	mg/kg	
lealth - Derived r	no-effect lev	el - DNEL /	DMEL						
Effects on consumers				Effects on workers					
Route of expos	ure Acu	ite Ac	ute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	loca	al sy	stemic	local	systemic	local	systemic	local	systemic
Inhalation		•		25	25		-	85	85
				mg/m3	mg/m3			mg/m3	mg/m3
Skin				VND	8.4			VND	12.1
					mg/kg bw/d				mg/kg
									bw/d

				2-BUTO	(YETHANO	L		
Threshold Limit V	/alue							
Туре	Country	TWA/8h		STEL/15r	STEL/15min		bservations	
		mg/m3	ppm	mg/m3	ppm			
TLV	CZE	100	20.4	200	40.8	SKIN		
AGW	DEU	49	10	98 (C)	20 (C)	SKIN		
MAK	DEU	49	10	98	20	SKIN	Hinweis	
TLV	DNK	98	20			SKIN	E	
VLA	ESP	98	20	245	50	SKIN		
VLEP	FRA	49	10	246	50	SKIN		
HTP	FIN	98	20	250	50	SKIN		
AK	HUN	98		246		SKIN		
VLEP	ITA	98	20	246	50	SKIN		
TLV	NOR	50	10			SKIN		
TGG	NLD	100		246		SKIN		
VLE	PRT	98	20	246	50	SKIN		
NDS/NDSCh	POL	98		200		SKIN		
TLV	ROU	98	20	246	50	SKIN		
NGV/KGV	SWE	50	10	246	50	SKIN		
NPEL	SVK	98	20	246	50	SKIN		
ESD	TUR	98	20	246	50	SKIN		
WEL	GBR	123	25	246	50	SKIN		
OEL	EU	98	20	246	50	SKIN		
TLV-ACGIH		97	20					

Legend

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction. VND = hazard identified but no DNEL/PNEC available; NEA = no exposure expected; NPI = no hazard identified.



CHT UK BRIDGWATER LTD

PRIMER NO 6

Revision nr.23 Dated 19/05/2022 Printed on 19/05/2022 Page n. 7 / 14 Replaced revision:22 (Dated 04/03/2021)

SECTION 8. Exposure controls/personal protection/>

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Value Information

Appearance liquid
Colour straw-coloured

Odour characteristic of solvent

Melting point / freezing point Not available Initial boiling point Not available Flammability Not available Lower explosive limit Not available Upper explosive limit Not available 28 °C Flash point Auto-ignition temperature Not available рΗ Not available Kinematic viscosity Not available Dynamic viscosity liquid

Solubility immiscible with water

Partition coefficient: n-octanol/water
Vapour pressure
Density and/or relative density
Relative vapour density
Particle characteristics
Not available
Not available
Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU) 85.16 % - 706.80 g/litre



Revision nr.23 Dated 19/05/2022 Printed on 19/05/2022 Page n. 8 / 14 Replaced revision:22 (Dated 04/03/2021)

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

2-BUTOXYETHANOL

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

2 DUTOVVETHANOL

Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

2-BUTOXYETHANOL

May develop: hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

ATE (Dermal) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

ΕN



CHT UK BRIDGWATER LTD PRIMER NO 6

Revision nr.23 Dated 19/05/2022 Printed on 19/05/2022 Page n. 9 / 14 Replaced revision:22 (Dated 04/03/2021)

SECTION 11. Toxicological information .../>>

OCTAMETHYLTRISILOXANE

 LD50 (Dermal):
 > 2000 mg/kg (Rat)

 LD50 (Oral):
 > 2000 mg/kg (Rat)

 LC50 (Inhalation vapours):
 > 2350 ppm/4h (Rat)

TETRAKIS (2-BUTOXYETHYL) ORTHOSILICATE

LD50 (Oral): > 2000 mg/kg (Rat)

ETHYL SILICATE

LD50 (Dermal): > 2000 mg/kg (Rat) LD50 (Oral): > 2500 mg/kg (Rat)

2-BUTOXYETHANOL

LD50 (Oral): 1200 mg/kg Guinea pig LC50 (Inhalation vapours): 2.2 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure



ΕN



CHT UK BRIDGWATER LTD PRIMER NO 6

Revision nr.23 Dated 19/05/2022 Printed on 19/05/2022
Page n. 10 / 14
Replaced revision:22 (Dated 04/03/2021)

SECTION 11. Toxicological information

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

TETRAKIS (2-BUTOXYETHYL) ORTHOSILICATE

> 161 mg/l/72h (Scenedesmus subspicatus) EC50 - for Algae / Aquatic Plants

ETHYL SILICATE

> 193 mg/l/48h (Desmodesmus subspicatus green algae) EC50 - for Crustacea

12.2. Persistence and degradability

TETRAKIS (2-BUTOXYETHYL) ORTHOSILICATE

Rapidly degradable 98%, 28 day exposure time, method OECD TG 301 B

ETHYL SILICATE

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

2-BUTOXYETHANOL

1000 - 10000 mg/l Solubility in water

Rapidly degradable

12.3. Bioaccumulative potential

ETHYL SILICATE

Partition coefficient: n-octanol/water 3.18 **BCF** 3 16

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water 0.81

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.



Revision nr.23 Dated 19/05/2022 Printed on 19/05/2022 Page n. 11 / 14 Replaced revision:22 (Dated 04/03/2021)

SECTION 12. Ecological information .../>>

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1993

14.2. UN proper shipping name

ADR / RID: FLAMMABLE LIQUID, N.O.S. (OCTAMETHYLTRISILOXANE; TETRA N BUTYL TITANATE)
IMDG: FLAMMABLE LIQUID, N.O.S. (OCTAMETHYLTRISILOXANE; TETRA N BUTYL TITANATE)
IATA: FLAMMABLE LIQUID, N.O.S. (OCTAMETHYLTRISILOXANE; TETRA N BUTYL TITANATE)

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 30 Limited Quantities: 5 L Tunnel restriction code: (D/E)

Limited Quantities: 5 L

Special provision: 274, 601 IMDG: EMS: F-E, S-E

IATA: Cargo: Maximum quantity: 220 L Packaging instructions: 366
Pass.: Maximum quantity: 60 L Packaging instructions: 355

Special provision: A3

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

@EPY 11.1.2 - SDS 1004.14



Revision nr.23 Dated 19/05/2022 Printed on 19/05/2022 Page n. 12 / 14 Replaced revision:22 (Dated 04/03/2021)

SECTION 15. Regulatory information

All chemical substances in this material are included or exempted from listing on the AICS inventory of chemical substances

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0.1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3
Acute Tox. 4 Acute toxicity, category 4

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Eye Dam. 1 Serious eye damage, category 1 Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.

H332 Harmful if inhaled.H373 May cause damage to organs through prolonged or repeated exposure.

H318 Causes serious eye damage.
H315 Causes skin irritation.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.



CHT UK BRIDGWATER LTD

Revision nr.23
Dated 19/05/2022
Printed on 19/05/2022
Page n. 13 / 14
Replaced revision:22 (Dated 04/03/2021)

PRIMER NO 6

SECTION 16. Other information .../>

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

ΕN



CHT UK BRIDGWATER LTD PRIMER NO 6

Revision nr.23 Dated 19/05/2022 Printed on 19/05/2022 Page n. 14 / 14 Replaced revision:22 (Dated 04/03/2021)

SECTION 16. Other information .../>>

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review: The following sections were modified: 02 / 03 / 08 / 09 / 11 / 12 / 14 / 15 / 16.