

SAFETY DATA SHEET

Version # Issue date: Supersedes date: Revision date: 2,0 19-May-2021 17-March-2022 19-May-2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SPOTCLEAN Name of the substance

Identification number 603-117-00-0 (Index number)

Registration number 01-2119457558-25

Synonyms None.

Product code BDS001292BU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaners - Precision

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company name CRC Industries Europe by

Touwslagerstraat 1 **Address**

> 9240 Zele Belgium

Telephone +32(0)52/45.60.11 +32(0)52/45.00.34 Fax hse@crcind.com E-mail Website www.crcind.com

1.4. Emergency telephone

number

Tel.: +32(0)52/45.60.11 (office hours: 9-17h CET)

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons

Information Centre

Belgium National Poisons

Control Center

Bulgaria National Toxicological Information

Centre

070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

available for the Emergency Service.)

Czech Republic National Poisons Information

Centre

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

Control Center

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Estonia National Poisons

Information Centre

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Hungary National Emergency Phone Number 36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and **Emergency Department**

2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC)

030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)

Material name: SPOTCLEAN - Kontakt chemie - Europe

Norway Norwegian Poison 22 59 13 00 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.) **Information Center**

800 250 250 (Available 24 hours a day. SDS/Product information may not be **Portugal Poison Centre**

available for the Emergency Service.)

Romania Număr de telefon care poate fi apelat în caz

de urgență:

021 5992300, int. 291 Spitalul Clinic de Urgență București:

spital@urgentafloreasca.ro

0265 212111, 0265 211292, 0265 217235 Spitalul Clinic Judetean de Urgentă Romania

Târgu Mures: secretariat@spitjudms.ro

Slovakia National Toxicological Information

Centre

+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Sweden National Poison

Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.)

Switzerland Tox Info

Suisse

145 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The substance has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids Category 2 H225 - Highly flammable liquid and

vapour.

Health hazards

Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Specific target organ toxicity - single Category 3 narcotic effects H336 - May cause drowsiness or

exposure

dizziness.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Propan-2-ol; Isopropyl alcohol; Isopropanol

Hazard pictograms



Signal word Danger

Hazard statements

Highly flammable liquid and vapour. H225 Causes serious eye irritation. H319 May cause drowsiness or dizziness. H336

Precautionary statements

Prevention

Keep out of reach of children. P102

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Response Not assigned. Storage Not assigned.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information None.

2.3. Other hazards This substance does not meet vPvB / PBT criteria of Regulation (EC) No 1907/2006, Annex XIII.

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1. Substances

General information

Chemical name % CAS-No. / EC No. REACH Registration No. **Notes** Index No. 67-63-0 01-2119457558-25 603-117-00-0 Propan-2-ol; Isopropyl alcohol; 100 200-661-7 Isopropanol

Classification: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The full text for all H-statements is displayed in section 16. Composition comments

SECTION 4: First aid measures

General information Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves. Wash contaminated clothing

before reuse

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

delayed 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Highly flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

procedures

so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate

protective clothing.

For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection

recommended in Section 8 of the SDS.

Avoid discharge into drains, water courses or onto the ground. 6.2. Environmental precautions

Material name: SPOTCLEAN - Kontakt chemie - Europe SDS FII BDS001292BU Version #: 2,0 Revision date: 17-March-2022 Issue date: 19-May-2021

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Components	Туре	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	MAK	500 mg/m3
		200 ppm
	STEL	2000 mg/m3
		800 ppm
Belgium. Exposure Limit Values		
Components	Туре	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
		400 ppm
	TWA	500 mg/m3
		200 ppm
Bulgaria. OELs. Regulation No 13	on protection of workers aga	inst risks of exposure to chemical agents at work
Components	Туре	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3
alcohol; Isopropanol (CAS	STEL	1225 mg/m3 980 mg/m3
alcohol; Isopropanol (CAS 67-63-0) Croatia. Dangerous Substance Ex	TWA cposure Limit Values in the Wo	980 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09
alcohol; Isopropanol (CAS 67-63-0) Croatia. Dangerous Substance Ex Components	TWA oposure Limit Values in the Wo Type	980 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09 Value
alcohol; Isopropanol (CAS 67-63-0) Croatia. Dangerous Substance Ex	TWA cposure Limit Values in the Wo	980 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09
alcohol; Isopropanol (CAS 67-63-0) Croatia. Dangerous Substance Ex Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	TWA oposure Limit Values in the Wo Type	980 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09 Value

Material name: SPOTCLEAN - Kontakt chemie - Europe

BDS001292BU Version #: 2,0 Revision date: 17-March-2022 Issue date: 19-May-2021 4 /

500 ppm

Components	Туре	Value	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	980 mg/m3	
,		400 ppm	
Czech Republic. OELs. Governme	nt Decree 361		
Components	Туре	Value	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	Ceiling	1000 mg/m3	
	TWA	500 mg/m3	
Denmark. Exposure Limit Values			
Components	Туре	Value	
Propan-2-ol; Isopropyl Ilcohol; Isopropanol (CAS 57-63-0)	TLV	490 mg/m3	
		200 ppm	
		stances (Regulation No. 105/2001, Annex), as ame	nde
Components	Туре	Value	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3	
,		250 ppm	
	TWA	350 mg/m3	
		150 ppm	
Finland. Workplace Exposure Lim	ts		
Components	Туре	Value	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	620 mg/m3	
,		250 ppm	
	TWA	500 mg/m3	
		200 ppm	
France. Threshold Limit Values (V Components	LEP) for Occupational Exposur Type	e to Chemicals in France, INRS ED 984 Value	
Propan-2-ol; Isopropyl	VLE	980 mg/m3	
alcohol; Isopropanol (CAS 67-63-0)		500 mg/ms	
Regulatory status: Indicative	limit (VL)	400 ppm	
Regulatory status: Indicative	limit (VL)	400 μμπ	
	, ,	vestigation of Health Hazards of Chemical Compo	und
Components	Туре	Value	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	500 mg/m3	
		200 ppm	
Germany. TRGS 900, Limit Values Components	in the Ambient Air at the Work Type	olace Value	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	AGW	500 mg/m3	
67-63-0)			
		200 ppm	

Components	Туре	Value	
ropan-2-ol; Isopropyl Icohol; Isopropanol (CAS 7-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	
Hungary. OELs. Joint Decree on C Components	hemical Safety of Workplaces Type	Value	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3	
37 00 0)	TWA	500 mg/m3	
celand. OELs. Regulation 154/199	9 on occupational exposure li	mits	
Components	Туре	Value	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	490 mg/m3	
		200 ppm	
Ireland. Occupational Exposure Li			
Components	Туре	Value	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
Italy. Occupational Exposure Limi			
Components	Туре	Value	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
Latvia. OELs. Occupational expos Components	ure limit values of chemical so Type	ıbstances in work environment Value	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3	
 /	TWA	350 mg/m3	
Lithuania. OELs. Limit Values for	Chemical Substances, Genera	ıl Requirements	
Components	Туре	Value	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 37-63-0)	STEL	600 mg/m3	
,		250 ppm	
	TWA	350 mg/m3	
		150 ppm	
Norway. Administrative Norms for Components	Contaminants in the Workpla Type	ce Value	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TLV	245 mg/m3	
31-03-0)			
		100 ppm	

concentrations and intensities of harm Components	Туре	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1200 mg/m3
·	TWA	900 mg/m3
Portugal. VLEs. Norm on occupational	exposure to chemical aç	gents (NP 1796)
Components	Туре	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 37-63-0)	STEL	400 ppm
	TWA	200 ppm
Romania. OELs. Protection of workers		
Components	Туре	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 37-63-0)	STEL	500 mg/m3
		203 ppm
	TWA	200 mg/m3
		81 ppm
		of health in work with chemical agents
Components	Туре	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 57-63-0)	STEL	1000 mg/m3
,		
		400 ppm
	TWA	400 ppm 500 mg/m3
	TWA	
	ng protection of workers	500 mg/m3
Official Gazette of the Republic of Slo	ng protection of workers venia)	500 mg/m3 200 ppm
Official Gazette of the Republic of Slov Components	ng protection of workers venia) Type	500 mg/m3 200 ppm against risks due to exposure to chemicals while work Value
Official Gazette of the Republic of Slov Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	ng protection of workers venia)	500 mg/m3 200 ppm against risks due to exposure to chemicals while work
Official Gazette of the Republic of Slov Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	ng protection of workers venia) Type	500 mg/m3 200 ppm against risks due to exposure to chemicals while work Value 500 mg/m3
Cofficial Gazette of the Republic of Slow Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	ng protection of workers venia) Type	500 mg/m3 200 ppm against risks due to exposure to chemicals while work Value
(Official Gazette of the Republic of Slow Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Spain. Occupational Exposure Limits	ng protection of workers venia) Type	500 mg/m3 200 ppm against risks due to exposure to chemicals while work Value 500 mg/m3
Cofficial Gazette of the Republic of Slove Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Spain. Occupational Exposure Limits Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	ng protection of workers venia) Type TWA	500 mg/m3 200 ppm against risks due to exposure to chemicals while work Value 500 mg/m3 200 ppm
Official Gazette of the Republic of Slove Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Spain. Occupational Exposure Limits Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	ng protection of workers venia) Type TWA	500 mg/m3 200 ppm against risks due to exposure to chemicals while work Value 500 mg/m3 200 ppm Value
Cofficial Gazette of the Republic of Slove Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Spain. Occupational Exposure Limits Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	ng protection of workers venia) Type TWA	500 mg/m3 200 ppm against risks due to exposure to chemicals while work Value 500 mg/m3 200 ppm Value 1000 mg/m3
Official Gazette of the Republic of Slov Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Spain. Occupational Exposure Limits Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS	ng protection of workers venia) Type TWA Type STEL	500 mg/m3 200 ppm against risks due to exposure to chemicals while work Value 500 mg/m3 200 ppm Value 1000 mg/m3 400 ppm
Cofficial Gazette of the Republic of Slove Components Propan-2-ol; Isopropyle alcohol; Isopropanol (CAS 67-63-0) Spain. Occupational Exposure Limits Components Propan-2-ol; Isopropyle alcohol; Isopropanol (CAS 67-63-0)	ng protection of workers venia) Type TWA Type STEL TWA	500 mg/m3 200 ppm against risks due to exposure to chemicals while work Value 500 mg/m3 200 ppm Value 1000 mg/m3 400 ppm 500 mg/m3 200 ppm
Cofficial Gazette of the Republic of Slove Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Spain. Occupational Exposure Limits Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Sweden. OELs. Work Environment Aut Components Propan-2-ol; Isopropyl alcohol; Isopropyl alcohol; Isopropyl alcohol; Isopropyl alcohol; Isopropyl alcohol; Isopropyl alcohol; Isopropanol (CAS	ng protection of workers venia) Type TWA Type STEL TWA hority (AV), Occupationa	500 mg/m3 200 ppm against risks due to exposure to chemicals while work Value 500 mg/m3 200 ppm Value 1000 mg/m3 400 ppm 500 mg/m3 200 ppm
Cofficial Gazette of the Republic of Slove Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Spain. Occupational Exposure Limits Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Sweden. OELs. Work Environment Aut Components Propan-2-ol; Isopropyl alcohol; Isopropyl alcohol; Isopropyl alcohol; Isopropyl alcohol; Isopropyl alcohol; Isopropyl alcohol; Isopropanol (CAS	ng protection of workers venia) Type TWA Type STEL TWA hority (AV), Occupationa	500 mg/m3 200 ppm against risks due to exposure to chemicals while work Value 500 mg/m3 200 ppm Value 1000 mg/m3 400 ppm 500 mg/m3 200 ppm tl Exposure Limit Values (AFS 2015:7) Value
Slovenia. OELs. Regulations concernir (Official Gazette of the Republic of Slove Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Spain. Occupational Exposure Limits Components Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Sweden. OELs. Work Environment Aut Components Propan-2-ol; Isopropyl alcohol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	ng protection of workers venia) Type TWA Type STEL TWA hority (AV), Occupationa	500 mg/m3 200 ppm against risks due to exposure to chemicals while work Value 500 mg/m3 200 ppm Value 1000 mg/m3 400 ppm 500 mg/m3 200 ppm I Exposure Limit Values (AFS 2015:7) Value 600 mg/m3

Components	Туре)	Va	llue
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	-	10	00 mg/m3
•			40	0 ppm
	TWA		50	0 mg/m3
			20	0 ppm
UK. EH40 Workplace Exp	osure Limits (WELs)			
Components	Туре	•	Va	llue
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	-	12	50 mg/m3
			50	0 ppm
	TWA		99	9 mg/m3
			40	0 ppm
ogical limit values				
Croatia. BLV. Dangerous Components	Substance Exposure L Value	imit Values at Wo Determinant	orkplace, Annex Specimen	es 4 (as amended) Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	50 mg/l	Acetone	Urine	*
,	50 mg/l	Acetone	Blood	*
	0,86 umol/l	Acetone	Urine	*
	0,86 umol/l	Acetone	Blood	*
* - For sampling details, ple	ease see the source docu	ument.		
Germany. TRGS 903, BAT Components	List (Biological Limit) Value	Values) Determinant	Specimen	Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	25 mg/l	ACETON	Urine	*
,	25 mg/l	ACETON	Blood	*
* - For sampling details, ple	ease see the source docu	ument.		
		nce Joint Decree	No. 25/2000 (An	nex 2): Permissible limit values of
biological exposure (effe Material	ct) indices Value	Determinant	Specimen	Sampling Time
SPOTCLEAN	430 µmol/l	Acetone	Urine	*
Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	25 μg/l	Acetone	Urine	*
	430 µmol/l	Acetone	Urine	*
* - For sampling details, ple				
Spain. Biological Limit Va Components	alues (VLBs), Occupation	onal Exposure Li Determinant	mits for Chemic Specimen	al Agents, Table 4 Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	40 mg/l	Acetona	Urine	*
* - For sampling details, ple				
Switzerland. BAT-Werte (Components	Biological Limit Values Value	in the Workplace Determinant	e as per SUVA) Specimen	Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	25 mg/l	ACETON	Urine	*

ACETON

Blood

25 mg/l

* - For sampling details, please see the source document.

Follow standard monitoring procedures.

procedures

Derived no effect levels (DNELs)

Genera	al Pop	oulation

Components	Value	Assessment factor	Notes
Propan-2-ol; Isopropyl alcohol; Isopropand	ol (CAS 67-63-0)		
Long-term, Systemic, Dermal	319 mg/kg bw/day	2	Repeated dose toxicity
Long-term, Systemic, Inhalation	89 mg/m3	2	Repeated dose toxicity
Long-term, Systemic, Oral	26 mg/kg bw/day	2	Repeated dose toxicity
<u>Workers</u>			
Components	Value	Assessment factor	Notes
Propan-2-ol; Isopropyl alcohol; Isopropand	ol (CAS 67-63-0)		
Long-term, Systemic, Dermal	888 mg/kg bw/day	1	
Long-term, Systemic, Inhalation	500 mg/m3	1	
edicted no effect concentrations (PNECs			

Pre

Components	Value	Assessment fa	ctor Notes
Propan-2-ol; Isopropyl alcohol; Isoprop	anol (CAS 67-63-0)		
Freshwater	140,9 mg/l	1	
Secondary poisoning	160 mg/kg	30	Oral
Sediment (freshwater)	552 mg/kg		
Soil	28 mg/kg		

Exposure guidelines

Cyprus OEL: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol Can be absorbed through the skin.

(CAS 67-63-0)

Hungary OELs: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol Can be absorbed through the skin.

(CAS 67-63-0)

Iceland OELs: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol Can be absorbed through the skin.

(CAS 67-63-0)

Ireland Exposure Limit Values: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol Can be absorbed through the skin.

(CAS 67-63-0)

8.2. Exposure controls

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

Eye/face protection Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

- Hand protection When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than

the breakthrough time, gloves should be changed part-way through. Suitable gloves can be

recommended by the glove supplier. Neoprene gloves are recommended.

- Other Wear suitable protective clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with Respiratory protection

organic vapour cartridge and full facepiece. (Filter type A)

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

When using do not smoke. Always observe good personal hygiene measures, such as washing Hygiene measures

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to

acceptable levels.

Material name: SPOTCLEAN - Kontakt chemie - Europe

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid. Colourless. Colour Odour Alcohol.

-89 °C (-128,2 °F) Melting point/freezing point

Boiling point or initial boiling point and boiling range

82 °C (179,6 °F) 1013,1 hPa

Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

2,5 % Explosive limit - lower (%) Explosive limit - upper 12 %

(%)

Flash point 12,0 °C (53,6 °F) Closed cup

Auto-ignition temperature > 200 °C (> 392 °F)

Decomposition temperature Not available. pН Not available.

Solubility(ies)

Solubility (water) Soluble in water 42 hPa at 20°C Vapour pressure Not available. Vapour density 0,79 g/cm3 at 25°C Relative density

Particle characteristics

Particle size Not applicable

9.2. Other information

No relevant additional information available. 9.2.1. Information with regard to physical hazard classes

9.2.2. Other safety characteristics

2,1 mPa.s (25 °C (77 °F)) Dynamic viscosity

Evaporation rate Not available. **Explosive properties** Not explosive. 27,4 kJ/g Heat of combustion Molecular weight 60,1 g/mol **Oxidising properties** Not oxidising Particle size Not applicable

Surface tension 20,93 mN/m (25 °C (77 °F))

VOC 786 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

10.5. Incompatible materials Acids. Strong oxidising agents. Chlorine. Isocyanates.

10.6. Hazardous Carbon oxides.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Based on available data, the classification criteria are not met.

Eye contact Causes serious eye irritation.

Material name: SPOTCLEAN - Kontakt chemie - Europe SDS FU BDS001292BU Version #: 2,0 Revision date: 17-March-2022 Issue date: 19-May-2021

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

11.1. Information on toxicological effects

Based on available data, the classification criteria are not met. **Acute toxicity**

Components Species **Test Results**

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Acute Inhalation

LC50 Rat > 25000 mg/m3, 6 h

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitisation Based on available data, the classification criteria are not met. Skin sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met.

Hungary, 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met. **Aspiration hazard**

Mixture versus substance

information

Not available.

11.2. Information on other hazards

Endocrine disrupting

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Species Test Results Components

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Aquatic

Acute

Crustacea LC50 Brine shrimp (Artemia salina) > 10000 mg/l, 24 hours Fish LC50 > 1400 mg/l, 96 hours Bluegill (Lepomis macrochirus)

No data is available on the degradability of this substance. 12.2. Persistence and

degradability

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

0,05 **SPOTCLEAN** Propan-2-ol; Isopropyl alcohol; Isopropanol 0.05

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

This substance does not meet vPvB / PBT criteria of Regulation (EC) No 1907/2006, Annex XIII.

assessment

Material name: SPOTCLEAN - Kontakt chemie - Europe

12.6. Endocrine disrupting

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects

The product contains volatile organic compounds which have a photochemical ozone creation

potential.

12.8. Additional information

Estonia Dangerous substances in soil Data

Propan-2-ol; Isopropyl alcohol; Isopropanol

(CAS 67-63-0)

Chemical pesticides (As the total sum of the active substances)

0,5 mg/kg

Chemical pesticides (As the total sum of the active substances) 20

mg/kg

Chemical pesticides (As the total sum of the active substances) 5

mg/kg

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code

The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number

14.2. UN proper shipping

ISOPROPANOL

ISOPROPANOL

UN1219

name

14.3. Transport hazard class(es)

Class 3 Subsidiary risk

Hazard No. (ADR) Not available.

Tunnel restriction code (D/E) ADR/RID - Classification F1

code:

14.4. Packing group 14.5. Environmental hazards No

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

ΙΔΤΔ

14.1. UN number UN1219

14.2. UN proper shipping

14.3. Transport hazard class(es)

3 Class Subsidiary risk 14.4. Packing group Ш 14.5. Environmental hazards No

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

IMDG

14.1. UN number UN1219

14.2. UN proper shipping **ISOPROPANOL**

name

14.3. Transport hazard class(es)

3 Class Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards Marine pollutant Nο

Material name: SPOTCLEAN - Kontakt chemie - Europe

EmS F-E. S-D

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

14.7. Maritime transport in bulk

according to IMO instruments

Not established.

ADR; IATA; IMDG



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Other regulations

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland

Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

Material name: SPOTCLEAN - Kontakt chemie - Europe

SDS FII

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification,

labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value. VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

Not available.

Not applicable.

References

Information on evaluation method leading to the classification of mixture

Full text of any H-statements not written out in full under

Sections 2 to 15

Revision information

Training information Disclaimer

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Physical & Chemical Properties: Multiple Properties

SECTION 12: Ecological information: 12,6. Endocrine disrupting properties

SECTION 16: Other information: Disclaimer

REACH: Registration Substance

Follow training instructions when handling this material.

CRC Industries Europe byba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

Material name: SPOTCLEAN - Kontakt chemie - Europe