



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 13

BERGQUIST HI FLOW THF 1600P known as Hi-Flow 300P

SDS No. : 640747  
V001.2

Revision: 10.10.2022

printing date: 17.10.2022

Replaces version from: 23.08.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

BERGQUIST HI FLOW THF 1600P known as Hi-Flow 300P

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Thermal Interface Material

#### 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

#### 2.2. Label elements

##### Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

**Supplemental information** Safety data sheet available on request.

#### 2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration  $\geq 0,1\%$  and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration  $\geq$  the concentration limit that are assessed to be a PBT, vPvB or ED.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
N,N-dimethylacetamide 127-19-5 204-826-4	0,1- < 0,3 %	Acute Tox. 4, Dermal, H312 Acute Tox. 4, Inhalation, H332 Repr. 1B, H360D		SVHC EU OEL
diboron trioxide 1303-86-2 215-125-8 01-2119486655-24	0,1- < 0,3 %	Repr. 1B, H360FD		SVHC

For full text of the H - statements and other abbreviations see section 16 "Other information".  
Substances without classification may have community workplace exposure limits available.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated contact may cause eye irritation.

Prolonged or repeated contact may cause skin irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

High pressure waterjet

**5.2. Special hazards arising from the substance or mixture**

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

In case of fire, keep containers cool with water spray.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**

In case of fire, keep containers cool with water spray.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

**6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

**6.3. Methods and material for containment and cleaning up**

Scrape up as much material as possible.

Sweep up spilled material. Avoid creating dust.

Store in a partly filled, closed container until disposal.

Dispose of contaminated material as waste according to Section 13.

**6.4. Reference to other sections**

See advice in section 8

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

**7.2. Conditions for safe storage, including any incompatibilities**

Ensure good ventilation/extraction.

Keep container tightly sealed.

Refer to Technical Data Sheet

**7.3. Specific end use(s)**

Thermal Interface Material

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational Exposure Limits

Valid for  
Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Aluminium oxide 1344-28-1 [ALUMINIUM OXIDES, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Aluminium oxide 1344-28-1 [ALUMINIUM OXIDES, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Paraffin waxes and Hydrocarbon waxes 8002-74-2 [Paraffin wax, fume]		6	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Paraffin waxes and Hydrocarbon waxes 8002-74-2 [Paraffin wax, fume]		2	Time Weighted Average (TWA):		EH40 WEL
N,N-Dimethylacetamide 127-19-5 [N,N-DIMETHYLACETAMIDE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
N,N-Dimethylacetamide 127-19-5 [N,N-DIMETHYLACETAMIDE]	10	36	Time Weighted Average (TWA):		EH40 WEL
N,N-Dimethylacetamide 127-19-5 [N,N-DIMETHYLACETAMIDE]	20	72	Short Term Exposure Limit (STEL):	Indicative	ECTLV
N,N-Dimethylacetamide 127-19-5 [N,N-DIMETHYLACETAMIDE]	10	36	Time Weighted Average (TWA):	Indicative	ECTLV
N,N-Dimethylacetamide 127-19-5 [N,N-DIMETHYLACETAMIDE]	20	72	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
N,N-Dimethylacetamide 127-19-5 [N,N-Dimethylacetamide]	10	36	Time Weighted Average (TWA):		EU OELIII
N,N-Dimethylacetamide 127-19-5 [N,N-Dimethylacetamide]		72	Short Term Exposure Limit (STEL):		EU OELIII
N,N-Dimethylacetamide 127-19-5 [N,N-Dimethylacetamide]	20		Short Term Exposure Limit (STEL):		EU OELIII
N,N-Dimethylacetamide 127-19-5 [N,N-Dimethylacetamide]			Skin designation:	Can be absorbed through the skin.	EU OELIII
Diboron trioxide 1303-86-2 [DIBORON TRIOXIDE]		10	Time Weighted Average (TWA):		EH40 WEL
Diboron trioxide 1303-86-2 [DIBORON TRIOXIDE]		20	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

#### Occupational Exposure Limits

Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Aluminium oxide 1344-28-1 [ALUMINIUM OXIDES]		4	Time Weighted Average (TWA):		IR_OEL
Aluminium oxide 1344-28-1 [ALUMINIUM OXIDES]		10	Time Weighted Average (TWA):		IR_OEL
Paraffin waxes and Hydrocarbon waxes		2	Time Weighted Average		IR_OEL

8002-74-2 [PARAFFIN WAX]			(TWA):		
Paraffin waxes and Hydrocarbon waxes 8002-74-2 [PARAFFIN WAX]		6	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
N,N-Dimethylacetamide 127-19-5 [N,N'-DIMETHYLACETAMIDE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
N,N-Dimethylacetamide 127-19-5 [N,N'-DIMETHYLACETAMIDE]	10	36	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
N,N-Dimethylacetamide 127-19-5 [N,N-DIMETHYLACETAMIDE]	20	72	Short Term Exposure Limit (STEL):	Indicative	ECTLV
N,N-Dimethylacetamide 127-19-5 [N,N-DIMETHYLACETAMIDE]	10	36	Time Weighted Average (TWA):	Indicative	ECTLV
N,N-Dimethylacetamide 127-19-5 [N,N'-DIMETHYLACETAMIDE]	20	72	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
N,N-Dimethylacetamide 127-19-5 [N,N-Dimethylacetamide]	10	36	Time Weighted Average (TWA):		EU OELIII
N,N-Dimethylacetamide 127-19-5 [N,N-Dimethylacetamide]		72	Short Term Exposure Limit (STEL):		EU OELIII
N,N-Dimethylacetamide 127-19-5 [N,N-Dimethylacetamide]	20		Short Term Exposure Limit (STEL):		EU OELIII
N,N-Dimethylacetamide 127-19-5 [N,N-Dimethylacetamide]			Skin designation:	Can be absorbed through the skin.	EU OELIII
Diboron trioxide 1303-86-2 [BORON OXIDE]		10	Time Weighted Average (TWA):		IR_OEL

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
diboron trioxide 1303-86-2	aqua (freshwater)		2,9 mg/l				
diboron trioxide 1303-86-2	aqua (marine water)		2,9 mg/l				
diboron trioxide 1303-86-2	sewage treatment plant (STP)		10 mg/l				
diboron trioxide 1303-86-2	Soil				5,7 mg/kg		

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
diboron trioxide 1303-86-2	Workers	inhalation	Long term exposure - systemic effects		4,66 mg/m <sup>3</sup>	
diboron trioxide 1303-86-2	Workers	dermal	Long term exposure - systemic effects		220,6 mg/kg	

**Biological Exposure Indices:**

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
N,N-Dimethylacetamide 127-19-5 [N,N-DIMETHYLACETAMIDE]	N-Methylacetamide	Creatinine in urine	Sampling time: End of shift.		UKEH40BMG V		

**8.2. Exposure controls:**

Engineering controls:  
Ensure good ventilation/extraction.

Respiratory protection:  
Ensure adequate ventilation.  
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area  
Filter type: A (EN 14387)

Hand protection:  
Chemical-resistant protective gloves (EN 374).  
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):  
nitrile rubber (NBR;  $\geq 0.4$  mm thickness)  
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):  
nitrile rubber (NBR;  $\geq 0.4$  mm thickness)  
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:  
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.  
Protective eye equipment should conform to EN166.

Skin protection:  
Wear suitable protective clothing.  
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state	solid
Delivery form	solid
Colour	green
Odor	None
Melting point	Not applicable, Decomposes.
Solidification temperature	Not applicable, Product is a solid.
Initial boiling point	> 200 °C (> 392 °F)
Flammability	The product is not flammable.
Explosive limits	Not applicable, Product is a solid.
Flash point	Not applicable, Product is a solid.
Auto-ignition temperature	Not applicable, Product is a solid.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no

	organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic)	Not applicable, Product is a solid.
Solubility (qualitative)	Insoluble
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	< 1 hPa
(20 °C (68 °F))	
Density	2,1 - 2,3 g/cm <sup>3</sup>
(20 °C (68 °F))	
Bulk density	2,2 g/cm <sup>3</sup>
Relative vapour density:	Not applicable, Product is a solid.
Particle characteristics	Not applicable
	Product is not powder.

## 9.2. Other information

Other information not applicable for this product

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reaction with strong acids.  
Reacts with strong oxidants.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

carbon oxides.

## SECTION 11: Toxicological information

### General toxicological information:

Prolonged or repeated contact may cause skin irritation.  
Prolonged or repeated contact may cause eye irritation.

### 1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
N,N-dimethylacetamide 127-19-5	LD50	4.930 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
diboron trioxide 1303-86-2	LD50	> 2.600 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
diboron trioxide 1303-86-2	LD50	> 2.000 mg/kg	rabbit	not specified

**Acute inhalative toxicity:**

No data available.

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
diboron trioxide 1303-86-2	not irritating	24 h	rabbit	not specified

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
diboron trioxide 1303-86-2	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
diboron trioxide 1303-86-2	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
diboron trioxide 1303-86-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
diboron trioxide 1303-86-2	negative	mammalian cell gene mutation assay	with and without		not specified
diboron trioxide 1303-86-2	negative	sister chromatid exchange assay in mammalian cells	with and without		not specified
diboron trioxide 1303-86-2	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
diboron trioxide 1303-86-2	not carcinogenic	oral: feed	103 w daily	mouse	male/female	OECD Guideline 451 (Carcinogenicity Studies)



**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
diboron trioxide 1303-86-2	NOAEL P 336 mg/kg NOAEL F1 100 mg/kg NOAEL F2 100 mg/kg	three- generation study	oral: feed	rat	not specified

**STOT-single exposure:**

No data available.

**STOT-repeated exposure::**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
diboron trioxide 1303-86-2	NOAEL 100 mg/kg	oral: feed	2 y daily	rat	not specified

**Aspiration hazard:**

No data available.

**11.2 Information on other hazards**

not applicable

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
N,N-dimethylacetamide 127-19-5	LC50	> 500 mg/l	96 h	Leuciscus idus	DIN 38412-15
diboron trioxide 1303-86-2	LC50	513,3 mg/l	96 h	Pimephales promelas	other guideline:
diboron trioxide 1303-86-2	NOEC	41,2 mg/l	34 d	Danio rerio (reported as Brachydanio rerio)	OECD Guideline 210 (fish early lite stage toxicity test)

#### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
N,N-dimethylacetamide 127-19-5	EC50	> 500 mg/l	48 h	other aquatic arthropod:	EU Method C.2 (Acute Toxicity for Daphnia)
diboron trioxide 1303-86-2	EC50	586,04 mg/l	48 h	Ceriodaphnia dubia	other guideline:

#### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
diboron trioxide 1303-86-2	NOEC	69,6 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

#### Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
N,N-dimethylacetamide 127-19-5	EC50	> 500 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
diboron trioxide 1303-86-2	EC50	337,5 mg/l	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
diboron trioxide 1303-86-2	EC10	225,4 mg/l	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
N,N-dimethylacetamide 127-19-5	EC10	> 1.995 mg/l	30 min		not specified

### 12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
N,N-dimethylacetamide 127-19-5	inherently biodegradable	aerobic	96 %	5 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
N,N-dimethylacetamide 127-19-5	readily biodegradable, but failing 10-day window	aerobic	70 %	28 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available for the product.

No substance data available.

### 12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
diboron trioxide 1303-86-2	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.

### 12.6. Endocrine disrupting properties

not applicable

### 12.7. Other adverse effects

No data available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09\* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

**SECTION 14: Transport information**

- 14.1. UN number or ID number**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Maritime transport in bulk according to IMO instruments**  
not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 3 %

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H312 Harmful in contact with skin.  
H332 Harmful if inhaled.  
H360D May damage the unborn child.  
H360FD May damage fertility. May damage the unborn child.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

**Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**