



Glass fibre Insulated Flat Pair Types 'K', 'J' & 'T' 1/0.3 solid strand— to IEC584



- Glass fibre insulated flat pair construction, conductors laid flat, Glass fibre insulated with Glass fibre overall, silicone varnished throughout
- Good temperature resistance but not suitable where fluids are present
- All types; conductors are made from associated K, J or T thermocouple alloy type
- Tolerance Class 2 to IEC-584
- Insulation rating -60°C to 350°C (short periods up to 400°C)
- Colour code (cores & jacket) to IEC-584-3

We are the largest UK manufacturer of both temperature sensors and thermocouple connectors

About Labfacility

Measurement.

Formed in 1971, Labfacility specialize in the field of Temperature and Process

Quality & Service

Quality and Service are key elements in the continued growth of Labfacility.

Technical support is always freely available from our experienced technical sales teams and the company has ISO9001 accreditation.

COD	tact	Detai	16
	Laul		110

Email sales@labfacility.com

Website www.labfacility.com

Туре	Conductors	Cores	Jacket	Reel Length	Manufacturers	order code
туре	Conductors	cores	Jacket	Reel Leligtii		order code
					Code	
K	1/0.3mm	+Green/-White	Green	5 metres	WK-351-D	XF-1973-FAR
K	1/0.3mm	+Green/-White	Green	10 metres	WK-351-D	708-5930
K	1/0.3mm	+Green/-White	Green	25 metres	WK-351-D	XF-1315-FAR
K	1/0.3mm	+Green/-White	Green	50 metres	WK-351-D	708-5941
K	1/0.3mm	+Green/-White	Green	100 metres	WK-351-D	XF-1290-FAR
К	1/0.3mm	+Green/-White	Green	200 metres	WK-351-D	XF-1301-FAR
К	1/0.508mm	+Green/-White	Green	25 metres	WK-352-D	XF-1253-FAR
К	1/0.508mm	+Green/-White	Green	50 metres	WK-352-D	XF-1258-FAR
J	7.02mm	+Black/-White	Black	10 metres	WJ-231-D	XF-1809-FAR
J	7.02mm	+Black/-White	Black	25 metres	WJ-231-D	XF-1778-FAR
J	7.02mm	+Black/-White	Black	50 metres	WJ-231-D	XF-1783-FAR
J	7.02mm	+Black/-White	Black	100 metres	WJ-231-D	XF-1771-FAR
Т	1/0.3mm	+Brown/-White	Brown	10 metres	WT-356-D	708-5953
Т	1/0.3mm	+Brown/-White	Brown	25 metres	WT-356-D	XF-1812-FAR
Т	1/0.3mm	+Brown/-White	Brown	50 metres	WT-356-D	XF-1821-FAR
Т	1/0.3mm	+Brown/-White	Brown	100 metres	WT-356-D	XF-1967-FAR