Type A Plug to Type A Plug

pro-signal



Specifications

Connector to Connector USB Standard Contact Resistance Insulation Resistance Cable Length Jacket Colour : Type A Plug to Type A Plug

: USB 3.0


: 2Ω Max.

: DC 300V/10ms, 10MΩ Min.

: 1m (3.28ft)

: Blue





Pin Assignment <u>Conn.1</u>
1 1
2 2
3 3
4 4
5 8
6 - (-) - 9
7 - 7
Shield
Shell Shell

No	Description	Qty.	Unit
1	UL 20275 USB 3.0 Cable (28AWG×1P+EAM)×2+28AWG×1 P+28AWG×2C+ADB OD:5.5±0.2mm 65% AL Colour: Blue	1	m
2	USB 3.0 A (M) 9P Connector	2	PCs
3	USB 3.0 A (M) Tin plate		
4	USB 3.0 A (M) Tin plate		
5	USB 3.0 AM Tee Connector		
6	45P Blue PVC	18	g

Part Number Table

	Description	Part Number	
imensions : Millimetres	Type A Plug to Type A Plug, Blue, 1m	CAC250018	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for white any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands

