

Electromechanical Audio Transducer

multicompPRO

**RoHS
Compliant**



Features

- Surface mount
- Black in colour
- Housing material : LCP
- Very small and low profile


Specifications

Rated voltage	: 3.6Vp-p
Operating voltage	: 2.5 to 4.5Vp-p
Rated current at rated voltage	: ≤90mA
Sound output at 2730Hz at 10cm at rated voltage	: ≥85dB
Resonant frequency	: 2,730Hz
Coil resistance	: 16 ±3Ω
Operating temperature	: -30°C to +80°C
Storage temperature	: -40°C to +85°C
Weight	: 0.5g

Requires additional electronic circuitry to operate as a sounder

All data at 25°C unless otherwise specified

Diagram




Dimensions : Millimetres
Tolerance : ± 0.2mm

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicompPRO

Surface Mount Transducer - Reflow Solder Profile



Part Number Table

Description	Part Number
Transducer, Surface Mount, Audio	ABT-443-RC

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.