

LC1G4004EHEA

Contactor, high power, TeSys Giga, advanced version, AC-1, <= 440V, 550A, 4 pole/NO, 48-130VAC/DC coil



Main

Range	TeSys
Range of Product	TeSys Giga
Product or Component Type	Contactor
Device short name	LC1G
Contactor application	Power switching
Utilisation category	AC-1 AC-5a AC-5b AC-6a AC-6b DC-1 DC-3 DC-5
Poles description	4P
[Ue] rated operational voltage	<= 1000 V AC 50/60 Hz <= 460 V DC
[Ie] rated operational current	550 A 104 °F (40 °C)) 1000 V AC-1
[Uc] control circuit voltage	48...130 V AC/DC 50/60 Hz
Color	Dark grey

Complementary

[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	550 A 104 °F (40 °C)
Rated breaking capacity	3480 A 440 V
[Icw] rated short-time withstand current	3.6 KA - 10 s 2.4 KA - 30 s 1.7 KA - 1 min 1.2 KA - 3 min 1.0 kA - 10 min
Associated fuse rating	500 A aM 440 V 315 A aM 690 V 630 A gG 690 V
Average impedance	0.0001 Ohm
[Ui] rated insulation voltage	1000 V
Power dissipation per pole	30 W AC-1 - Ith 550 A
Compatibility code	LC1G
Pole contact composition	4 NO
Auxiliary contact composition	1 NO + 1 NC
Network Frequency	50/60 Hz 16.67...400 Hz
Maximum Horse Power Rating	125 Hp 200/208 V at 60 Hz 150 Hp 230/240 V at 60 Hz 300 Hp 460/480 V at 60 Hz 400 hp 575/600 V at 60 Hz
Irms rated making capacity	5090 A 440 V
Control circuit voltage limits	Operational 0.8...1.1 Uc AC/DC 140 °F (60 °C)) Drop-out 0.1...0.45 Uc AC/DC 140 °F (60 °C))
Coil technology	Built-in bidirectional peak limiting

Mechanical durability	5 Mcycles 8 Mcycles with sub-assembly substitution
Inrush power in VA (50/60 Hz, AC)	450 VA
Inrush power in W (DC)	360 W
Hold-in power consumption in VA (50/60 Hz, AC)	11.7 VA
Hold-in power consumption in W (DC)	8.3 W
Operating time	45...60 ms closing 15...45 ms opening
Maximum operating rate	300 cyc/h AC-1
Connections - terminals	Power circuit bar 2 32 x 10 mm Power circuit lugs-ring terminals 1 0.29 in ² (185 mm ²) Power circuit bolted connection Control circuit push-in 1 0.00...0.00 in ² (0.2...2.5 mm ²) solid stranded without cable end Control circuit push-in 1 0.00...0.00 in ² (0.25...2.5 mm ²) flexible with cable end Control circuit push-in 2 0.00...0.00 in ² (0.5...1.0 mm ²) with cable end Control circuit push-in 0.00...0.00 in ² (0.75...2.5 mm ²) solid stranded without cable end Control circuit push-in 0.00...0.00 in ² (0.75...2.5 mm ²) flexible with cable end
Connection pitch	1.77 in (45 mm)
Mounting Support	Plate
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 JIS C8201-5-1
Product Certifications	CB Scheme CCC CULus EAC CE UKCA EU-RO-MR by DNV-GL
Tightening torque	309.78 lbf.in (35 N.m)
Height	11.42 in (290 mm)
Width	7.28 in (185 mm)
Depth	8.86 in (225 mm)
Net Weight	19.18 lb(US) (8.7 kg)

Environment

IP degree of protection	IP2x front face with shrouds IEC 60529 IP2x front face with shrouds VDE 0106
Ambient Air Temperature for Operation	-13...140 °F (-25...60 °C)
Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
Mechanical robustness	Vibrations 5...300 Hz 2 gn contactor open Vibrations 5...300 Hz 4 gn contactor closed Shocks 10 gn 11 ms contactor open Shocks 15 gn 11 ms contactor closed
Protective treatment	TH
Permissible ambient air temperature around the device	-40...158 °F (-40...70 °C) at Uc

Ordering and shipping details

Category	22329-TESYS GIGA CONTACTORS
Discount Schedule	I12
GTIN	3606481922687
Nbr. of units in pkg.	1
Package weight(Lbs)	24.14 lb(US) (10.95 kg)
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.63 in (27.0 cm)
Package 1 width	12.40 in (31.5 cm)
Package 1 Length	14.57 in (37.0 cm)
Unit Type of Package 2	S06
Number of Units in Package 2	4
Package 2 Weight	120.15 lb(US) (54.5 kg)
Package 2 Height	29.53 in (75.0 cm)
Package 2 width	23.62 in (60.0 cm)
Package 2 Length	31.50 in (80.0 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product