

# Nozzle Thermocouple, Glassfibre insulated Cable with Stainless Steel Over-Braid Terminating in Bare tails, Miniature or Standard Plug- JIS



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockists of Thermocouple Cables. The Company has been trading since 1971 and is ISO 9001 accredited.

Labfacility have supplied Farnell for over 30 years, and an extensive range of our products are available to buy online, from stock, direct from Farnell.

# **Datasheet**



# **Specifications**

<b>General Description</b>	Thermocouple housed in a stainless steel threaded bolt		
Thermocouple Type	K		
Thermocouple Junction	Grounded hot junction for fast response, M6x1mm thread		
Cable Length	1, 2 or 5m		
Cable Type	Glassfibre insulated lead with stainless steel overbraid		
Core / Strands	7/0.2mm		
Termination Type	Bare tails, Miniature or Standard Plug (with cable clamps)		
Max. Temperature	+350°C		
Min. Temperature	-60°C		
Standards Met	JIS		
Thread	M6 x 1mm thread		

# **Ordering Information**

Thermocouple Type	Cable Length	Termination	Farnell Order Code
K	1m	Bare Tails	XF-2138-FAR
K	2m	Bare Tails	XF-2139-FAR
K	5m	Bare Tails	XF-2140-FAR
K	1m	Miniature Plug	XF-2135-FAR
K	2m	Miniature Plug	XF-2136-FAR
K	5m	Miniature Plug	XF-2137-FAR
K	1m	Standard Plug	XF-2125-FAR
K	2m	Standard Plug	XF-2126-FAR
K	5m	Standard Plug	XF-2127-FAR

TC-42 Feb-23



#### Thermocouple & PRT Cable

Thermocouple cables are available in IEC or ANSI colour codes. Insulation types include PFA, PTFE, PVC &

Fibreglass. Available spool lengths include 10, 25, 50, 100 and 200m.

## Best Sellers



**ANSI PTFE Insulated Twin Twisted** Farnell 2443696 Newark 73AC8304

**ANSI PFA Insulated** Twin Twisted Farnell 2443711 Newark 73AC8297

### **Fabricated and Specialist Thermocouples**

Styles include; Magnet, Washer, Nozzle, Leaf, Bayonet & Bolt thermocouple. Various lengths and calibration types available.

# **Best Sellers**



Washer Thermocouple Farnell 8597952 Newark 38K1555



Magnet Thermocouple Farnell 2081298 Newark 88T2877



# Thermocouples

Including exposed junctions with fitted or moulded miniature plug and insulated leads, ideal for test and development applications.

1, 2, 3, 5 & 10m lengths available in IEC or ANSI colours.

# **Best Sellers**









### Thermocouple Connectors

Range of miniature or standard thermocouple connectors. Available in thermocouple types K, J, T, E, N, RS, B, and copper. IEC, ANSI & JIS colour codes available.







**IEC Thermocouple** Plug

Farnell 7086362 Newark 67C1559





#### **RTD Detectors**

Wire-wound type provides greater accuracy and stability but are vulnerable to shock.

Flat film type are resistant to shock and have quicker thermal response times.

Various lengths and diameters available, in class A, B and 1/10th Din.

# **Best Sellers**



Film Detector Farnell 8598550 Newark 38K0883

PT100 Wire **Wound Detector** 

Farnell 2770776 Newark 25AC2608

PT100 Class A Thin Film Detector

Farnell 8598525 **Newark 38K0885** 



## Mineral Insulated Thermocouples

Available in various calibration types with a variety of terminations.

These include; Thermocouple plugs, Terminal heads and Thermocouple cable.

## **Best Sellers**



**ANSI Thermocouple** Farnell 2420317 Newark 53X3217

IEC Thermocouple with Mini Plug Farnell 4248338

Newark 19J1166

**IEC Melt Bolt** Thermocouple Farnell 2816490 Newark 44AC8638



Pt100 Heavy Duty Sensor Probe Farnell 8598096 Newark 38K0974



Pt100 Sensor in Stainless Steel Tube with Teflon Lead Farnell 2420300 Newark 53X3459

Pt100 Outdoor/ Cold Store Temperature Sensor Farnell 2816462 Newark 44AC8648

## L60 Fine Wire Thermocouple Welder

The Thermocouple Welder is a compact, simple-to-use instrument designed for thermocouple and fine wire welding. Supplied with foot switch, spare electrodes, pliers & safety glasses, impact clip and pen plate.

# **Best Sellers**







L60+ Thermocouple & Fine Wire Welder and accessories Farnell 2897470 Newark 62AC8741

applications and styles, available in class A or B.

Resistance Thermometer

Detectors (RTD) / Platinum

Resistance Thermometers (PRT)

To suit a wide range of

TC-42