



RoHS
Compliant

Physical Properties

Diameter	: 0.71mm $\pm$ 0.05mm
Tensile Strength	: 7.93 kg.
Elongation Percent	: 15
UV Resistance	: Pass UL – 1581 720h Sunlight
Core Type	: Nylon
Coating Type	: Black, PVC
Length	: 25m

Thermal Properties

Cold Flex Tolerance	: -54°C UL – 1581 Cold Bend
Maximum Service Temp.	: 138°C 168 Hours Continuous Exposure
Brittleness Temperature	: -15°C A.S.T.M. D - 746
Flame Resistance	: Pass M VSS 302, SAEJ369, & UL94 VO @ 125 mils.

Part Number Table

Description	Part Number
Lacing Cord, PVC, Black, 25m	81400000

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of Premier Farnell Limited 2019.