

Valuable convenience in a wide range of applications




Less Effort

Compact/Lightweight



Easy switch operation

One finger operation for switch-on/forward/reverse



Recharge any time/any place

Recharge built-in Li-Ion battery with *USB Type-C™ cable. Simple and quick charging like smart phones.





*USB Type- C^{TM} is a trademark of USB Implementers Forum

Easy and quick fastening





Convenient single-handed operation in any direction

Switch synchronized LED light

Lighting up dark spot, and low battery/overload warning

Sufficient capacity with quick charge

More than 600 x (M3x5) metal screws with one full charge in approx. 45 minutes.



Increased Safety

Double durable housing structure

The internal mechanism is entirely enclosed in a heavy duty, double layered housing for increased insulation durability. At the Panasonic R&D lab, this cordless screwdriver body has been rigorously tested for high voltage insulation durability according to the same testing procedure of DIN EN IEC60900.



Ensure higher insulation level as well as foreign material exclusion in professional job site use.

Double-safety insulated bit structure

The insulated bits are tested according to DIN EN IEC 60900 at VDE.

- The surface of each bit is molded with a highly durable, red insulated plastic coating for safety.
- In addition, the 'non-standard' bit shank size(6mm) prevents standard hex bits from being inserted by mistake.





Inner housin



Image photo

(Image photo) Input 10,000VAC for 3 minutes by immersing in



(Image photo) Input 10,000VA for 3 minutes with insulated manual grip by immersing in water pool.

High Durability

3 x Battery protection control

High density electronic circuit has three protection control of over-charge, over-load and over-discharge for ensuring longer battery life.

IP56 – Dust and water resistance body





Charging status indication



Over-load/discharge warning



Front rubber ring





Middle rubber ring



End cap rubber ring

Cordless Screwdriver with Insulated Feature





Bit set included

- PZ1 (75mm) x 1
- PZ2 (75mm) x 1
- PH1 (75mm) x 1
- PH2 (75mm) x 1
- SL4.0 (0.8/75mm) x 1
- SL6.0 (1.2/75mm) x 1

Specifications (approx.)

Chuck	6mm Hex for Panasonic insulated bit		
Maximum instant torque	1 Nm (Max. screw size : M3)		
Shaft lock durability	up to 8 Nm (Max. screw size : M6)		
Speed at no load	230 min ⁻¹		
Electric brake	Yes		
LED light	Yes		
Battery (built-in)	Li-ion DC3.7V 850mAh		
Charging terminal	*USB Type-C™ (DC 5V)		
Charging time	45 minutes with commercial available USB charging adaptor 5V 1A		
Dimensions / Weight	146 x 46mm / 220g		
Battery capacity (approx. with full charge)	Small metal screws (without washer)	M3 x 5	690
		M3 x 10	420
		M3 x 16	180
Dust / Water protection	IP56		

*USB Type- C^{TM} is a trademark of USB Implementers Forum.

Accessories

Panasonic insulated manual screwdriver grip and bits are tested according to DIN EN IEC 60900 at VDE.



Insulated manual screwdriver grip



EYEGH1SA with PZ1 (75mm) x 1

2 pcs Insulated-Bit Set



EY9EBS01EPZ1 (75mm) x 1, PH1 (75mm) x 1



EY9EBS02EPZ2 (75mm) x 1, PH2 (75mm) x 1



EY9EBS03E

SL4.0 (0.8/75mm) x 1, SL6.0 (1.2/75mm) x 1


Panasonic[®]

Panasonic Power Tools

Panasonic UK Maxis 2, Western Road, Bracknell, Berkshire RG12 1RT United Kingdom

Produced in Japan 10/2022 © 2022 Panasonic Industry Europe GmbH

www.panasonic-powertools.eu



Panasonic Industry Europe GmbH

The design and specification of products are constantly changing in the interest of improvement. Whilst every care has been taken in preparation of this catalogue, some changes may not have been indicated and may have occurred after publication. Please check with your Panasonic dealer for details. Panasonic Electric Works Europe AG cannot accept responsibility for any errors and omissions.

