



VeriSafe™ Absence of Voltage Tester

VS2-AVT-1PF-08

The VS2-AVT-1PF-08 VeriSafe 2.0 Absence of Voltage Tester is an a permanently mounted voltage tester for use in single-phase AC or DC systems up to 1,000 V. Activating VeriSafe performs an absence of voltage test before opening the panel, helping to prevent possible exposure to electrical hazards. This SKU includes a single-phase VeriSafe 2.0 AVT tester equipped with a 8' (2.4m) system cable, 10' (3m) sensor leads and a single-phase battery-free indicator module.

Specifications

Sub Brand	VeriSafe™
Product Type	Absence of Voltage Tester
Cable Length (ft.)	8
Cable Length (m)	2.4
Maximum Voltage (V)	1000
Maximum Voltage (V ac)	1000
Maximum Voltage (V dc)	1000
Standards Met	UL 1436, UL 508, CSA-C22.2 No. 14, CAN/CSA-C22 No.160, CAN/CSA-C22.2 No.107.1, IEC/UL/CSA C22.2 No. 61010-1, IEC/UL.CSA C22.2 No 61010-2-030, IEC 61508-1, -2 and -3 (SIL Rating)
For Use With	1-Phase AC systems, DC systems
Power Source	12-24 VDC, POE*
Network Compatible	Yes
Maximum Operating Temperature (°C)	60
Maximum Operating Temperature (°F)	140
Minimum Operating Temperature (°C)	-25
Minimum Operating Temperature (°F)	-13
Maximum Storage Temperature (°C)	85
Maximum Storage Temperature (°F)	185
Minimum Storage Temperature (°C)	-45
Minimum Storage Temperature (°F)	-49

Packaging Detail

UPC	61305683259
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.6171
Std. Ctn. Qty.	6
Std. Ctn. Volume (cf)	3.7029