

PRODUCT-DETAILS

## Sentry SSR10P Sentry SSR10P Safety relay



Extended Product Type	Sentry SSR10P
Product ID	2TLA010050R0001
EAN	7350024486254
Catalog Description	Sentry SSR10P Safety relay
	Sentry SSR10P Safety relay with relay outputs 3NO+1NC, +24 VDC supply voltage and push-in spring terminals
	For monitoring of safety devices with contacts, 1 or 2 equivalent channels , and safety devices with OSSD outputs.
	Manual or automatic reset selectable by switch on front.
	Sentry safety relays cover various types of safety applications up to PLe / SIL3. Basic models provide reliable supervision of simpler safety functions, while universal models provide advanced features and high flexibility
Long Description	Models with display offer preset configurations and extensive information to further simplify troubleshooting
	Additional variants offer a high accuracy timer function of ± 1% and an adjustable time setting range from 0-999 s.
	High output current capacity of up to 6 A can save the use of an intermediary
	contactor. Multi-reset allows up to 10 safety relays connected to one reset light button.
	All models are available with detachable push-in or screw terminals. Terminals and coding kit to mark removed terminals are available as accessories

Ordering	
EAN	7350024486254

Subject to change without notice

© 2023 ABB. All rights reserved.

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads	
Data Sheet, Technical Information	2TLC010037L0201
Instructions and Manuals	2TLC010063M0201
CAD Dimensional Drawing	2CDC001079B0201
Dimension Diagram	2TLC010001U0201
Wiring Diagram	2TLC010007T0001
Marketing Video	2TLC010019N0201 2TLC010018N0201

Dimensions	
Product Net Width	22.5 mm
Product Net Height	120 mm
Product Net Depth / Length	120 mm
Product Net Weight	0.207 kg

Technical		
Function	Safety relay for monitoring of safety devices	
Sub-Function	Start/test input, Manual/Auto reset selectable by switch	
Timer Relay Type	No Time Delay	
Rated Control Supply Voltage (U <sub>s</sub> )	24 V DC	
Degree of Protection	IP20	
Connecting Capacity	Crimped Pin 1x0.22.5 mm Crimped Pin 2x0.251.5 mm Flexible with Ferrule 1x0.22.5 mm Flexible with Ferrule 2x0.251.5 mm Solid 1x0.22.5 mm Solid 2x0.251.5 mm	
Wire Stripping Length	6.5 mm	
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715	
Standards	ISO 13849	

Connecting Capacity	Crimped Pin 1x 24-14 AWG
UL/CSA	Flexible with Ferrule 1x 24-14 AWG
	Solid 1x 24-14 AWG

Ambient Air	Operation -25 +65 °C
Temperature	Storage -40 +70 °C
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations	
CQC Certificate	CQC2017010303977544
cUL Certificate	2TLC010006D0201
Declaration of Conformity - CCC	2020980303000244
Declaration of Conformity - CE	2TLC010010D0201
Declaration of Conformity - UKCA	2TLC010190D0201
TÜV Certificate	2TLC010008D0201

## **Container Information**

Package Level 1 Units	box 1 piece
Package Level 1 Width	125 mm
Package Level 1 Depth / Length	31 mm
Package Level 1 Height	129 mm
Package Level 1 Gross Weight	0.268 kg
Package Level 1 EAN	7350024486254
Package Level 2 Units	36 piece
Package Level 2 Width	280 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Height	210 mm
Package Level 2 Gross Weight	9.9 kg

Classifications	
Object Classification Code	к
ETIM 7	EC001449 - Device for monitoring of safety-related circuits
ETIM 8	EC001449 - Device for monitoring of safety-related circuits
ETIM 9	EC001449 - Device for monitoring of safety-related circuits
eClass	V11.0 : 27371819
UNSPSC	39122331
E-Number (Finland)	2712897
E-Number (Sweden)	3861403

Accessories				
Identifier	Description Sentry S30A Terminal block	Type Quantity		Unit Of Measure
2TLA010099R0000		Sentry S30A	1	piece
2TLA010099R0100	Sentry S30B Coding kit	Sentry S30B	1	piece
2TLA010099R0001	Sentry S30C Terminal block	Sentry S30C	1	piece

## Categories

© 2023 ABB. All rights reserved.

Low Voltage Products and Systems  $\rightarrow$  Control Products  $\rightarrow$  Electronic Relays and Controls  $\rightarrow$  Safety Relays  $\rightarrow$  Single Function Safety Relays

 $\mathsf{Low}\ \mathsf{Voltage}\ \mathsf{Products}\ \mathsf{and}\ \mathsf{Systems}\ \to\ \mathsf{Control}\ \mathsf{Products}\ \to\ \mathsf{Safety}\ \mathsf{Relays}\ \to\ \mathsf{Single}\ \mathsf{Function}\ \mathsf{Safety}\ \mathsf{Relays}\ \to\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Relays}\ \to\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Relays}\ \to\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Relays}\ \to\ \mathsf{Safety}\ \mathsf{Saf$ 

