

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes Date: 15-Sep-2021

Revision date 01-Aug-2022 Revision Number 3.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK BUILD SILICONE SEALANT WHITE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

Ireland NPIC - National Poison Information Centre

Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)

Healthcare Professionals: +353 (01) 8092566 (24 hour service)

Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Chronic aquatic toxicity Category 3 - (H412)

2.2. Label elements

Signal word

None

Hazard statements

H412 - Harmful to aquatic life with long lasting effects.

EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane & 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

United Kingdom - BE Page 1 / 17

Revision date 01-Aug-2022 Revision Number 3.01

EVO-STIK BUILD SILICONE SEALANT WHITE

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

Supercedes Date: 15-Sep-2021

P273 - Avoid release to the environment

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	932-078-5	RR-100254-6	10 - <20	Asp. Tox. 1 (H304)	-	01-2119552497- 29-xxxx
Silica, amorphous	231-545-4	7631-86-9	5 - <10	[B]	-	01-2119379499- 16-XXXX
Trimethoxyvinylsilane	220-449-8	2768-02-7	1 - <3	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	01-2119513215- 52-XXXX
Titanium dioxide	236-675-5	13463-67-7	0.1 - <1	[C]	-	01-2119489379- 17-XXXX
Methyl alcohol	200-659-6	67-56-1	0.1 - <1	(H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	28-XXXX
Dioctyltin oxide	212-791-1	870-08-6	0.1 - <1	STOT SE 2 (H371)	-	01-2119971268- 27-xxxx
Octamethylcyclotetrasilo xane [D4]	209-136-7	556-67-2	0.01 - <0.1	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	01-2119529238- 36-XXXX

United Kingdom - BE Page 2 / 17

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes Date: 15-Sep-2021

Revision date 01-Aug-2022

Revision Number 3.01

2-octyl-2H-isothiazol-3-o ne [OIT]	247-761-7	26530-20-1	0.0015 - <0.01	Acute Tox. 3 (H301)	Skin Sens. 1A :: C>=0.0015%	-
				Acute Tox. 3		
				(H311) Acute Tox. 2		
				(H330) Skin Corr. 1B		
				(H314)		
				Eye Dam 1 (H318)		
				Skin Sens. 1A (H317)		
				Aquatic Acute 1		
				(H400) Aquatic Chronic 1		
				(H410)		

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact In the case of skin irritation or allergic reactions see a doctor. Wash skin with soap and

water.

Ingestion Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with

water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when

the product is exposed to moisture or water. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

United Kingdom - BE Page 3 / 17

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes Date: 15-Sep-2021 Revision Number 3.01

5.2. Special hazards arising from the substance or mixture

chemical

Specific hazards arising from the Thermal decomposition can lead to release of irritating gases and vapours.

Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Silicon **Hazardous combustion products**

dioxide. Thermal decomposition can lead to release of irritating and toxic gases and

Revision date 01-Aug-2022

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as

required. Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section **Environmental precautions**

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Take up mechanically, placing in appropriate containers for disposal. Methods for cleaning up

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure adequate ventilation. Advice on safe handling

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feedingstuffs.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

United Kingdom - BE Page 4/17

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes Date: 15-Sep-2021

Revision date 01-Aug-2022 Revision Number 3.01

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Silica, amorphous	TWA: 0.1 mg/m ³	TWA: 6 mg/m ³
7631-86-9		TWA: 2.4 mg/m ³
		TWA: 0.1 mg/m ³
		STEL: 18 mg/m ³
		STEL: 7.2 mg/m ³
		STEL: 0.3 mg/m ³
Titanium dioxide	-	TWA: 10 mg/m ³
13463-67-7		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm
67-56-1	TWA: 260 mg/m ³	TWA: 266 mg/m ³
	*	STEL: 250 ppm
		STEL: 333 mg/m ³
		Sk*
Dioctyltin oxide	-	TWA: 0.1 mg/m ³
870-08-6		STEL: 0.2 mg/m ³
		Sk*

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol	-	15 mg/L (urine - Methanol end of	-
67-56-1		shift)	

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
Trimethoxyvinylsilane (2768	3-02-7)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Systemic health effects Long term	Inhalation	27,6 mg/m³		
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d		

Titanium dioxide (13463-67-7)				
Туре	Exposure route	Derived No Effect Level	Safety factor	
		(DNEL)		
worker	Inhalation	10 mg/m³		
Long term				
Local health effects				

Methyl alcohol (67-56-1)				
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Short term Systemic health effects worker	Dermal	40 mg/kg bw/d		

United Kingdom - BE Page 5 / 17

EVO-STIK BUILD SILICONE SEALANT WHITE Supercedes Date: 15-Sep-2021

Revision date 01-Aug-2022 **Revision Number** 3.01

Short term Systemic health effects worker	Inhalation	260 mg/m³	
Short term Local health effects worker	Inhalation	260 mg/m³	
Long term Systemic health effects worker	Dermal	40 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	260 mg/m³	
Long term Local health effects worker	Inhalation	260 mg/m³	
Dioctyltin oxide (870-08-6)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	0.004 mg/m³	

Octamethylcyclotetrasiloxane [D4] (556-67-2)				
Туре		Derived No Effect Level (DNEL)	Safety factor	
worker	Inhalation	73 mg/m³		
Long term				
Systemic health effects				

Derived No Effect Level (DNEL)					
Trimethoxyvinylsilane (2768-02-7)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m³			
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d			
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d			

Titanium dioxide (13463-67-7)			
Туре			Safety factor
		(DNEL)	
Consumer	Oral	700 mg/kg bw/d	
Long term			
Systemic health effects			

Methyl alcohol (67-56-1)					
Туре	1	Derived No Effect Level (DNEL)	Safety factor		
Consumer Short term	Dermal	8 mg/kg bw/d			

United Kingdom - BE Page 6/17

EVO-STIK BUILD SILICONE SEALANT WHITE

Revision date 01-Aug-2022 **Revision Number** 3.01 Supercedes Date: 15-Sep-2021

			
Systemic health effects			
Consumer	Oral	8 mg/kg bw/d	
Short term			
Systemic health effects			
Consumer	Inhalation	50 mg/m ³	
Long term			
Local health effects			
Consumer	Oral	8 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Inhalation	50 mg/m ³	
Long term			
Systemic health effects			
Consumer	Dermal	50 mg/kg bw/d	
Long term			
Systemic health effects			

Dioctyltin oxide (870-08-6)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer	Oral	0.0005 mg/kg bw/d		
Long term				
Systemic health effects				
Consumer	Dermal	0.025 mg/kg bw/d		
Long term				
Systemic health effects				
Consumer	Inhalation	0.0009 mg/m ³		
Long term		_		
Systemic health effects				

Octamethylcyclotetrasiloxane [D4] (556-67-2)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Systemic health effects	Inhalation	13 mg/m³		
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d		

Predicted No Effect Concentration No information available. (PNEC)

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

United Kingdom - BE Page 7/17

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes Date: 15-Sep-2021

Dioctyltin oxide (870-08-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight
Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	0.0015 mg/l		
Marine water	0.00015 mg/l		
Freshwater sediment	3 mg/kg		
Marine sediment	0.3 mg/kg		
Soil	0.54 mg/kg		
Sewage treatment plant	10 mg/l		

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Ensure that the breakthrough time of the glove material is not

exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness

None known

None known

Revision date 01-Aug-2022

Revision Number 3.01

as well as the temperature. Gloves must conform to standard EN 374

Skin and body protection None under normal use conditions.

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid **Appearance** Paste White Colour

Odour Characteristic.

Odour threshold No information available

Property Values Remarks • Method No data available

Melting point / freezing point No data available °C Initial boiling point and boiling

range

Flammability Not applicable for liquids .

Flammability Limit in Air None known

Upper flammability or explosive No data available

limits Lower flammability or explosive No data available

limits

Flash point > 60 °C

Decomposition temperature

Autoignition temperature No data available °C

No data available pН

Not applicable. Insoluble in water. None known

No data available pH (as aqueous solution) Kinematic viscosity > 21 mm²/s

No data available Dynamic viscosity Water solubility Immiscible in water.

Solubility(ies) No data available None known

United Kingdom - BE Page 8 / 17

EVO-STIK BUILD SILICONE SEALANT WHITE

Revision date 01-Aug-2022

Revision Number 3.01

_

Partition coefficientNo data availableNone knownVapour pressureNo data availableNone known

Relative density 1.00

Supercedes Date: 15-Sep-2021

Bulk Density
No data available
Liquid Density
No data available

Relative vapour density No data available None known

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze.

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

products curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

United Kingdom - BE Page 9 / 17

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes Date: 15-Sep-2021

Revision date 01-Aug-2022

Revision Number 3.01

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met. May cause sensitisation in

susceptible persons.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 37,769.20 mg/kg ATEmix (inhalation-vapour) 194.00 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C13-C23,	LD50 > 5000 mg/kg (Rattus)	LD50 > 2000 mg/kg	-
n-alkanes, isoalkanes, cyclics,	OECD 401	(Oryctolagus cuniculus)	
< 0.03% aromatics		OECD 402	
Silica, amorphous	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus cuniculus)	>2.2 mg/L (Rattus) 1 h
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
Methyl alcohol	=2500 mg/kg (Rattus)	200-1000 mg/kg (Oryctolagus cuniculus)	=22500 ppm (Rattus) 8 h = 64000 ppm (Rattus) 4 h
Dioctyltin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-
Octamethylcyclotetrasiloxane	LD50 > 4800 mg/kg (Rattus)	LD50 > 2400 mg/kg (Rattus)	=36 g/m³ (Rattus) 4 h
[D4]	OECD 401	OECD 402	
2-octyl-2H-isothiazol-3-one	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus	-
[OIT]		cuniculus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

United Kingdom - BE Page 10 / 17

Revision date 01-Aug-2022

Revision Number 3.01

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes Date: 15-Sep-2021

Exposure route

Dermal

Results

were observed

No sensitisation responses

Species 4 1

Guinea pig

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Corrosive
Acute Dermal					
Irritation/Corrosion					
Serious eye damage/e	ye irritation	Based on available data, th	e classification crite	eria are not met.	
Trimethoxyvinylsilane (2	2768-02-7)				
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye		24 hours	Non-irritant
Acute Eye		-			
Irritation/Corrosion					
	•	•	•	•	•
Titanium dioxide (13463	3-67-7)				
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	Eye			Non-irritant
OLOD TOST NO. 400.					
Acute Eye					

Trimetho	wwinyleila	na (2768-C	12-71

OECD Test No. 406: Skin

Method

Sensitisation

Third and the first of the firs					
Method	Species	Exposure route	Results		
OECD Test No. 406: Skin	Guinea pig	Dermal	sensitising		
Sensitisation, Buehler test					

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	Not a skin sensitiser
Sensitisation	-		
OECD Test No. 429: Skin	Mouse	Dermal	Not a skin sensitiser
Sensitisation: Local Lymph Node			
Assay			

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin	Mouse		sensitising
Sensitisation: Local Lymph Node			
Assay			

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse	in vitro	Not mutagenic
Mutation Test		-

Carcinogenicity

Based on available data, the classification criteria are not met.

United Kingdom - BE Page 11 / 17

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes Date: 15-Sep-2021

Revision date 01-Aug-2022 Revision Number 3.01

Reproductive toxicity

Based on available data, the classification criteria are not met.

Chemical name	European Union		
Octamethylcyclotetrasiloxane [D4]	Repr. 2		

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose	Rat	Not Classifiable
Toxicity Study with the		
Reproduction/Developmental Toxicity Screening		
Test		

STOT - single exposure

Based on available data, the classification criteria are not met.

Dioctyltin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422:	Rat	Oral	5 mg/kg	28 days	0.3 - 0.5 mg/kg
Combined Repeated Dose					bw/d May cause
Toxicity Study with the					damage to the
Reproduction/Developme					following organs:
ntal Toxicity Screening					Immune system
Test					·

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapour		90 days	0.058 NOAEL
Sub-chronic Inhalation					
Toxicity: 90-day Study					

Dioctyltin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 days	0.3 -0.5 mg/kg bw/d

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Harmful to aquatic life with long lasting effects.

	Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Г	Hydrocarbons,	EL50 (72h) > 10	LL50 (96h) >	-	LL50 (48h) > >		, , ,

United Kingdom - BE Page 12 / 17

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes Date: 15-Sep-2021

Revision date 01-Aug-2022

Revision Number 3.01

C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100254-6	000 mg/L (Skeletonema costatum)	1028 mg/L (Scophthalmus maximus)		3193 mg/l (Acartia tonsa)		
Silica, amorphous 7631-86-9	EC50: =440mg/L (72h, Pseudokirchneri ella subcapitata)	=5000mg/L (96h, Brachydanio	-	EC50: =7600mg/L (48h, Ceriodaphnia dubia)		
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Methyl alcohol 67-56-1	-	LC50 96 h > 100 mg/L (Pimephales promelas static)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	-		
Dioctyltin oxide 870-08-6	EC50 (3hr) >1.000 mg/l (bacteria) (Activated Sludge, Respiration Inhibition Test)	LC50 (96hr) >0,09 mg/l (Brachydanio rerio (zebra)) (Acute Toxicity Test)	-	EC50 (48Hr) >0,21 mg/l (Daphnia magna (Dappnia magna)) (Daphnia sp. Acute Immobilisation Test)		
Octamethylcyclotetrasil oxane [D4] 556-67-2		LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	_	EC50: =25.2mg/L (24h, Daphnia magna)		10
2-octyl-2H-isothiazol-3- one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

Silica, amorphous (7631-86-9)

Method	Exposure time	Value	Results
			The methods for determining
			biodegradability are not
			applicable to inorganic
			substances

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily

United Kingdom - BE Page 13/17

Revision date 01-Aug-2022

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes Date: 15-Sep-2021 Revision Number 3.01

Biodegradability: Manometric		biodegradable
Respirometry Test (TG 301 F)		-

Dioctyltin oxide (870-08-6)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	755 hours	biodegradation	Not readily biodegradable 2
Biodegradability: Manometric			%
Respirometry Test (TG 301 F)			

Octamethylcyclotetrasiloxane [D4] (556-67-2) 2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Exposure time	Value	Results
OECD Test No. 309: Aerobic		Half-life 0.6-1.4 d	Readily biodegradable
Mineralization in Surface Water -			
Simulation Biodegradation Test			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	cal name Partition coefficient	
Trimethoxyvinylsilane	1.1	
Methyl alcohol	-0.77	
Dioctyltin oxide	6	
Octamethylcyclotetrasiloxane [D4]	6.49	
2-octyl-2H-isothiazol-3-one [OIT]	2.92	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment	
Silica, amorphous	The substance is not PBT / vPvB PBT assessment does	
	not apply	
Trimethoxyvinylsilane	The substance is not PBT / vPvB	
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does	
	not apply	
Methyl alcohol	The substance is not PBT / vPvB PBT assessment does	
	not apply Further information relevant for the PBT	
	assessment is necessary	
Dioctyltin oxide	The substance is not PBT / vPvB	
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB	
2-octyl-2H-isothiazol-3-one [OIT]	The substance is not PBT / vPvB	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance	Negative.	
with the criteria set out in Commission		
Delegated Regulation (EU) 2017/2100(3) or		

United Kingdom - BE Page 14 / 17

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes Date: 15-Sep-2021

Commission Regulation (EU) 2018/605(4).

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

Revision date 01-Aug-2022

Revision Number 3.01

international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1UN number or ID numberNot regulated14.2Proper Shipping NameNot regulated14.3Transport hazard class(es)Not regulated14.4Packing groupNot regulated14.5Environmental hazardsNot applicable

14.6 Special Provisions None

IMDG

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated

14.5 Marine pollutant NP14.6 Special Provisions None

14.7 Maritime transport in bulk

according to IMO instruments

Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

United Kingdom - BE Page 15/17

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes Date: 15-Sep-2021

Revision date 01-Aug-2022 Revision Number 3.01

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Methyl alcohol	67-56-1	69.
·		75.
Dioctyltin oxide	870-08-6	20.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 689/2008 - Annex Number
Dioctyltin oxide	l.1

Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Methyl alcohol - 67-56-1	500	5000

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour

H226 - Flammable liquid and vapour

H301 - Toxic if swallowed

United Kingdom - BE Page 16 / 17

EVO-STIK BUILD SILICONE SEALANT WHITE

Revision date 01-Aug-2022

Revision Number 3.01

....

H304 - May be fatal if swallowed and enters airways

H311 - Toxic in contact with skin

Supercedes Date: 15-Sep-2021

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled H331 - Toxic if inhaled

H332 - Harmful if inhaled

H361f - Suspected of damaging fertility H370 - Causes damage to organs H371 - May cause damage to organs H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 01-Aug-2022

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 17 / 17