

PRODUCT DATASHEET SPC.T CL 15 W 230 V E14

SPECIAL OVEN T | Incandescent lamps, tubular shape, for oven lighting



Areas of application

- Baking ovens
- Domestic baking ovens




TECHNICAL DATA

Electrical data

Nominal wattage	15 W
Construction wattage	15.00 W
Nominal voltage	230 V
Nominal current	65 mA

Photometrical data

Luminous flux	60 lm
Luminous efficacy	4 lm/W
Color temperature	2700 K
Color rendering index Ra	100
Light color	1027



Light technical data

Starting time	0 s
---------------	-----

Dimensions & Weight

Overall length	54.00 mm
Length with base excl. base pins/connection	55,00 mm
Diameter	17,0 mm
Product weight	5.9 g

Lifespan

Lifespan L70/B50 at 25 °C	1000 h

Additional product data

Base (standard designation)	E14
-----------------------------	-----

Energy efficiency class Energy consumption Country-specific categorizations ILCOS Order reference Semergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	Yes G 15.00 kWh/1000h IBT/C-15-230-E14-17 SPECIAL. CL 15W OTHER NDLS MLS
Energy efficiency class Energy consumption Country-specific categorizations ILCOS Order reference Semergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	G 15.00 kWh/1000h BBT/C-15-230-E14-17 SPECIAL. CL 15W OTHER NDLS
Energy efficiency class Energy consumption 1 Country-specific categorizations ILCOS Order reference Senergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Energy efficiency class Order Energy consumption 1 Autority-specific categorizations IICOS III Order reference Senergy labelling regulation data acc EU 2019/2015 Lighting technology used Connected light source (CLS)	15.00 kWh/1000h IBT/C-15-230-E14-17 SPECIAL. CL 15W OTHER NDLS
Energy consumption Country-specific categorizations ILCOS II Order reference Senergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	15.00 kWh/1000h IBT/C-15-230-E14-17 SPECIAL. CL 15W OTHER NDLS
ILCOS Order reference Somergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	IBT/C-15-230-E14-17 SPECIAL. CL 15W OTHER NDLS
ILCOS Order reference Somergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	OTHER NDLS
Order reference nergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	OTHER NDLS
nergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	OTHER NDLS
Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	NDLS
Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	NDLS
Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	
Light source cap-type (or other electric interface) Connected light source (CLS)	MLS
Connected light source (CLS)	
	E14
	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length 5	54.00 mm
Height 1	17,0 mm
Width 1	17,0 mm
Chromaticity coordinate x	0.497
Chromaticity coordinate y	0.417
Beam angle correspondence	SPHERE_360
EPREL ID 7	714465

October 31, 2023, 09:42:43 SPC.T CL 15 W 230 V E14

Spectral power distribution

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300066639	Folding box 1	62 mm x 19 mm x 19 mm	7.00 g	0.02 dm³
4050300092928	Blister 1	140 mm x 22 mm x 120 mm	32.40 g	0.37 dm³
4050300098500	Shipping box 50	204 mm x 78 mm x 110 mm	476.00 g	1.75 dm³
4050300093680	Shipping box 10	148 mm x 156 mm x 130 mm	264.00 g	3.00 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.