



Trueforce CorePro LED HPL

TForce Core LED HPL 26W E27 830 FR

Philips TrueForce Core LED HPL lamps are an easy, LED solution with a short pay-back to replace High-Intensity Discharge (HID) lamps. This new generation of LED Core post-top lamps brings all the energy-efficiency and long-lifetime benefits of LED-to-HID replacement, while delivering instant saving for a low initial investment. Furthermore, TrueForce CorePro LED HPL lamps are designed to have the same lamp size and light distribution as their HID alternatives. And thanks to our high-power LED filament technology, you'll never know the difference. Plus, their unique IP65 design means that TrueForce Core LED HPL Post-Top lamps can be used for outdoor, as well as indoor applications.

Warnings and Safety

- Installation must always be performed by a qualified electrician or installer. Use the installation guide for instructions.


Product data

General Information			
Cap base	E27 [E27]	Colour designation	White (WH)
Nominal lifetime	25,000 h	Correlated Colour Temperature	3000 K
Switching Cycle	15,000	Luminous efficacy (rated) (nom.)	153 lm/W
Lighting Technology	LED	Colour consistency	<6
Flux measurement reference	Sphere	Colour rendering index (CRI)	80
CE mark	Yes	LLMF at end of nominal lifetime (nom.)	0.7 %
EU RoHS compliant	Yes	Flickering value (PstLM)	1
		Stroboscopic effect	1.6
		Photobiological safety according to EN 62471	RG1
Light Technical		Operating and Electrical	
Colour Code	830 [CCT of 3000K]	Line Frequency	50 to 60 Hz
Beam angle (nom.)	300 degree(s)	Input frequency	50 to 60 Hz
Luminous Flux	4,000 lm		

Trueforce CorePro LED HPL

Power Consumption	26 W
Lamp current (nom.)	145 mA
Starting time (nom.)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (nom.)	220-240 V
Inrush current at mains	29
Max. lamp no. on MCB B type 10A — Mains	6
Max. lamp no. on MCB B type 10A — EM ballast without Comp. Cap.	-
Max. lamp no. on MCB B type 10A — EM ballast with Comp. Cap.	-
Max. lamp no. on MCB B type 16A — Mains	9
Max. lamp no. on MCB B type 16A — EM ballast without Comp. Cap.	-
Max. lamp no. on MCB B type 16A — EM ballast with Comp. Cap.	-
Temperature	
Ambient temperature range	-30 to +45 °C
T-Case maximum (nom.)	54 °C
Controls and Dimming	
Dimmable	No

Dimensional drawing





Mechanical and Housing	
Lamp Finish	Frosted
Bulb shape	ED90 [ED 90 mm]
Approval and Application	
Energy Efficiency Class	D
Energy consumption kWh/1,000 hours	26 kWh
EPREL registration number	403622
Product Data	
Order product name	TForce Core LED HPL 26W E27 830 FR
Full product name	TForce Core LED HPL 26W E27 830 FR
Full EOC	871869975033600
Order code	75033600
Material no. (12 NC)	929002350102
SAP numerator – quantity per pack	1
EAN/UPC — Product/Case	8718699750336
Numerator – packs per outer box	6
EAN/UPC - Case	8718699750343

Product	D	C
TForce Core LED HPL 26W E27 830 FR	90 mm	245 mm


Trueforce CorePro LED HPL

Photometric data



General uniform lighting - TForce Core LED HPL 26W E27 830 FR

Light Distribution Diagram - TForce Core LED HPL 26W E27 830 FR




Spectral Power Distribution Colour - TForce Core LED HPL 26W E27 830 FR

Lifetime



Life Expectancy Diagram - TForce Core LED HPL 26W E27 830 FR



Lumen Maintenance Diagram - TForce Core LED HPL 26W E27 830 FR

Trueforce CorePro LED HPL

