





Color: ■ light gray



PFC200 Communication Options Overview

Option	Module	Protocol	Max. Length	Max. Speed	Max. Nodes	Max. I/Os	Max. Power	Max. Temp.	Max. Humidity
1	WAGO PFC200-1000-0000	Modbus TCP	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
2	WAGO PFC200-1000-0001	Modbus RTU	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
3	WAGO PFC200-1000-0002	Modbus ASCII	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
4	WAGO PFC200-1000-0003	Modbus CAN	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
5	WAGO PFC200-1000-0004	Modbus CANopen	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
6	WAGO PFC200-1000-0005	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
7	WAGO PFC200-1000-0006	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
8	WAGO PFC200-1000-0007	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
9	WAGO PFC200-1000-0008	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
10	WAGO PFC200-1000-0009	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
11	WAGO PFC200-1000-0010	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
12	WAGO PFC200-1000-0011	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
13	WAGO PFC200-1000-0012	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
14	WAGO PFC200-1000-0013	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
15	WAGO PFC200-1000-0014	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
16	WAGO PFC200-1000-0015	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
17	WAGO PFC200-1000-0016	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
18	WAGO PFC200-1000-0017	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
19	WAGO PFC200-1000-0018	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
20	WAGO PFC200-1000-0019	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
21	WAGO PFC200-1000-0020	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
22	WAGO PFC200-1000-0021	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
23	WAGO PFC200-1000-0022	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
24	WAGO PFC200-1000-0023	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
25	WAGO PFC200-1000-0024	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
26	WAGO PFC200-1000-0025	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
27	WAGO PFC200-1000-0026	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
28	WAGO PFC200-1000-0027	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
29	WAGO PFC200-1000-0028	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
30	WAGO PFC200-1000-0029	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
31	WAGO PFC200-1000-0030	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
32	WAGO PFC200-1000-0031	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
33	WAGO PFC200-1000-0032	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
34	WAGO PFC200-1000-0033	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
35	WAGO PFC200-1000-0034	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
36	WAGO PFC200-1000-0035	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
37	WAGO PFC200-1000-0036	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
38	WAGO PFC200-1000-0037	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
39	WAGO PFC200-1000-0038	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
40	WAGO PFC200-1000-0039	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
41	WAGO PFC200-1000-0040	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
42	WAGO PFC200-1000-0041	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
43	WAGO PFC200-1000-0042	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
44	WAGO PFC200-1000-0043	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
45	WAGO PFC200-1000-0044	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
46	WAGO PFC200-1000-0045	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
47	WAGO PFC200-1000-0046	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
48	WAGO PFC200-1000-0047	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
49	WAGO PFC200-1000-0048	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
50	WAGO PFC200-1000-0049	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
51	WAGO PFC200-1000-0050	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
52	WAGO PFC200-1000-0051	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
53	WAGO PFC200-1000-0052	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
54	WAGO PFC200-1000-0053	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
55	WAGO PFC200-1000-0054	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
56	WAGO PFC200-1000-0055	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
57	WAGO PFC200-1000-0056	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
58	WAGO PFC200-1000-0057	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
59	WAGO PFC200-1000-0058	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
60	WAGO PFC200-1000-0059	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
61	WAGO PFC200-1000-0060	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
62	WAGO PFC200-1000-0061	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
63	WAGO PFC200-1000-0062	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
64	WAGO PFC200-1000-0063	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
65	WAGO PFC200-1000-0064	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
66	WAGO PFC200-1000-0065	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
67	WAGO PFC200-1000-0066	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
68	WAGO PFC200-1000-0067	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
69	WAGO PFC200-1000-0068	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
70	WAGO PFC200-1000-0069	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
71	WAGO PFC200-1000-0070	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
72	WAGO PFC200-1000-0071	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
73	WAGO PFC200-1000-0072	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
74	WAGO PFC200-1000-0073	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
75	WAGO PFC200-1000-0074	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
76	WAGO PFC200-1000-0075	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
77	WAGO PFC200-1000-0076	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
78	WAGO PFC200-1000-0077	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
79	WAGO PFC200-1000-0078	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
80	WAGO PFC200-1000-0079	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
81	WAGO PFC200-1000-0080	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
82	WAGO PFC200-1000-0081	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
83	WAGO PFC200-1000-0082	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
84	WAGO PFC200-1000-0083	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
85	WAGO PFC200-1000-0084	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
86	WAGO PFC200-1000-0085	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
87	WAGO PFC200-1000-0086	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
88	WAGO PFC200-1000-0087	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
89	WAGO PFC200-1000-0088	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
90	WAGO PFC200-1000-0089	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
91	WAGO PFC200-1000-0090	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
92	WAGO PFC200-1000-0091	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
93	WAGO PFC200-1000-0092	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
94	WAGO PFC200-1000-0093	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
95	WAGO PFC200-1000-0094	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
96	WAGO PFC200-1000-0095	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
97	WAGO PFC200-1000-0096	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
98	WAGO PFC200-1000-0097	Modbus RS-422	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
99	WAGO PFC200-1000-0098	Modbus RS-485	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %
100	WAGO PFC200-1000-0099	Modbus RS-232	1000 m	1000 baud	1000	1000	1000 W	1000 °C	1000 %



The PFC200 Controller is a compact PLC for the modular WAGO I/O System. Besides network and fieldbus interfaces, the controller supports all digital, analog and specialty modules found within the 750/753 Series.

Two ETHERNET interfaces and an integrated switch enable line topology wiring.

An integrated Webserver provides user configuration options, while displaying PFC200 status information.

Besides the processing industry and building automation, typical applications for the PFC200 include standard machinery and equipment control (e.g., packaging, bottling and manufacturing systems, as well as textile, metal and wood processing machines).

Programming per IEC 61131-3

- Programmable with CODESYS V3.5 from Firmware Release 23, WAGO-I/O-PRO V2.3 or **e!COCKPIT** up to Firmware Release 22
- Direct connection of WAGO's I/O modules
- 2 x ETHERNET (configurable), RS-232/-485, CAN, CANopen
- Linux operating system with RT-Preempt patch
- Configuration via CODESYS, **e!COCKPIT** or Web-Based Management user interface
- Maintenance-free

||
||
||

Technical data

ETHERNET protocols	DHCP DNS NTP FTP FTPS SNMP HTTP HTTPS SSH
Telecontrol protocols	IEC 60870 (additional license as slave or master) IEC 61850 (additional license as Client or Server) DNP3 (additional license as Slave or Master)
Visualization	Web-Visu
Operating system	Real-time Linux (with RT-Preempt patch)
CPU	Cortex A8; 1 GHz
Programming languages per IEC 61131-3	Instruction List (IL) Ladder Diagram (LD) Function Block Diagram (FBD) Continuous Function Chart (CFC) Structured Text (ST) Sequential Function Chart (SFC)
Programming environment	CODESYS V3.5, Firmware Release 23 or higher e! COCKPIT (based on CODESYS V3) up to Firmware Release 22 WAGO-I/O-PRO V2.3 (based on CODESYS V2.3), up to Firmware Release 22
Configuration options	CODESYS V3 e! COCKPIT WAGO-I/O-CHECK Web-Based Management e! RUNTIME library CODESYS Library
Baud rate (communication/fieldbus 1)	10/100 Mbit/s
Baud rate	ETHERNET: 10/100 Mbit/s
Transmission medium (communication/fieldbus)	ETHERNET: Twisted pair S-UTP; 100 Ω; Cat. 5; 100 m maximum cable length
Main memory (RAM)	512 MB
Internal memory (flash)	4096 MB
Non-volatile hardware memory	128 KB
Program memory	CODESYS V2: 16 MB; CODESYS V3: 32 MB
Data memory	CODESYS V2: 64 MB; CODESYS V3: 128 MB
Non-volatile software memory	128 KB 128 KB
Type of memory card	SD and SDHC up to 32 GB (all guaranteed properties only valid with the WAGO 758-879/000-001 Memory Card)
Memory card slot	Push-push mechanism; cover lid (sealable)
Number of modules per node (max.)	250
Number of modules without a bus extension (max.)	64
Input and output process image (internal) max.	1000 words/1000 words
Input and output process image (Modbus®) max.	CODESYS V2: 1000 words/1000 words; CODESYS V3: 32000 words/32000 words
Input and output process image (CAN) max.	2000 words/2000 words
Indicators	LED (SYS, RUN, I/O, CAN, U1 ... U6) red/green/orange: Status system, program, internal data bus, CANopen, status programmable by user (can be used via CODESYS library); LED (A, B) green: Status system power supply, field supply
Supply voltage (system)	24 VDC (-25 ... +30 %); via pluggable connector (CAGE CLAMP® connection)
Input current (typ.) at nominal load (24 V)	550 mA
Total current (system supply)	1700 mA
Supply voltage (field)	24 VDC (-25 ... +30 %); via power jumper contacts
Current carrying capacity (power jumper contacts)	10 A
Number of outgoing power jumper contacts	3
Isolation	500 V system/field



Connection data	
Connection technology: communication/fieldbus	CANopen: 1 x D-sub 9 plug; Modbus (TCP, UDP): 2 x RJ-45; Modbus RTU: 1 x D-sub 9 socket; RS-232 serial interface: 1 x D-sub 9 socket; RS-485 interface: 1 x D-sub 9 socket
Connection technology: system supply	2 x CAGE CLAMP®
Connection technology: field supply	6 x CAGE CLAMP®
Connection type 1	System/field supply
Solid conductor	0.08 ... 2.5 mm² / 28 ... 14 AWG
Fine-stranded conductor	0.08 ... 2.5 mm² / 28 ... 14 AWG
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches
Connection technology: device configuration	1 x Male connector; 4-pole

Physical data	
Width	112 mm / 4.409 inches
Height	100 mm / 3.937 inches
Depth	71.9 mm / 2.831 inches
Depth from upper-edge of DIN-rail	64.7 mm / 2.547 inches

Mechanical data	
Weight	256.9 g
Color	light gray
Housing material	Polycarbonate; polyamide 6.6
Conformity marking	CE

Environmental requirements	
Ambient temperature (operation)	0 ... +55 °C
Ambient temperature (storage)	-25 ... +85 °C
Protection type	IP20
Pollution degree	2 per IEC 61131-2
Operating altitude	without temperature derating: 0 ... 2000 m; with temperature derating: 2000 ... 5000 m (0.5 K/100 m); 5000 m (max.)
Relative humidity (without condensation)	95 %
Mounting position	any
Mounting type	DIN-35 rail
Vibration resistance	4g per IEC 60068-2-6
Shock resistance	15g per IEC 60068-2-27
EMC immunity to interference	per EN 61000-6-2, marine applications
EMC emission of interference	per EN 61000-6-3, marine applications
Exposure to pollutants	per IEC 60068-2-42 and IEC 60068-2-43
Fire load	2.911 MJ
Permissible H ₂ S contaminant concentration at a relative humidity 75 %	10 ppm
Permissible SO ₂ contaminant concentration at a relative humidity 75 %	25 ppm

Commercial data	
eCl@ss 10.0	27-24-26-07
eCl@ss 9.0	27-24-26-07
ETIM 8.0	EC000236
ETIM 7.0	EC000236
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143759762
Customs tariff number	85371091990



Approvals for marine applications		
LR	-	LR22180952TA
Lloyds Register EMEA		
RINA	-	ELE343521XG001
RINA Germany GmbH		

Approvals for hazardous areas		
PTB 0102 ERC IECEx		
Approval	Standard	Certificate Name
ATEX TUEV Nord Cert GmbH	EN 60079-0	TUEV14ATEX148929X (II 3 G Ex ec IIC T4 Gc)
CCCEX CQST/CNEx	CNCA-C23-01	2020312310000213 (Ex ec IIC T4 Gc)
EAC Brjansker Zertifizierungsstelle	TP TC 012/2011	EAC RU C-DE.AM02. B.00163/19 (2Ex e IIC T4 Gc X)
IECEx TUEV Nord Cert GmbH	IEC 60079-0	IECEx TUN 14.0035 X (Ex ec IIC T4 Gc)
INMETRO TÜV Rheinland do Brasil Ltda.	IEC 60079-0	TÜV 12.1297 X
UKEx WAGO GmbH & Co. KG	EN 60079-0	UKCA_WA GO22UKEX003X_ec
UL Underwriters Laboratories Inc. (HAZARDOUS LOCATIONS)	UL 121201	E198726 Sec.1

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 750-8214	

Documentation			
Manual		System Description	
Cyber Security for Controller PFC100 / PFC200	V 1.2.0	pdf	
Product Manual PFC200 G2 2ETH RS CAN	1.13.0 / FW 26 27.11.2023	8128.80 KB	
System Manual WAGO I/O System 750/753	V 3.3.3 29.08.2023	pdf	
System Manual Series 750/753		5144.77 KB	
Product Manual OPC UA Mapping Editor	V 1.1.0 11.03.2022	pdf	
OPC-UA Mapping Editor		3314.23 KB	
Product Manual WAGO MODBUS Master Configurator	V 1.1.0	pdf	
Migration Guide	V 1.3.0 03.07.2023	1761.59 KB	
Migrationsleitfaden von e!COCKPIT-Projekten zu CODESYS V3.5		4938.74 KB	

Overview on WAGO-I/O-SYSTEM 750 approvals	pdf	770.48 KB	
Controller PFC100/200, General Product Information	pdf	578.66 KB	

Tutorial			
Establish connection to a controller using SSH	1.0 05.08.2017	mp4 28368.02 KB	↓
Set IP address with Ethernet Settings	3.0 18.12.2017	mp4 86272.82 KB	↓

Additional Information			
WAGO OPC UA Server	V 1.1.0 28.01.2021	pdf 1132.87 KB	↓

Bid Text			
750-8214	19.02.2019	xml 9.63 KB	↓
750-8214	23.01.2019	docx 21.75 KB	↓

Instruction Leaflet			
CCC Ex (Additional information)	26.04.2023	pdf 159.76 KB	↓

Application Notes

Application Note CoDeSys 2.3			
Application note for installing a MySQL-Server on a PFC-Controller	1.0.4 16.05.2019	zip 4392.22 KB	↓
Application note Cloud Connectivity	2019-09-17 17.09.2019	zip 3973.74 KB	↓
HART Tool Routing via ETHERNET with 750-820x/750-88x and CODESYS 2.3 (a116120)	1.0.0 22.03.2019	pdf 3798.36 KB	↓
HART Tool Routing via PROFIBUS with 750-833 and 750-333 (a116140)	1.0.0 22.03.2019	pdf 5214.96 KB	↓
Using the web visualization with Java™ runtime environment (JRE, JVM) 7 update 51 (7u51) (a500690)	1.2.4 26.02.2019	zip 4896.43 KB	↓
Application Note PowerMeasurement_03 Library	19.01.2011 19.03.2012	zip 932.08 KB	↓
Application Note: DMX_02	26.04.2017 26.04.2017	zip 733.43 KB	↓
HVAC System Macros	10.03.2017 15.03.2019	zip 13252.92 KB	↓
Application Note: Mp-Bus_03 Library	2020-08-14 14.08.2020	zip 513.66 KB	↓
Connection of a Thermokon Thanos SR L MODBUS room control unit to the WAGO-I/O-SYSTEM	02.05.2013 13.05.2013	zip 305.89 KB	↓
Anbindung der HKW-Elektronik Wetterprognose-Station WS-K xx T ModBus	1.1 07.07.2017	zip 762.78 KB	↓
Application Note Scheduler_03.lib	20.05.2011 20.05.2011	zip 1717.92 KB	↓
Application Note Connecting with an iPod Touch	30.03.2011 28.10.2011	zip 428.79 KB	↓
GRUNDFOS GENibus interface, application note	20.03.2017 20.03.2017	zip 279.86 KB	↓
Connection of Thermokon Multi-function room control units WRF 08	10.04.2019 10.04.2019	zip 855.84 KB	↓

Application Note CoDeSys 2.3			
Connection of DMX devices to the WAGO-I/O-SYSTEM via the ArtNet-DMX STAGE-PROFI 1.1	11.01.2013 11.01.2013	zip 1450.63 KB	↓
Connection of Thermokon Multi-function room control units WRF 06	10.04.2019 08.04.2016	zip 826.10 KB	↓
Application Note for the 750-494 3-Phase Power Measurement Module	24.01.2014 11.11.2014	zip 1629.99 KB	↓
Application Note: EnOcean_06 Library	30.11.2016 30.11.2016	zip 822.25 KB	↓
Application Note for the 750-495 3-Phase Power Measurement Module	24.01.2014 24.01.2014	zip 1806.18 KB	↓
Application Note Library WagoDatalogger_02	2020-05-20 20.05.2020	zip 1256.74 KB	↓
Application Note Weather Station Elsner P03 Modbus	01.12.2011 28.10.2011	zip 269.09 KB	↓
Application note: DALI 753-647 Configuration Interface	1.0.2 29.04.2019	zip 3032.71 KB	↓
HLK-Anlagenmakros für TRIC	2015-07-10 10.07.2015	zip 74963.43 KB	↓
Application Note Library ModuleAccess_01	05.01.2016 29.01.2016	zip 1001.22 KB	↓
Anwendungshinweis für die Steuerung eines Igus robolink	12.11.2015 12.11.2015	zip 1281.38 KB	↓



Application Note e!COCKPIT			
e!COCKPIT application note installation MyS-QL-Server	1.0.3 09.09.2019	pdf 1868.46 KB	↓
e!COCKPIT application note WagoAppCloud	2022-11-04 04.11.2022	zip 2678.52 KB	↓
HART Tool Routing via ETHERNET with 750-820x and e!RUNTIME (a116130)	1.0.0 22.03.2019	pdf 2867.01 KB	↓
SNMP Communication (a500850)	1.1.0 20.02.2020	zip 3743.05 KB	↓

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 750-8214 ↓	EPLAN Data Portal 750-8214 ↓
	ZUKEN Portal 750-8214 ↓

Engineering-Software			
Configuration and Commissioning Software			
WAGO-IO-PRO Demo-Version (759-912) / Serie 750, 758 und 762	V 2.3.9.68 17.02.2022	zip 122524.17 KB	↓
(759-316) WAGO Ethernet Settings / Serie 750	06.18.01.01 02.09.2021	zip 26678.54 KB	↓
WAGOupload	1.16.1.0 02.02.2022	zip 12111.45 KB	↓

Runtime Software			
Firmware			
Image Update (SD Karte) PFC100/200 für Codesys V2.3 u. Elcockpit	V 22 SP1 12.12.2022	zip 205815.20 KB	↓
PFC200, Firmware Update für CoDeSys V3.5	V 23 24.02.2023	zip 167985.38 KB	↓
WUP Update (WAGOuploadTool) PFC100/200 Codesys V2.3 u. Elcockpit	V 22 SP1 12.12.2022	zip 203580.70 KB	↓



Libraries				
Device Description File			Library	
750-914; EDS file for CANopen / 750, 752 and 767 Series	XT 12.03.2021	zip 1728.38 KB		
			WagoConfigToolLIB	1.0.0 08.10.2013
				pdf 340.92 KB
			WagoLibLed	1.0.0
				pdf 504.39 KB
			WagoLibNetSnmpManager	1.1.0
				pdf 1090.83 KB
			WagoLibDiagnosticIDs	1.0.0
				pdf 291.17 KB
			WagoLibCpuUsage	1.0.0
				pdf 259.51 KB
			Library WagoLib-Cloud_02.lib	2.2.4 21.01.2020
				zip 56.21 KB
			WAGO_Datalogger_02.lib	2.7 20.05.2020
				zip 662.90 KB

1 Compatible Products
1.1 Optional Accessories
1.1.1 Cables and connectors
1.1.1.1 Connector plug

Item No.: 750-979/000-011 Connector ETHERNET; RJ-45; Cat. 6A; angled; Code T568A; AWG 22; Strain relief	Item No.: 750-979/000-021 Connector ETHERNET; RJ-45; Cat. 6A; angled; Code T568A; AWG 24; Strain relief	Item No.: 750-979/000-012 Connector ETHERNET; RJ-45; Cat. 6A; angled; Code T568B; AWG 22; Strain relief	Item No.: 750-979/000-022 Connector ETHERNET; RJ-45; Cat. 6A; angled; Code T568B; AWG 24; Strain relief
Item No.: 750-977/000-011 Connector ETHERNET; RJ-45; Cat. 6A; straight; Code T568A; AWG 22	Item No.: 750-978/000-011 Connector ETHERNET; RJ-45; Cat. 6A; straight; Code T568A; AWG 22; Strain relief	Item No.: 750-977/000-021 Connector ETHERNET; RJ-45; Cat. 6A; straight; Code T568A; AWG 24	Item No.: 750-978/000-021 Connector ETHERNET; RJ-45; Cat. 6A; straight; Code T568A; AWG 24; Strain relief
Item No.: 750-977/000-012 Connector ETHERNET; RJ-45; Cat. 6A; straight; Code T568B; AWG 22	Item No.: 750-978/000-012 Connector ETHERNET; RJ-45; Cat. 6A; straight; Code T568B; AWG 22; Strain relief	Item No.: 750-977/000-022 Connector ETHERNET; RJ-45; Cat. 6A; straight; Code T568B; AWG 24	Item No.: 750-978/000-022 Connector ETHERNET; RJ-45; Cat. 6A; straight; Code T568B; AWG 24; Strain relief
Item No.: 750-975 ETHERNET RJ-45 connector, IP20; ETHERNET 10/100 Mbit/s; for field assembly	Item No.: 750-963 Fieldbus Connector CANopen; with D-sub female connector; 9-pole		



1.1.2 Communication

1.1.2.1 Communication cable



Item No.: 750-923
Configuration cable; USB connector;
Length: 2.5 m



Item No.: 750-923/000-001
Configuration cable; USB connector;
Length: 5 m

1.1.3 DIN-rail

1.1.3.1 Mounting accessories



Item No.: 210-196
Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslopped; similar to EN 60715; silver-colored



Item No.: 210-198
Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslopped; according to EN 60715; copper-colored



Item No.: 210-508
Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slopped; galvanized; similar to EN 60715; silver-colored



Item No.: 210-197
Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slopped; similar to EN 60715; silver-colored



Item No.: 210-506
Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslopped; galvanized; similar to EN 60715; silver-colored



Item No.: 210-114
Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slopped; similar to EN 60715; silver-colored



Item No.: 210-118
Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslopped; according to EN 60715; silver-colored



Item No.: 210-115
Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slopped; according to EN 60715; "Hole width 18 mm; silver-colored



Item No.: 210-112
Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slopped; according to EN 60715; "Hole width 25 mm; silver-colored



Item No.: 210-504
Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slopped; galvanized; according to EN 60715; silver-colored



Item No.: 210-113
Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslopped; according to EN 60715; silver-colored



Item No.: 210-505
Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslopped; galvanized; according to EN 60715; silver-colored

1.1.4 Marking

1.1.4.1 Group marker carrier



Item No.: 750-107
Group marker carrier

1.1.4.2 Marker



Item No.: 2009-145/000-006
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue



Item No.: 2009-145/000-007
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray



Item No.: 2009-145/000-023
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green



Item No.: 2009-145/000-012
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange



Item No.: 2009-145/000-005
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; red



Item No.: 2009-145/000-024
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet



Item No.: 2009-145
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white



Item No.: 2009-145/000-002
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow



Item No.: 248-501/000-006
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; blue



Item No.: 248-501/000-007
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; gray



Item No.: 248-501/000-023
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; green



Item No.: 248-501/000-017
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; light green



1.1.4.2 Marker



Item No.: 248-501/000-012
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; orange



Item No.: 248-501/000-005
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; red



Item No.: 248-501/000-024
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; violet



Item No.: 248-501
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white



Item No.: 248-501/000-002
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; yellow

1.1.4.3 Marker carrier



Item No.: 750-103
Group marker carrier

1.1.5 Memory card

1.1.5.1 Memory card



Item No.: 758-879/000-2108
Memory Card SD; pSLC-NAND; 8 GB; Temperature range: -40 to 90 °C



Item No.: 758-879/000-001
Memory Card SD; SLC-NAND; 2 GByte; Temperature from -40 to 90 °C

1.1.6 Shield termination

1.1.6.1 Shield clamping saddles



Item No.: 790-108
Shield clamping saddle; 11 mm wide; diameter of compatible conductor; 3 ... 8 mm



Item No.: 790-208
Shield clamping saddle; 12.4 mm wide; 3 ... 8 mm



Item No.: 790-116
Shield clamping saddle; 19 mm wide; diameter of compatible conductor; 7 ... 16 mm



Item No.: 790-216
Shield clamping saddle; 21.8 mm wide; 6 ... 16 mm



Item No.: 790-124
Shield clamping saddle; 27 mm wide; diameter of compatible conductor; 6 ... 24 mm



Item No.: 790-220
Shield clamping saddle; 30 mm wide; 6 ... 20 mm



Item No.: 790-140
Shield clamping saddle; diameter of compatible conductor

1.1.7 Software

1.1.7.1 Basic version



Item No.: 2759-101/1110-4000
e!COCKPIT; Buy-out License



Item No.: 2759-101/1110-2005
e!COCKPIT; Multi-User License; 05 pcs



Item No.: 2759-101/1110-2010
e!COCKPIT; Multi-User License; 10 pcs



Item No.: 2759-101/1110-2015
e!COCKPIT; Multi-User License; 15 pcs



Item No.: 2759-101/1110-2020
e!COCKPIT; Multi-User License; 20 pcs



Item No.: 2759-101/1110-3000
e!COCKPIT; Site License



Item No.: 2759-101/1110-2002
e!COCKPIT; Workstation License



Item No.: 759-333
WAGO-I/O-PRO



Item No.: 759-333/000-923
WAGO-I/O-PRO; USB-Set



1.1.7.2 Software Application



Item No.: 2759-120/1121-1000 e!COCKPIT MTP; Single License; Online activation	Item No.: 2759-245/211-1000 Library Controller Redundancy Master; Single License; Online activation	Item No.: 2759-208/211-1000 Library MTP; Single License; Online activation
---	---	--

1.1.8 System enclosure

1.1.8.1 System enclosure



Item No.: 850-825
IP65 enclosure; Aluminium (RAL 7032); WxHxD (160x100x160 mm); 9 x M12, 4 x M20



Item No.: 850-826
IP65 enclosure; Aluminium (RAL 7032); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip



Item No.: 850-827
IP65 enclosure; Aluminium (RAL 7032); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip



Item No.: 850-828
IP65 enclosure; Aluminium (RAL 7032); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip



Item No.: 850-826/002-000
IP65 enclosure; Aluminium (RAL 7035); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip



Item No.: 850-827/002-000
IP65 enclosure; Aluminium (RAL 7035); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip



Item No.: 850-828/002-000
IP65 enclosure; Aluminium (RAL 7035); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip



Item No.: 850-834
IP65 enclosure; Polyester (RAL 7032); WxHxD (164x100x164 mm); 9 x M12, 4 x M20



Item No.: 850-835
IP65 enclosure; Polyester (RAL 7032); WxHxD (244x100x164 mm); 4 x M20, 4 x M16, 14 x M12 cable grip



Item No.: 850-836
IP65 enclosure; Polyester (RAL 7032); WxHxD (324x100x164 mm); 4 x M20, 8 x M16, 17 x M12 cable grip



Item No.: 850-814/002-000
IP65 enclosure; Sheet steel (RAL 7035); WxHxD (200x120x200 mm); without flange plate



Item No.: 850-815/002-000
IP65 enclosure; Sheet steel (RAL 7035); WxHxD (300x120x200 mm); without flange plate



Item No.: 850-816/002-000
IP65 enclosure; Sheet steel (RAL 7035); WxHxD (400x120x200 mm); without flange plate



Item No.: 850-817/002-000
IP65 enclosure; Sheet steel (RAL 7035); WxHxD (600x120x200 mm); without flange plate